
Wireless I/O and Ethernet Connectivity Catalog



Product Portfolio



Wireless I/O and Ethernet Connectivity

Catalog 12

Product Overview	Introduction 3
Industry Applications	6
Application Notes	8
Application Examples	9
Wireless I/O	Unidirectional Transmitter/Receiver Units Introduction
	Transmitter (Single Sensor Units) Introduction
	Wireless Meshing I/O Units Introduction
	Multi-I/O Units Introduction
	Expansion I/O Units Introduction
	Wireless Gateways Introduction
Wireless Data Modems	Introduction .43 Serial Only Data .44 Ethernet and Serial Data .47 Ethernet Only Data .49 Licensed Frequencies .50
Enclosures	Specialty Enclosures
Cellular - Routers	Introduction
Wireless Accessories	Selection Guide 60 Connection Diagrams 64 Radiation Patterns 66 Product Data - Antennas 69 Product Data - Cables 90 Product Data - Hardware 92 Product Data - Adapters 94 Product Data - Filters 95
Ethernet	Product Data - Switches
Power Supplies	Product Data
Glossary	

Weidmuller Catalogs at a Glance

Catalog 1: **Modular Terminal Blocks**

- P-Series (Push-in)
- Power Distribution Blocks and Fuse Blocks
- Stud Style (Screw clamp)
- **Enclosures and Cable Glands** • Z-Series (Tension clamp)
- W-Series (Screw clamp)

Enclosures

Catalog 5:

- Cable Glands
- Cabtite (Cable Entry System)

Catalog 2: **PCB Terminals and Connectors**

- Space Saving Technologies
- Wide Variety of Clamping Technologies
- Pitches Ranging from 3.50 mm to 15.00 mm
- Orientations Ranging from 90° to 270°

Catalog 6: **Tools**

- Cutting Stripping
- Crimping
- Screwdrivers
- Automatic Machines
- Ferrules

Catalog 3: RockStar®- Heavy Duty Connectors

- Inserts
- Modular System
- Housings IP65 and IP68
- Cable Glands

Catalog 7: **Marking Systems**

- Terminal Markers
- Wire and Cable Markers
- Device and Equipment Markers
- · Printing Systems and Software

Catalog 4.1: **Analog Signal Conditioning**

- Intrinsically Safe Conditioners
- Signal Converters and Monitoring Devices
- Indicators and Configurable Displays

Catalog 8:

Sensor Actuator Interface JACKPAC® IP67

- SAI Passive Blocks
- SAI Universal
- · Cables and Connectors
- SALASI

Catalog 4.2: **Relays and Optocouplers**

- Mechanical Relays
- Solid-State (opto) Relays
- Power Solid-State Relays
- Multifunction Relays and Timers

Catalog 9: **Industrial Ethernet**

- Unmanaged Switches
- Managed Switches
- Routers
- Media Converters
- SteadvTEC®
- IE Connectors
- Accessories

Catalog 4.3: **Power Delivery**

- Power Supplies
- · UPS control units/battery back up units
- AC outlet DIN-Rail Mountable Receptacles

Catalog 10: **Industrial Connectivity**

- Short Form Catalog
- Product Overview

Catalog 4.4: **Surge Protection**

- Surge Protection for Low-Voltage
- Surge Protection for Instrumentation and Control
- · Surge Protection for Data Interfaces
- Surge Protection for Photovoltaic Systems

Catalog 11: **Circuit and Surge Protection**

- Circuit Breakers
- Overvoltage Protection
- AC Receptacles
- GFCI Outlets

Catalog 4.5: **Interface Units and PLC Solutions**

- Interface Units
- PLC Interfaces H-, R- and S-System
- Byte Precabling Solution

Catalog 12:

Wireless I/O and Ethernet Connectivity


- Wireless I/O and Ethernet
- · Wireless Gateways
- Wireless Transceivers
- · Antennas and Accessories

Types of Wireless Products

Product Overview

Weidmuller industrial wireless products provide secure and reliable solutions for a wide range of industries and applications, as an alternative for signal and data wiring. These products fall into four groups:

Wireless Meshing I/O, combines multi I/O and/or gateway functionality with the reliability of secure, scalable mesh distance communications. The IP-based addressing provides mesh/self-healing of network communications, multi-hop repeating and remote over the air re-configuration and diagnostics. The Meshing I/O units further complemented by its ease of commissioning and integration into existing plant infrastructure plus seamless interface with non-meshing systems.



Wireless Gateways provide wireless connectivity between data buses - connectivity between devices using the same data bus, or between different data buses (Ethernet to Profibus to DeviceNet to Modbus etc). Wireless gateways are similar in operation to wireless modems, however gateways only provide a register interface to the data bus, transferring I/O registers only.

Wireless Modems transmit serial or Ethernet data, providing a wireless extension of the data link. Example applications are PLC to PLC connections (point-to-point), connecting SCADA to a group of PLCs (point-to-multipoint), or forming a wireless PLC LAN (multidrop). Wireless modems transmit the data with minimal transformation.





Wireless Meshing I/O





Wireless I/O





Wireless Gateways





Wireless Modems

Wireless System Architecture


Weidmuller's solutions enable innovative WIB-net™ communications protocol specifically designed for highly reliable and secure operation on open license-free radio bands. Weidmuller wireless units form a WIB network—Wireless Information Backbone. A WIB is an effective plant-wide wireless information network for transferring data and connecting signals and data- buses in a highly efficient exception-reporting, peer-to-peer network. WIB-net provides the following features:

Exception-reporting transmissions for maximum wireless efficiency

Wireless messages are only transmitted whenever a signal value changes, yielding effective real-time performance. Integrity check messages ensure reliable operation of the wireless network as well as signal link accuracy. Exception-reporting reduces signal traffic to messages of only real significance.

Error-checking with automatic re-transmission for high reliability operation

Every radio message has a probability of corruption, so automatic error detection, acknowledgement and re-transmission is critical to reliable operation.




Event-driven communication

WIB-net will send and then re-transmit up to five times. After the fifth attempt, a communication failure status is logged and an alarm set externally.

 Listen-before transmit wireless operation to maximize the chance of successful message transmission

Peer-to-peer networking for maximum network flexibility

Each Weidmuller wireless gateway and transceiver unit can transmit/receive directly to/from any other wireless gateway and transceiver, and can transmit/receive to/from multiple




Peer-to-Peer Example

wireless units. There are no master units and no slaves. Any module in a network can talk to any other. Input signals can be transmitted to multiple destinations.

· Wireless mesh structure

WIB-net enables every Weidmuller wireless gateway/ transceiver to act as a repeater to optimize wireless message propagation. Messages can hop through multiple gateway/transceiver units to reach a destination. If these units have a reliable wireless link to at least one other gateway/transceiver, a wireless mesh forms to enable reliable links to the whole network.



· High security encryption

WIB-net uses a highly secure data encryption technique to protect against misuse of wireless data. Weidmuller wireless networks security matches or exceeds that of wired networks.

Input/Output Mapping

Process signals or sensors convey the value of an input value to a designated output channel:

- System address (15-bit, 1 32768)
- Source module address (1 127)
- Destination module address (1 127)
- Repeater addresses (up to 5 addresses)
- Output channel number
- I/O signal value (16-bit)
- CRC error-checking (16-bit)

All modules in the same system share a unique system address to avoid cross-talk between systems in the same radio environment. The configuration software automatically generates a random system address for each system.

Destination or repeater modules automatically acknowledge messages when received with a correct error-check value, except for messages from transmit-only units. If an acknowledgement is not received within 500 milliseconds, the message is re-transmitted. The message will be transmitted up to five times with random re-try times. After the fifth attempt, a "comms-fail" event will be set, which can be used to trigger an output alarm or register.

Block Messages

Block messages are similar to other transmissions. However, signal information is condensed into "blocks" and these blocks are sent at programmed intervals. Each block message contains up to 64 x 16-bits of values. Block messages are only transmitted or repeated by the wireless gateway product range (D2 W GMD).

Discrete/digital values can be packed [i.e. up to 1024 (64 x 16)] into a block message and unpacked at the destination gateway.

Block messaging creates a more robust, reliable and efficient system by reducing the chance that messages will become corrupt and by minimizing radio frequency congestion.

Message Control

The WIB-net[™] protocol is based on exception-reporting for optimum performance. Messages can be triggered by any of the following:

- Exception change in input value compared to userconfigurable "sensitivity" values
- Update time user-configurable time period since the last message, individually configured for each I/O register
- Real time block mappings only; messages transmitted on real time values
- On demand block mappings only; poll command from another wireless unit or write command by a connected databus device


Before a message is transmitted, the radio channel is checked to ensure it is clear (listen-before-transmit). The message is preceded by a lead-in transmission; the length depends on the radio model to allow all other units to lock onto the transmitted message.

Security Encryption

Security encryption of wireless messages is user-selectable. A 64-bit secure proprietary encryption algorithm is used. The 64-bit key is randomly generated by the configuration software and is never disclosed to the user or transmitted by radio. Configuration files are protected by password, up to 256 characters.



Oil and Gas Applications




From the control room to the field, wireless solutions provide a wireless control infrastructure for productivity and safety gains in oil and gas applications.

Wireless benefits:

- **Long range:** Current frequencies allow for 20–50 km LoS between clients
- High speed: Up to 50 Mbps bandwidth
- Secure: Military-grade security encryption
- Rugged: Weatherproof casing
- **Reliable:** Advanced, self-healing meshing technology provides high availability
- Easy deployment: Deploys more easily and can be redeployed more quickly when compared to wired installation
- **Cost-effective:** Lower installation costs and longer, faster equipment uptime

More than Wireless








	Production	Separation / Refining	Storage	Distribution	Upgrading
Circuit Protection	•			•	•
Industrial Ethernet				•	
Intrinsic Safety		•		•	
Junction Boxes			•		
Marshalling Solutions		•			
Mechanical and Solid State Relays		•			
Power Supplies and UPS		•			
Printing / Marking Systems	•				•
Signal Isolation and Conditioning		•	•		
Surge and Lightning Protection	•		•	•	•
Terminal Blocks	•		•		•
Wireless Communication	•	•	•		•
Wireless Monitoring			•		•
Wireless Technology				•	

Water and Waste Water Applications




Wireless solutions reduce remote installation costs up to 70% and communicate reliable, secure EPA compliance data for system locations including:

- Head Works, Main Lift Stations, Remote Lift or Pumping Stations
- Storm Sewer Overflow, Sanitary Sewers and Collection Pits
- Effluent Discharge Points: River, Lake and Wetlands Re-use
- Transportation and Paved Runoff Areas
- Potable Water Storage and Processing
- · Security and Surveillance

Wireless benefits:

- Optimizes response times and immediately indicates critical diagnostic information
- Improves monitoring and control of water flow over extended distances
- Improves operator safety and efficiency by eliminating travel time to remote site locations
- Reduces labor expenses and maximizes efficiency
- Simplifies installation and commissioning of network with reduced infrastructure required
- Provides enhanced reliability through a flexible network topology that can self-heal, while easing future expansion

More than Wireless



	Head Works	Influent	Aeration	Treatment	Effluent
Circuit and Surge Protection	•		•		
Distribution Blocks				•	
Engineered Systems				•	
Industrial Ethernet Networks		•			•
Interface Systems		•			
Intrinsic Safety	•		•	•	
Mechanical and Solid State Relays					•
Power Supplies and Battery Backup	•	•			•
Printing / Marking Systems / Ferrules			•		
Signal Conversion and Isolation			•	•	
Terminal Blocks		•			
Wireless Communication			•		•
Wireless Systems		•			
Wireless Technology	•			•	

Application Notes


Factors Affecting Distance & E.R.P

- Frequency (as frequency increases, distance decreases proportionally)
- · Receiver sensitivity, antenna gain, cable loss
- Noise / interference (the noisier the environment the more careful you have to be with antenna placement)
- Transmitter power, antenna gain, cable loss
- Attenuation of radio signal
- · Heights of antennas, Obstructions in radio path
- · Other factors Atmospheric, Ground Mineralization

In most applications it is desirable to have an overall dB gain as opposed to a loss to ensure good communication between radios.

Gain Sources	
Radios	1 W radio = 30dB Gain
	300mW radio = 24dB Gain
	100mW radio = 20dB Gain
Antennas	(see antenna selection chart for Antenna dB Gains)

Points of Loss	
Connection points	~0.1dB loss per connection
Jumper cables	see cable selection section (p. 64)
Surge Protection	see surge protection section (p. 65)
Bulkhead adapters	see Bulkhead Adapter section (p. 65)



*Sample assembly showing radios, power supply, surge arrestor (bottom of cabinet), terminals & relays.

WIBnet

WIBnet makes use of all the standard features of the Weidmuller Wireless radios.

Exception-reporting transmission for maximum wireless efficiency.

Wireless messages are only transmitted whenever a signal value changes, yielding effective real-time performance.

- Error-checking with automatic re-transmission for high reliability operation.
- Listen-before-transmit wireless operation to maximize the chance of successful transmission.
- Peer-to-peer networking, giving the maximum network flexibility.


WIBnet communications protocol is specifically designed for highly reliable and secure operation on open license-free radio bands.

WIBnet provides the following features:

- Any of the 900Mhz I/O or Gateway radios can be used on the WIBnet system
- Up to 95 radios can be put into one network

Messages can hop through multiple units to reach a destination providing each Wireless I/O unit has a reliable wireless link to at least one other unit. A wireless mesh forms to ensure reliable links are established within the whole network.

Wireless system flexibility and scalability



Application Examples

Remote Wastewater Overflow Protection

Company: JEA, City of Jacksonville, Florida Introduction

JEA is the municipal utilities provider for Jacksonville Florida. They were facing a problem with sanitary sewer overflows (SSO) in the downtown section of Jacksonville. Avoiding sewage overflow, aside from being a safety, environmental and public relations necessity, is good business for JEA.

Objective

The engineers at JEA needed a way to monitor underground sewer levels throughout the city. The plan involved the placement of measuring devices in strategically located manholes around the city in order to monitor the various fluid levels at each location.

This approach required the city to install power and control circuits at the strategic locations. Since the manholes were proven to be a very harsh Class 1, Division 1 environment, they knew that the solution was not going to be easy. JEA had already invested in a very robust SCADA system to control and monitor over 1200 lift stations. The end goal was to locate a monitoring system from the sewer manhole to the existing SCADA system.

About

The issue faced by Jacksonville in establishing a monitoring system is that the city itself is physically in the way—buildings, bridges, communication lines, power lines and other typical city fixtures. They would need to dig up most of the downtown at a cost of millions of dollars and months of traffic congestion and delays. The idea was proposed to monitor the manholes and their levels wirelessly. This solution could provide the city with a quick way to install a solution that would not require the demolition of the entire city.

A search was conducted to determine who could provide a solution that fit a very specific list of requirements. These requirements included the necessary power to send signals through the ground and steel manhole covers wirelessly to receivers located in control cabinets within the city; the need for ultra low power consumption; the ability to power the solution via batteries; be contained in a Class 1, Division 1 enclosure; the ability to send both analog and discrete signals; and be portable so it could be moved to different locations in the city as needed. After extensive field tests and evaluations for signal strength and durability, along with careful evaluation of different types of equipment, a Weidmuller wireless solution was selected.

The components of the solution include a compact, easy-to-use wireless transmitter (WI-I/O-9-K), coupled with its matching battery pack (WI-BP-I/O-9-K), which does not require any special OEM batteries. The wireless transmitter sends analog and discrete signals to a wireless transceiver (WI-I/O 9-4). This unit collects the data from each transmitter and forwards it via a wired connection into the JEA's SCADA application. The receiver works very well with the existing SCADA system. The programming software for the devices is provided for free via web down load and is easy to use and understand.

The software that is included with each device makes it simple for JEA to map the transmission of signals and control transmit schedules, thus prolonging battery life. Based on the level of power consumption, JEA could replace the batteries once a year, however, they have implemented a proactive battery maintenance program to change out the batteries (standard AA sized Alkaline) every 6 months.


These wireless devices are mounted in a Class 1, Division 1 explosion proof enclosure with a small external antenna. Each enclosure unit is then placed in a cradle within the manhole. Portability is an important feature because it allows JEA to redeploy each wireless radio in other locations in the city as needed.

The transmitter sends signals from each underground manhole installation to set receivers through the downtown area. JEA teamed with a local distributor and packaged the Weidmuller radio system, enclosure, terminals and equipment needed to meet application requirements of this monitoring system.

Outcome

This wireless manhole monitoring system has been used in 17 manholes in Jacksonville. It was implemented in just six months at a savings of millions of dollars and many months of time, versus a wired solution.

The system has proven to be a very successful solution to an important problem. Since the implementation of the manhole monitoring system, JEA has successfully prevented numerous manhole sanitary sewer overflows (SSO), thus protecting the public and the environment—a top priority for JEA and the city.



Remote Pumping Station Monitoring

Company: Pemex, Coatzacoalcos, Mexico

Introduction

Petroleos Mexicanos (PEMEX) is Mexico's state-owned petroleum company. It is the tenth largest oil company in the world in terms of revenue and ranked thirty-fourth in Fortune 500 companies. The company controls the entire oil industry for the nation of Mexico. This includes extraction, storage, refining and marketing to the public.

Objective

The engineers at PEMEX needed to monitor 200+ different remote pumping stations and compressors. The pumping stations are scattered over a 180 square mile area that is covered in very dense forest growth, making the transmission of wireless signals a real challenge. The pumping stations are physically clustered into four groups. Each group has approximately 50 pumping/monitoring locations. These groups are Reforma, Castano, Planta de Agua Samaria and Comalcalo. Each of the remote pumping locations covers an area of 37 square miles. These four remote areas with pumping stations need to send signals back to a central office location.


Solution

Weidmuller designed a solution that uses wireless Ethernet modems (WI-MOD-E) at each pumping location (Level 3) to acquire and transmit the requested information to a central point in each of the four pumping areas (Level 2). Another identical Ethernet modem is used to transmit all the needed information from each central point in each pumping area back to the Central Control office (Level 1). The Weidmuller modems, with 300mW broadcast power, were the only ones with a powerful enough transmitter to penetrate the dense forest growth with a clear and reliable wireless signal.

Each wireless Ethernet modem communicates between each pump location (Level 3) to each central pumping section (Level 2) and back to the Central Office (Level 1) via ModBus TCP. The components used in this installation include 250 Ethernet modems (WI-MOD-E), 5 unmanaged Ethernet switches, 5 Ethernet routers, 250 DC-DC converting power supplies (to isolate radios from the rest of the system) and all necessary terminal and fuse blocks to complete the system connectivity.

Outcome

PEMEX now has a simple easy-to-use solution for monitoring their remote pumping stations. They were able to deploy this solution quickly and it was up and running in a matter of months. Training and maintenance is streamlined because the solution employs one type of product, using one software interface for all three levels of their system, from 200+ remote stations to the central office location. The wireless products were coupled with other Weidmuller components, providing a complete and seamless system that is easy for PEMEX to maintain and support.



Weldmüller ¾

Wireless Remote Vehicle Control

Company: Meggitt Training Systems, Inc.

Company Profile

Meggitt Training Systems, Inc.(MTSI), a part of Meggitt Plc, provides training systems used by militaries, law enforcement and security agencies around the world. They develop, manufacture, market and service high quality virtual and live fire training systems. MTSI employs over 500 people at their headquarters in Atlanta and in other facilities in Australia, Canada, Singapore, the Netherlands, the UAE and the United Kingdom. They are the industry leader of interactive simulation systems for the handling and use of small and supporting arms training.

Overview

Meggitt designed and installed one of the most advanced live fire ranges ever provided to the U.S. Military. The range, installed and operating in Fort Carson, Colorado, is a digitally controlled heavy armor range. It is comprised of 14 moving targets located across a 60 square kilometer area. Each of the 14 moving targets includes one bunker location and a separate remote vehicle or mover. The bunkers are made of reinforced concrete and contain the technology to operate the movers including a wireless Ethernet modem.

The mover is a 3000 lb. vehicle that is mounted onto a raised metal track. This remote vehicle has four lift arms that enable it to raise and lower a target, which is a silhouette of an armored vehicle. A control box located on the mover contains another wireless modem and the circuitry to operate the drive motors and the lift arms of the vehicle. The raised metal tracks vary in length from 300 to 500 meters, depending on the range. Each of the 14 moving target ranges is controlled via Ethernet signals from a central Range Operations Center (ROC).

Problem

Meggitt faced two major problems at the Fort Carson, Colorado range. The first challenge was environmental. Operating conditions on a live fire heavy armor range are not favorable to electronic equipment– especially highly sensitive, high technology wireless devices. The temperature inside the control box on each mover varies from -40°C (-40°F) in the winter to +65°C (+149°F) in the summer months. In addition to temperature issues, operating on a range with tanks firing live ammunition necessitated a wireless device that withstands shock and vibration.

The second challenge was to secure reliable and stable wireless communication between each bunker location and its respective mover. The mover needs to be controlled at every point along its track so it can move in either direction, stop, raise and lower the target. The mover rolls on a set of raised tracks that extend away from the bunker at a distance of 300 to 500 meters, with various elevation changes and turns. Normally, a large antenna placed at each bunker and on each mover would solve any signal communication issues. However, the antennas at Fort Carson could not extend beyond the protective wall that guarded each mover from the live ammunition.

Solution


Weidmuller's WI-MOD-E-300 modems were tested and selected for the application because of their ability to operate within the required temperature ranges. They were also the most powerful production 802.11b modems available. Weidmuller sent a team to Fort Carson to install ten WI-MOD-E-300 wireless modems at 5 bunker-mover locations. The modems were installed using antenna and connecting cables that were already on-site from a previous vendor. Signal strength was improved and the Weidmuller team was able to get four of the five ranges communicating successfully.

The new installations were tested for several months after installation and it was determined that communications were not as consistent as desired. The Weidmuller team returned to Fort Carson and performed extensive site surveys at each of the 14 different bunker-mover locations. This information enabled an accurate diagnosis of each installation and the results determined that the previously installed cables and antennas were at fault. They had not been properly installed by the previous vendor and in some cases incorrect cables and antennas had been used. The Weidmuller team developed a solution to correct the communication issues at each range location. The recommended solution was accepted by Meggitt Training Systems and installed.

In order to streamline the support and spare parts management for the Fort Carson range, all of the components and equipment used for each bunker-mover location are identical. The technology solution includes a WI-MOD-E-300 wireless Ethernet modem, WI-ACC-LMR400-55FT jumper cable and a WI-ANT24GHz-4DB ONMI antenna. Each mover is equipped with a matching WI-MOD-E-300 wireless Ethernet modem, WI-ACC-LMR195-3FT jumper cable and a WI-ANT-24GHZ-4DB OMNI antenna.



Wireless Ethernet Modem mounted within an enclosure located inside bunker




Wireless Ethernet Modem mounted inside

Outcome

Weidmuller and Meggitt Training Systems have replaced all of the original faulty modems from a previous vendor and installed all new connecting cables and Omni antennas in each bunker and on each mover. The entire range is up and fully operational, providing solid data and control connections for each of the 14 bunker-mover locations. MTSI considers their Fort Carson digital range installation a complete success and the U.S. military is actively using the range as a testing facility for tanks and other armored vehicles.



Mover with target raised



Weidmuller Wireless Ethernet

Company: Targa Energy

Overview

Targa Energy owns and/or operates over 11,300 miles of natural gas gathering pipelines and Liquefied Natural Gas (NGL) pipelines through the states of Texas and Louisiana. These pipelines cover a total area of over 14,400 square miles. Targa also operates 22 natural gas processing plants, with a total of over 10,250 MMcf/d of gross processing capacity. In addition to these gathering systems and processing plants, Targa manages an onshore plant facility that provides access to natural gas supplies in the Permian Basin, Fort Worth/Bend Arch Basin, South Louisiana Basin, deepwater and deep shelf Gulf of Mexico.

Problem

The Targa Energy gas plant in Chico, Texas is a multi function location that performs pumping, storage and processing for the natural gas industry. This location covers several square miles, and includes a compressor station and multiple remote pumping stations located around the plant. Most of the pumping stations are very remote and have no access to the plant's communication network. Some of the pumping stations have a satellite uplink that is only used for processing data, production logistics and safety information.

Targa required a solution that could provide network access to their compressor station and numerous pumping station locations, and make a significant section of their gas plant a "Hot Spot" for broadband Ethernet access. Targa's field technicians would require access to this broadband network to conduct system monitoring, access data files and connect with other offices or company resources via the company's Intranet network. The field technicians use laptop computers, therefore a 2.4GHz (WiFi) wireless frequency was necessary.

Targa was having difficulty achieving reliable and stable connections due to the distance between the pumping stations, the compressor station, and the plant (over 3.5 miles in some cases) and the need to use the 2.4GHz (WiFi) spectrum for field technician access.




Solution

At Targa's request, Weidmuller's application engineer visited the plant location and performed a wireless Ethernet site survey. After the site survey was completed, a solution was proposed that included a combination of wireless Ethernet modems (WI-MOD-E-300) and dipole antennas with 3dbi of gain. The Ethernet modems provided the needed level of powerful signal transmission, and combined with a sensitive high performance signal receiver, Targa was able to receive the necessary signal strength and reliability required for their locations.



This wireless solution provides the required "Hot Spots" for service technicians to access the Intranet network with their laptops, as well as enabling connectivity between Targa's base station locations and several remote pumping stations for an added level of communication and information exchange.

Compressor Station



Unidirectional Transmitter/ Receiver Units – Introduction

Wireless Input/Output (I/O)

Wireless I/O connects directly to analog, discrete and pulse transducer signals. The signals are transmitted by radio and either re-created as output signals, or output via serial link or field-bus.

Weidmuller Wireless I/O units have the ability to form sophisticated peer-to-peer networks, with event-reporting messaging to optimize wireless density. Weidmuller products are designed for high reliability operation on open license-free radio bands.

WI-I/O 9-L Unidirectional Transmitter/Receiver Units

The Unidirectional Wireless I/O range of products is suitable for connecting to a single sensor or group of sensors and provides an economical solution for remote monitoring systems. The Unidirectional L products can also be used in more complex networks as signal transmitters or receivers.

- Frequency hopping spread spectrum 902-928 MHz 1W license-free USA/Canada/Mexico
- Configurable sub-bands license-free South America, Australia/NZ, Asia, Europe

Applications

- Wireless connection of flowmeters or energy meters
- · Monitoring storage tanks
- Monitoring cathodic protection on pipelines
- · Wireless alarms from power reticulation fault relays



Features


Matched transmitter/receiver pair of modules, or individual transmitter and receiver units

- Peer-to-peer communications. Exception reporting.
 Reliable self-checking messages. Highly secure data encryption.
- Multi-hop repeater functions up to 5 intermediate units can be configured in any input-output link
- Factory configured as a matched Transmitter/Receiver pair or user-configurable with E-Series Windows configuration program




Transmitter unit

- Input-only transmitter unit two digital/pulse inputs, one analog input and one thermocouple mV input
- Transmits to Receiver unit as a matched pair where the input signals are re-created as output signals, or can transmit to a Multi-I/O or Gateway unit
- Class 1 Div 2 hazardous areas approval
- Up to 3000 wireless units per network
- External inputs plus internally calculated values analog setpoint status, pulse count, power supply voltage
- Thermocouple input –20 to +100mV with cold-junction compensation and linearization for J, K or T-type
- Setpoints status generated by comparing analog input to high and low setpoints
- Digital inputs can also be used as pulse count inputs
- Power supply 9 30VDC, measured and available as a transmitted variable
- 24VDC analog loop supply internally provided
- · RS232 Configuration and diagnostics port



Receiver unit


- Output-only receiver unit three digital contact outputs and one analog output
- Receives radio commands from Transmitter unit as a matched pair where the input signals are re-created as output signals, or can receive commands from a Multi-I/O or Gateway unit
- Class 1 Div 2 hazardous areas approval
- · Up to 3000 wireless units per network
- Power supply 9 30VDC; 24VDC analog loop supply internally provided
- Communications failure indication and configurable output
- Outputs can be configured as retained or reset (fail-safe) on communications failure
- · LED indication of radio signal strength
- RS232 Configuration and diagnostics port



Transmitter/Receiver Unit Ordering Information

Unit	Description
WI-I/O 9-L-T	Wireless Transmitter (900 MHz)
WI-I/O 9-L-R	Wireless Receiver (900 MHz)
WI-I/O 9-L-P1	900 MHz Wireless Transmitter/ Receiver Pair with two -2 dB Dipole Antennas
WI-I/O 9-L-P2	900 MHz Wireless Transmitter/ Receiver Pair with two 0 dB Dipole Antennas

Dimensions



General

- Frequency: frequency hopping spread spectrum 902-928MHz, sub-bands available, 1W
- Sensitivity: line-of-sight range 20 miles (4W ERP "effective radiated power"), 15km (1W ERP); 3000 ft
 /1000 m in obstructed industrial environments; radio
 distances can be increased by up to 5 intermediate
 transceiver or gateway units
- Antenna Connector: SMA connector for antenna or coaxial cable connection
- Temperature: -40 to 60°C / -40 to 140°F

- Humidity: 0 99% RH
- Regulatory Approvals: EMC compliant 89/336 EEC, EN 301 489, AS3548, FCC Part 15, Approved to FCC Part 15.247, RS210
- **Housing:** DIN-rail thermo-plastic enclosure 100 x 22 x 120 mm / 3.9 x 0.9 x 4.7 inches
- Transmitter Unit: Power/OK, radio TX, DIN1, DIN2, analog set-point status
- Receiver Unit: Power/OK, radio RX, DO1, DO2, DO3, communications fail LEDs also used to provide radio signal strength indication

Transmitter Inputs

Input Type	Source	Function
Digital	external	status
Pulse Total	external	count
Analog	external	analog
Thermocouple	external	analog
Set Point	internal	status
Supply Voltage	internal	analog

Input values transmitted as per WIB-net (see page 8) protocol - exception-reporting on signal change, and update time. Up to 5 repeater addresses, configurable.

Digital / Pulse Inputs

 Two inputs, suitable for voltage-free contacts / NPN, or voltage input 0-1 VDC on / >3 VDC off pulse input max. rate 10 Hz, 50 msec on time. Pulse counted as 16-bit register.

Analog Inputs

- 0-20 mA (4-20mA)
- "Floating" differential input, resolution 16-bit, accuracy < 0.1 %

Thermocouple Inputs

- Millivolt (-20mV to +100mV), J, K, or T type linearization with on-board cold-junction compensation
- Accuracy better than 1°C

Power Supply

- Normal Supply: 9 30 VDC, power consumption @12VDC - receiver normal 70mA, max. 250mA
- · Transmitter normal 70mA, transmitting max. 600mA
- Analog loop supply internally generated, 24VDC 35mA
- Internal monitoring of supply voltage may be transmitted as an "input" (transmitter unit only)

Set-point Status

- High and low set-points generate internal digital statusset-point status sets (on) when analog value < low setpoint and resets (off) when analog value > high set-point.
 Status is transmitted as per digital input, set-point values are set via the front panel rotary switch or configuration software.
- Separate set-points for (4-20 mA), thermocouple and supply inputs are configurable

Receiver Outputs

Digital Outputs

• Three relay contact outputs, 260V 1A

Analog Outputs

 0-20mA, source output, 12-bit resolution, 0.1% accuracy

Communication Failure

- · Internal status based on configurable time-out value
- "Comms-fail" status can be configured to a local output

Fail-Safe

 On "comms-fail," outputs user-configurable as retained last correct value or reset (fail-safe)

Serial Port

RS232 RJ45 female DCE, used for configuration and diagnostics

LED Indication

Transmitter Unit

 Power/OK, radio TX, DIN1, DIN2, analog set-point status

Receiver Unit

- Power/OK, radio RX, DO1, DO2, DO3, communications fail
- LEDs also used to provide radio signal strength indication

Configuration and Diagnostics

- Factory configuration transmitter/receiver matched pair, AI to AO, 2DI to 2DO, SP status to DO3 via RS232 - RJ45 cable
- User configuration via serial port. Unidirectional units can be configured to network with multi-I/O and gateway units.
- Diagnostics features: read input values, write output values, radio signal strength, monitor communication messages



WI-I/O 9-L-T Transmitter









Technical Data Transmitter Inputs

Transmitter Inputs		
Digital	two inputs, suitable for voltage free contacts / NPN, or voltage input 0-1 VDC on / >3 VDC off	
Pulse	max rate 10 Hz, 50 msec on time. Pulse counted as 16 bit register.	
Analog	0-20 mA (4-20mA)	
"floating" differential input:		
resolution	16 bit	
accuracy	< 0.1 %	
Thermocouple	Millivolt (-20mV to +100mV), J, K or T type linearization with on-board cold-junction compensation	
Accuracy	greater than 1°C	
Receiver Outputs		
Digital		three relay contact outputs, 260V 1A
Analog		0-20mA
resolution		12 bit
accuracy		0.10%
Comms-Fail		Internal status based on configurable time-out value. Comms-fail status can be configured to a local output.
Fail-safe		On "comms-fail", outputs user-configurable as retained (last correct value) or reset (fail-safe)
Power Supply	9-30 VDC	9-30 VDC
Power consumption @12VDC	Receiver 100mA, Transmitter 40mA quiescent, during radio transmission (50 msec) 300mA	Receiver 100mA, Transmitter 40mA quiescent, during radio transmission (50 msec) 300mA
Analog loop supply internally generated	24VDC 30mA	24VDC 30mA
Internal monitoring of supply low voltage status	may be transmitted as an "input" (Transmitter unit only)	
Power consumption increases for pulse inputs > 10Hz.		
Serial Port	RS232 RJ45 female DCE, used for configuration and diagnostics	RS232 RJ45 female DCE, used for configuration and diagnostics
General Data		
Operating Temperature	-40 to 60°C (-40 to 140°F)	-40 to 60°C (-40 to 140°F)
Humidity	0 - 99% RH	0 - 99% RH
EMC Standards	FCC Part 15.247, RS210	FCC Part 15.247, RS210
Mounting	DIN-rail mounting	DIN-rail mounting
LED indication: Transmitter Unit	Power/OK, Radio TX, DIN1, DIN2, Analog Setpoint status	
LED indication: Receiver Unit		Power/OK, Radio RX, DO1, DO2, DO3, Communications Fail.
frequency hopping spread spectrum	902-928MHz, sub-bands available	902-928MHz, sub-bands available
Transmit power	1W	1W
Maximum line of sight range	20 miles (4W ERP), 15km (1W ERP); 3000 ft / 1000 m in obstructed industrial environments. Radio distances can be increased by up to 5 intermediate repeater units. Each transmission may be configured to be sent 1 to 5 times.	20 miles (4W ERP), 15km (1W ERP); 3000 ft / 1000 m in obstructed industrial environments. Radio distances can be increased by up to 5 intermediate repeater units. Each transmission may be configured to be sent 1 to 5 times.
Antenna connector	SMA female coaxial	SMA female coaxial
Dimensions mm (in)	100 x 23 x 120 (3.9 x 0.9 x 4.7)	100 x 23 x 120 (3.9 x 0.9 x 4.7)
Configuration	User configuration via serial port. Unidirectional units can be configured to network with Multi-I/O and Gateway units.	User configuration via serial port. Unidirectional units can be configured to network with Multi-I/O and Gateway units.
Diagnostics	Diagnostics features - read input values, write output values, radio signal strength, monitor communication messages.	Diagnostics features - read input values, write output values, radio signal strength, monitor communication messages.

Ordering Data

	Туре	Part No.
	WI-I/O 9-L-T	6720005005
Accessories: DB9 Female-RJ45 Serial configuration cable	WI-CSER-RJ45	6720005108

Туре	Part No.
WI-I/O 9-L-R	6720005006
WI-CSER-RJ45	6720005108

°C1D2

WI-I/O 9-L-P1 Set - 1 Transmitter, 1 Receiver



WI-I/O 9-L-P2 Set with 2 WI-ANT-DPL-0-8



Technical Data

Transmitter Inputs		
Digital	two inputs, suitable for voltage free contacts / NPN,	two inputs, suitable for voltage free contacts / NPN, or
D. I.	or voltage input 0-1 VDC on / >3 VDC off	voltage input 0-1 VDC on / >3 VDC off
Pulse	max rate 10 Hz, 50 msec on time. Pulse counted as 16 bit register.	max rate 10 Hz, 50 msec on time. Pulse counted as 16 bit register.
Analog	0-20 mA (4-20mA)	0-20 mA (4-20mA)
"floating" differential input:		
resolution	16 bit	16 bit
accuracy	< 0.1 %	< 0.1 %
Thermocouple	Millivolt (-20mV to +100mV), J, K or T type linearization with on-board cold-junction compensation	Millivolt (-20mV to +100mV), J, K or T type linearization with on-board cold-junction compensation
Accuracy	greater than 1°C	greater than 1°C
Receiver Outputs Digital	three relay contact outputs, 260V 1A	three relay contact outputs, 260V 1A
Analog	0-20mA	0-20mA
resolution	12 bit	12 bit
accuracy	0.10%	0.10%
Comms-Fail	Internal status based on configurable time-out value. Comms-fail status can be configured to a local output.	Internal status based on configurable time-out value. Comms-fail status can be configured to a local output.
Fail-safe	On "comms-fail", outputs user-configurable as retained (last correct value) or reset (fail-safe)	On "comms-fail", outputs user-configurable as retained (last correct value) or reset (fail-safe)
Power Supply	9-30 VDC	9-30 VDC
Power consumption @12VDC	Receiver 100mA, Transmitter 40mA quiescent, during radio transmission (50 msec) 300mA	Receiver 100mA, Transmitter 40mA quiescent, during radio transmission (50 msec) 300mA
Analog loop supply internally generated	24VDC 30mA	24VDC 30mA
Internal monitoring of supply low voltage status	may be transmitted as an "input" (Transmitter unit only)	may be transmitted as an "input" (Transmitter unit only)
Power consumption increases for pulse inputs > 10Hz.		
Serial Port	RS232 RJ45 female DCE, used for configuration and diagnostics	RS232 RJ45 female DCE, used for configuration and diagnostics
General Data		
Operating Temperature	-40 to 60°C (-40 to 140°F)	-40 to 60°C (-40 to 140°F)
Humidity	0 - 99% RH	0 - 99% RH
EMC Standards	FCC Part 15.247, RS210	FCC Part 15.247, RS210
Mounting	DIN-rail mounting	DIN-rail mounting
LED indication: Transmitter Unit	Power/OK, Radio TX, DIN1, DIN2, Analog Setpoint status	Power/OK, Radio TX, DIN1, DIN2, Analog Setpoint status
LED indication: Receiver Unit	Power/OK, Radio RX, DO1, DO2, DO3, Communications Fail.	Power/OK, Radio RX, DO1, DO2, DO3, Communications Fail. LEDs also used to provide radio signal strength indication
frequency hopping spread spectrum	902-928MHz, sub-bands available	902-928MHz, sub-bands available
Transmit power	1W	1W
Maximum line of sight range	20 miles (4W ERP), 15km (1W ERP); 3000 ft / 1000 m in obstructed industrial environments.Radio distances can be increased by up to 5 intermediate repeater units. Each transmission may be configured to be sent 1 to 5 times.	20 miles (4W ERP), 15km (1W ERP); 3000 ft / 1000 m in obstructed industrial environments. Radio distances can be increased by up to 5 intermediate repeater units. Each transmission may be configured to be sent 1 to 5 times.
Antenna connector	SMA female coaxial	SMA female coaxial
Dimensions mm (in)	100 x 23 x 120 (3.9 x 0.9 x 4.7)	100 x 23 x 120 (3.9 x 0.9 x 4.7)
Configuration	Factory configuration transmitter/receiver matched pair, Al to AO, 2DI to 2DO, SP status to DO3. User configuration via serial port. Unidirectional units can be configured to network with Multi-I/O and Gateway units.	Factory configuration transmitter/receiver matched pair, Al to AO, 2DI to 2DO, SP status to DO3. User configuration via serial port. Unidirectional units can be configured to network with Multi-I/O and Gateway units.
Diagnostics	Diagnostics features - read input values, write output values, radio signal strength, monitor communication messages.	Diagnostics features - read input values, write output values, radio signal strength, monitor communication messages.

Ordering Data

 Type
 Part No.

 Kit Contents
 WH/O 9-L-P1
 6720005007

- Two -2 dB Dipole antennas (6720005086)
- Two 3 ft. antenna connecting cables/brackets
- One configuration cable

 Type
 Part No.

 WI-I/O 9-L-P2
 6720005008

- Two 0 dB Dipole antennas (6720005080)
- Two 15 ft. antenna connecting cables/brackets
- One configuration cable

WI-I/O 9-K Transmitter (Single Sensor Units)

The Single Sensor Wireless I/O range of products is suitable for connecting to a single sensor or group of sensors and provides an economical solution for remote monitoring systems. Capable of being powered by battery-only supplies, these products are particularly suitable where power is not available.

- Frequency hopping spread spectrum 902-928 MHz 1W, license-free USA/Canada/Mexico
- Configurable sub-bands license-free South America, Australia/NZ, Asia, Europe available on request



Applications


- · Wireless connection of flowmeters or energy meters
- · Monitoring of storage tanks
- Monitoring cathodic protection on pipelines
- · Wireless alarms from power reticulation fault-relays



Features

- Input-only unit two digital/pulse one analog
- Networks with Multi-I/O and Gateway units
- · Analog Loop Supply for field devices
- Sensor signals (inputs) are transmitted to a Multi-I/O module where the signals are re-created as output signals, or passed via serial or Ethernet data bus to a host device such as a PLC or SCADA system.
- Extremely low power consumption by reverting to "sleep" mode
- Multiple power supply options including battery-only supply
- Weatherproof IP66 / NEMA 4 enclosures
- Class 1 Div 2 hazardous areas approval
- Up to 3000 wireless units per network
- Any input on any unit can be wirelessly linked to any output on any unit. Inputs can be linked to multiple outputs.
- Peer-to-peer communications. Exception reporting.
 Reliable self-checking messages. Highly secure data encryption.
- Multi-hop repeater functions up to 5 intermediate units can be configured in any input-output link

- External inputs plus internally calculated values analog setpoint status, pulse rate and pulse total, power supply voltage, power supply alarm
- Setpoint status generated by comparing analog input to high and low setpoints.
- Pulse inputs generate separate pulse count value and a pulse rate value. Pulse rates are treated as internal analog registers with a configurable maximum value.
- Power supply generates internal I/O values that can be transmitted-low normal supply voltage status, low battery voltage status and battery voltage (analog)
- Can connect to up/down counter transducers such as shaft-encoders
- Easily configured to repeat the transmission several times to ensure that the transmission is received correctly
- Easy-to-use E-Series Windows configuration available at www.weidmuller.ca or weidmuller.com



WI-I/O 9-K Transmitter Ordering Information

Unit	Description
WI-I/O-9-K	Wireless Transmitter (900 MHz)



Dimensions



General Specifications

 Frequency: frequency hopping spread spectrum 902-928MHz, sub-bands available

• Power: 1W

 Max. Range (line-of-sight): 20 miles (4 ERP), 15km (1 ERP); 3000 ft / 1000 m in obstructed industrial environments

Antenna Connector: SMA connector
 Temperature: -40 to 60°C / -40 to 140° F

• **Humidity:** 0-99% RH

 Regulatory Approvals: approved to FCC Part15.247, RS210; EMC compliant 89/336 EEC, EN 300 683, AS3548. FCC Part 15

- **Housing:** weatherproof (IP66) painted aluminum enclosure 170 x 64 x 36mm/ 6.7 x 2.5 x 1.4 inches; weatherproof connector for external connections
- Each transmission may be configured to be sent 1 to 5 times
- LED indicators radio TX, operation OK
- High and low set-points generate internal digital status. Set-point status sets (on) when analog value
 low set-point and resets (off) when analog value > highset-point status transmitted as per digital input.

Input Type	Source	Function
Digital	external	status
Pulse Total	external	count
Pulse Rate	internal	analog
Analog	external	analog
Set-point	internal	status
Supply Voltage	internal	analog
Supply Low Voltage	internal	status

Digital Inputs

- Two inputs, suitable for voltage-free contacts / NPN, or voltage input 0-1.5 VDC (ON) / 3.5-13 VDC (OFF)
- Status transmission on change of input signal and on time elapsed since last transmission - update time period 10 sec. - 5 days, a separate update time can be configured when the discrete input is "on"

Pulse Inputs

- Pulse input max. rate 10KHz, 3 msec on time (50KHz available using a 1/10 divider). Pulse counted as 16-bit register with a 16-bit overflow register (total count 32-bit). Transmissions occur when count change exceeds configured increase or on time elapsed since last transmission. Update time 10 sec. 5 days. Change-of-state transmissions may be suspended if increase exceeds a configured value to reduce radio traffic.
- Up/Down Pulse Count: the two pulse inputs may be configured to a single count to suit quadrature or incremental shaft encoder transducers.
- Pulse Rate: calculated from rate of pulse input and treated as an internal analog input. Configurable scaling. Transmitted as per analog input.

Analog Inputs

- 0-24mA (4-20mA) available all models, 0-10V also available "floating" differential input, resolution 12-bit, accuracy < 0.1 % measurement continuous or sampled, sample time configurable 0-9.1 hours, transducer warm-up time configurable 0.5-127 sec.
- Analog value transmitted on change of input signal or time elapsed since last transmission, change sensitivity configurable from 0.7-75%, update time configurable from 0.1 min. - 5 days

Power Supply

- Battery Supply: WI-BP-I/O-9-K Battery pack, 6 x AA batteries, 9 VDC
- Normal Supply: 6-30 VDC, power consumption @12VDC - quiescent (sleep mode) 120μA, operating mode 10mA + analog loop during radio transmission (50 - 100 msec.)
- 300mA @ 1W
- Analog loop supply internally generated (24VDC)
- Internal monitoring of supply low voltage status maybe transmitted to remote modules as an "input"
- Power consumption increases for pulse inputs > 10Hz

Set-point Status

High and low set-points generate internal digital status.
 Set-point status sets (on) when analog value <low set-point and resets (off) when analog value > high set-point.
 Status transmitted as per digital input.

Serial Port

 RS232 DB9 female DCE used for configuration and diagnostics

Battery Pack

The WI-BP-I/O-9-K is a battery pack for the WI-I/O-9-K wireless device. The battery pack is used in applications where power lines are either not installed or not allowed.


Applications

- Used to power WI-I/O-9-K units atop of water tanks for monitoring fluid level
- Used to power WI-I/O-9-K units to monitor pipeline cathodes


Features

- 9V, 6 AA alkaline batteries
- Housed in a weatherproof (IP66) enclosure

Dimensions




Specifications WI-BP-I/O-9-K



WI-BP-I/O 9-K Battery Pack Ordering Information

Unit	Description
WI-BP-I/O-9-K	Battery Pack for WI-I/O-9-K





WI-I/O-9-K





Technical Data

Inputs	two digital/pulse inputs, suitable for voltage free contacts / NPN, or voltage input 0-1.5 VDC (ON) / 3.5-13 VDC (OFF)
Digital	status transmission on change of input signal and on time elapsed since last transmission - update time period 10 sec - 5days, a separate update time can be configured when the discrete input is "on"
Pulse	Pulse rate up to 1000 Hz, 3 msec on time. Pulse counted as 16 bit register with a 16 bit overflow register (total count 32 bit). Transmissions occur when count change exceeds configured increase, or on time elapsed since last transmission; update time 10 sec - 5 days; change transmissions may be suspended if increase exceeds a configured value to reduce radio traffic.
Up/Down Pulse Count	the two pulse inputs may be configured to a single count, to suit quadrature or incremental shaft encoder transducers.
Pulse Rate	calculated from rate of pulse input and treated as an internal analog input. Configurable scaling. Transmitted as per analog input.
Analog	one analog input 0-25 mA (4-20mA) 0-10V also available "floating" differential input
resolution	12 bit
accuracy	< 0.1 % measurement continuous or sampled
sample time configurable	1 min - 5 days
transducer warm-up time configurable	0.5-127 sec
analog value transmitted on change of input signal or time elapsed since last transmission,	
change sensitivity configurable	0.7-75%
update time configurable	0.1min - 5 days
Setpoint Status	high and low setpoints generate internal digital status setpoint status sets (on) when analog value < low setpoint and resets (off) when analog value > high setpoint status transmitted as per digital input
Power Supply	6 - 30VDC
Power consumption @12VDC	quiescent (sleep mode) 120μA, operating mode 10mA + analog loop
Power consumption during radio transmission (50 - 100 msec)	300mA @ 1W, 220μA @ 500mW 100mA @ 100mW, 50mA @ 10mW
Analog loop supply internally generated	Yes
Internal monitoring of supply low voltage status	may be transmitted to remote modules as an "input"
Power consumption increases for pulse inputs > 10Hz.	
General Data	
Operating Temperature	-40 to 60°C (-40 to 140°F)
Humidity	0 - 99% RH
EMC Standards	compliant 89/336 EEC, EN 300 683, AS3548, FCC Part 15
Approvals	Housing - IP66 NEMA4; FCC Part 15.247, RS210, Class 1, Div. 2
Mounting	
LED indication	Radio TX, Operation OK
frequency hopping spread spectrum	902-928MHz, sub-bands available
Transmit power	1 W
Maximum line of sight range	20 miles (4W ERP), 15 km (1W ERP)
Receiver data sensitivity	-108 dBm
Data rate	19.2 Kbs with forward error correction
Antenna connector	SMA female coaxial
Dimensions mm (in)	170 x 64 x 36 (6.7 x 2.5 x 1.4)

Ordering Data

	Туре	Part No.
	WI-I/O-9-K	6720005004
Battery Pack (optional)	WI-BP-I/O-9-K	6720005112
Plug and Lead-1 meter (included w/ radio)	WI-PLI-9-K	6720005113

Wireless Meshing I/O Units

Weidmuller's WI-I/O-9-U2 combines multi I/O and/or gateway functionality with the reliability of secure, scalable mesh distance communications. The WI-I/O-9-U2 IP-based addressing provides mesh/self-healing of network communications, multihop repeating and remote over the air re-configuration and diagnostics. The WI-I/O-9-U2 is further complemented by its ease of commissioning and integration into existing plant infrastructure.

Features:

- 902-928MHz Frequency Shift Keying (FSK): Frequency Hopping Spread Spectrum Channels/Hop Sets: 50 x 250kHz; 2 frequency channels.
- IP Based Wireless MESH Technology @ 1 Watt transmit power.
- Self-healing, repeatable, secure communications to 128bit AES
- User friendly operation with self discovery of radio path and expansion I/O
- Remote over the air re-configuration, firmware upgrade and fault analysis
- · Scalable, simple to complex, and point to multipoint network design
- Block Mapping and Block Messaging technology for ease of system integration
- I/O and/or gateway functionality via feature key upgrade
- System wide view, localized I/O referencing, and printing/exporting of configuration



WI-I/O-9-U2 TC

The WI-I/O-9-U2 TC is a thermocouple adapter interface for the WI-I/O-9-U2 product. The WI-I/O-9-U2 TC provides greater accuracy by allowing calibration between the adapter, measurement devices and ambient temperatures. Temperature measurement accuracy depends on the measured temperature and ambient temperature. Errors are a result of both errors in cold junction temperature and thermocouple voltage measurement. The WI-I/O-9-U2 TC provides for greater accuracy by allowing calibration of the cold junction temperature offset value and thermocouple temperature (i.e. offset calibration).

Supported Thermocouple: Type T

Measurement ranges: -200 to +30°C and 0 to +390°C

Basic Accuracy (Un-calibrated): +/- 3.5°C at -200 to

+30°C +/- 2°C at 0 to +390°C

Calibrated Accuracy: +/- 1°C over ambient temperature

range +/- 0.5°C at calibration temperature

Security and Configuration

Data encryption: 64bit; 128bit AES

Password: https accessibility

User Configuration: Web page; software configuration




Dimensions



WI-I/O-9-U2 Meshed Multi I/O and Gateway


Configuring and commissioning time/effort on the WI-I/O-9-U2 has been designed for ease of customer use and cost savings during commissioning. The configuration utility allows for simple nomination of I/O points origin and destination with automatically detecting and routing the most efficient path to the destination node. This is complemented by periodic interrogation for optimal path verification, quick recovery of network communications and automatic detection of expansion I/O (Weidmuller's WI-I/O-EX-1-S). It also incorporates efficient 'change of state' radio communications and user configurable I/O or register periodic reporting of link status (ie update time). All combine to ensure the user is in charge of network communications.



Configuration is user friendly by nominating and labelling origin and destination points, and IP-based addressing finds the most efficient route.

Remote/local configuration, upgrade and analysis.

Weidmuller's IP-based addressing further aids in cost reduction providing remote analysis and/or upgrade. A user may perform remote or local over the air re-configuration and interrogation of nodes for diagnostics and firmware upgrade. User nominated localized referencing of I/O and system wide network viewing aids in fault analysis and exporting/printing of node configuration is supported.




Quicker, more cost effective commissioning.

Radio network efficiency and commissioning of the WI-I/O-9-U2 into legacy process control/automation networks is aided with block mapping and block messaging technology.

Block mapping technology allows end-users to gather related, non-contiguous data points/registers, into a single radio message structure and scatter these points at receiving devices for ease of integration (eg PLC logic, SCADA tags).


Block Mapping Technology



Block mapping technology enables non-contiguous data to be transferred between network devices reducing re-programming time and associated costs.

Block mapping technology is complemented by block messaging technology allowing end users to select continuous, related, I/O and registers for forwarding to receiving devices in a single message. Both block mapping and block messaging combine with highly efficient 'change of state', dense capacity radio messaging capabilities in providing scalable system design for ever growing application needs.

Block Messaging Technology



Block messaging communicates continuous blocks of data improving the efficiency of radio band use and even more scalable network design.

Cost effective, distance IP based mesh networks.

The WI-I/O-9-U2 combines distance, 900MHz, IP mesh communications with ease of configuration, local/remote over the air re-configurability, firmware upgrade and diagnoses of nodes in the network.

Featuring Weidmuller's IP-based addressing technology with its innovations in network communications efficiency, the WI-I/O-9-U2 provides for scalable network design for process control and automation base applications.

WI-I/O-9-U2





Technical Data

Inputs

Digital: opto-isolated (5kV) inputs suitable for voltage free contacts or NPN transistor

Analog:

"floating" differential inputs, common mode voltage 27V, 24VDC for powering external loops provided, digital filtering 1 sec.

Pulse: (configurable Digital Inputs)

_		٠.	_		4-
v	u	u	p	u	ts

Digital

Analog: current sink to common, max loop voltage 27V, max loop resistance 1000 ohms

Pulse:

FET 30VDC 200mA max 10kHz

Power Supply
Battery supply
Normal supply
Battery charging circuit
Average Current Draw
Transmit Current Draw
Internal monitoring

Notes

Connections
RS232/RS485
RS232 connection
RS485 connection
Ethernet Port
USB Port
General Data
Frequency
Transmit Power
Transmission
Modulation
Receive Sensitivity
Channel Spacing
Data Rate
Range (LoS)
Operating Temperature
Humidity

Up to 8 DI (Configurable),

On-state Voltage <2.1V Wetting, Current 5mA

4 AI (2 differential: 2 single ended) resolution 14bits; accuracy 0.1% Current Range - 0-24mA Voltage Range: Al 1,2: 0-25V, Al 3,4: 0-5V

4 PI

DI 1,2: Max. Pulse rate 50kHz, Pulse width min 10us DI 3,4: Max. Pulse rate 1kHz, Pulse width min 0.2ms

Up to 8 DO (Configurable) FET (30V DC @ 200mA max.) On-state Voltage - DO Max: 30 V DC Wetting Current - DO Max: 200mA

2 AO 0-24mA;

resolution 13bits; accuracy 0.1%

4 PO

DO 1, 2 Max. Pulse rate 50kHz, Pulse width min. 10µs DO 3, 4 Max. Pulse rate 1kHz, Pulse width min 0.2ms

12-15V DC 15-30V DC, over-voltage and reverse power protected

220mA @ 12V DC (Idle), 110mA @ 24V DC (Idle) 500mA @ 12V DC (1W), 250mA @ 24V DC (1W)

power fail and battery voltage

An internal DC/DC converter provides 24V DC

included for 1.2-12 AHr sealed battery

150mA for analog loop supply.

serial port 9600 baud, 8 bits, no parity, 1 stop bit EIA-562 (RJ45 connector) max cable distance 2000 m terminal connections 10/100 BaseT; RJ45 - IEEE 802.3

USB-B connector for configuration

902-982MHz

1mW (+0dBm) to 1W (+30dBm)

Frequency Hopping Spread Spectrum (FHSS)

Frequency Shift Keying (FSK)

-109dBm @ 19.2Kbps (3% FER)

50 x 250 KHz

19.2-115.2 Kbps "Auto Mode" selects fastest rate possible relative to RSSI

32Km (20 mi.) @ 1W -40 to 60°C (-40 to 140°F)

0-99%RH

EN 300 683; FCC Part 15; AS 3548; 89/336/EEC

Class 1 Div 2 (, CE, IEC60950, IECex

DIN-rail mounting

Power, RF, RS232, RS485, D I/O (P I/O), A I/O

1 x SMA female coaxial

180 x 150 x 35 (5.91 x 7.09 x 1.38)

Ordering Data

Antenna connector

Dimensions mm (in)

EMC Standards

LED indication

Approvals

Mounting

Wireless Mesh I/O 8 DI/O, 4AI, 2AO, 1-4 PI/O
Wireless Mesh Radio + Modbus Gateway
software (Preloaded)
Modbus TCP/RTU Gateway (software Add-on)
TCP Adaptor (Type T Thermocouple Add-on)

Туре	Part No.
WI-I/O-9-U2	6720005011
WI-I/O-9-U2-MODTCP-900US	6720005014
WI-I/O 9-U2-GTWY*	6720005012
WI-I/O 9-U2 TC	6720005013

*Note: Gateway Software Add-on is licensed to a single WI-I/O-9-U2 Radio Serial number & is not intended for use on multiple radios. When ordering WI-I/O-9-U2-GTWY alone, please include existing WI-I/O-9-U2 radio Serial Number (printed on the side of the unit).


WI-I/O 9 Multi I/O Units

A transceiver is a wireless device made up of a transmitter and receiver. Since each module can manage both input and output signals, it can be used to monitor transducers and control industrial processes. This module can also be used as a repeater to relay another wireless device's transmission, thus increasing the overall range of the system.



Typical Applications


- Wireless junction box in a process plant to connect a large number of signals to other parts of the plant and to the plant control center
- Simple Remote Terminal Unit (RTU) in a SCADA system, connecting sensors/instrumentation/process signals in pump stations, sub-stations, pipeline regulator stations, etc.
- · Machine-to-Machine wireless connectivity in factories



- Short distance and long distance applications with license-free and licensed products
- Multi-hop repeater functions up to 5 intermediate units can be configured in any input/output link
- Four versions available
- Any input on any unit can be wirelessly linked to any output on another unit. Inputs can be linked to multiple outputs.
- Inputs and outputs can be added via additional serial units
- The units can be pre-programmed to consider analog set-points, pulse rate and pulse total, power supply voltage, power supply alarm
- Set-point status generated by comparing analog inputs to high and low set-points. Available on Al1 of -1 units, and Al1-4 of -2 units.
- Pulse inputs generate a separate pulse count value and a pulse rate value. Pulse rates are treated as internal analog registers with a configurable maximum value.
- Wide voltage power supply, with integral UPS battery charger and solar regulator
- Power supply generates internal signal values which can be transmitted, low normal supply voltage status, low battery voltage status and battery voltage (analog)
- Multiple communication failure diagnostics with output status. Fail-to-transmit alarm and fail-to-receive alarm status.
- Radio receives signal and background RF noise measurement / logging diagnostics
- Input measurement display and output "forcing" diagnostics
- Communication logging diagnostics
- Easy-to-use E-Series Windows configuration available at www.weidmuller.ca or www.weidmuller.com

Features

- Class I, Division 2 hazardous areas approved (USA/Canada); (CSA certified)
- Multiple inputs/output channels for monitoring and control functions
- Up to 95 wireless units per network
- Each wireless unit can connect to input/output expansion modules via RS485 multi-drop with up to 31 expansion modules per wireless unit
- Sensor signals connected at one module; input signals are transmitted to another module where the signals are re-created as output signals or passed via serial to a host device such as a PLC or SCADA system



Multi-I/O Unit Ordering Information

WI-I/O 9	-1	-2	-3	-4
Digital inputs	4	4	0	4 - 16
	Voltage-free contacts	Voltage-free contacts	Voltage-free contacts	Voltage-free contacts
Digital outputs	1 + 3	1	8	4 - 16
	Relay + FET	FET	FET	FET
Analog inputs	2	6	0	0
	4-20mA	0-20mA/0-10V		
Analog outputs	2	0	8	0
	4-20mA		0-20mA/0-10V	
Pulse inputs	1	4	0	4
•	100Hz	1 x 1KHz, 3 x 100Hz		1 x 1KHz, 3 x 100Hz
Pulse outputs	1	0	4	4
	100Hz		1 x 1KHz, 3 x 100Hz	1 x 1KHz, 3 x 100Hz

Note: Pulse and digital inputs are same connection point.

FET = Field Effect Transistor

Dimensions







General

- **Frequency:** frequency hopping spread spectrum 902-908 MHz, sub-bands configurable
- Power: transmit power 1W, approved to FCC Part 15.247, RSS210
- Sensitivity: receiver data sensitivity -108dBm
- Max. Range (line-of-sight): USA/Canada 4W ERP, 20+ miles. Other countries - 1W ERP, 15+ km depending on local conditions
- Data Rate: 19.2 Kb/s with forward-error correction
- Antenna Connector: SMA female coaxial • Temperature: -40 to 60°C / -40 to 140°F
- **Humidity:** 0-99% RH

- Regulatory Approvals: EMC FCC Part 15, AS3548, 89/336/EEC, EN 301 489
- Certifications: CSA Class I, Division 2 hazardous areas (USA/Canada)
- **Housing:** extruded aluminum case, 5.1" x 7.4" x 2.4" (130 x 188 x 60mm) with DIN-rail mounting
- Removable terminals up to 2.5 mm² (12 gauge) wires
- **LED indication** for power supply, module status, digital I/O

Inputs and Outputs*

Digital Inputs

- Opto-isolated (5000V) inputs suitable for voltage-free contacts or NPN transistor, contact wetting current 5mA
- Type-1 & -2 four inputs
- Type-4 up to 16 inputs (4 inputs + 12 selectable I/O).
 The 12 selectable inputs are surge protected, but not isolated.

Digital Outputs

- Type-1 four relay, contacts, Form A, AC 50V 5A / DC 30V 2A
- Type-2 1 FET output 30VDC 500mA
- Type-3 8 FET output 30VDC 500mA
- **Type-4** up to 16 FET output (4 outputs + 12 selectable I/O)

Analog Inputs

- "Floating" differential inputs, common mode voltage 27V. 24VDC for powering external loops provided. Digital filtering 1 sec.
- **Type-1** two 4-20mA resolution 15-bit, accuracy 0.1% (over range indication 2-25mA)
- **Type-2** six 0-20mA resolution 12-bit, accuracy 0.1% (over range indication 0-25mA)

^{*} See table above for Input/Output summary

Analog Outputs

- Current sink to common, max. loop voltage 27V, max. loop resistance 1000 ohms
- **Type-1** two 4-20 mA resolution 15-bit, accuracy 0.1% (over range indication 0.5-25mA)
- Type-3 eight 0-20 mA resolution 12-bit, accuracy 0.1% (over range indication 0-20.5mA)

Pulse Inputs

- Specifications as per digital inputs, max. pulse rate 100Hz, pulse width min. 5 ms
- Type-1 one input (DI1)
- **Type-2** four inputs (DI1-4) first pulse input (DI1) max. 1000Hz, pulse width min. 0.5 ms
- **Type-4** four inputs (DI1-4) first pulse input (DI1) max. 1000Hz, pulse width min. 0.5 ms

Pulse Outputs

- FET 30VDC 500mA max. 100Hz
- Type-1 one
- Type-3 & -4 four

Power Supply

- Battery Supply: 11.5-15.0 VDC
- Normal Supply: 12-24 VAC or 15-30 VDC, overvoltage and reverse power protected
- Internal monitoring of power fail, solar charge status and battery voltage. These values may be transmitted to remote modules for monitoring.
- Internal DC/DC converter provides 24VDC 150mA for analog loop supply
- Battery charging circuit included for 1.2-12 AHr sealed battery
- Solar regulator for direct connection of solar panel (up to 30W) and solar battery (100AHr)

Serial Port

- A serial port can be used to configure transceivers and to hard wire one transceiver to another when desired.
 This connection avoids the need to add wireless nodes to circumvent impenetrable obstructions and provides a redundant path for critical applications.
- RS232/RS485 serial port 9600 baud, 8 bits, no parity, 1 stop bit
- RS232 9 pin DB9 female connector
- RS485 terminal connections (max. cable distance 2000m)



WI-I/O 9-1 WI-I/O 9-2







Technical Data

Inputs				
Digital: opto-isolated (5000V) inputs suitable for voltage free contacts or NPN transistor, contact wetting current 5 mA	four inputs	four inputs		
Analog: "floating" differential inputs, common mode voltage 27V, 24VDC for powering external loops provided, digital filtering 1 sec.	two 4-20mA resolution 15 bit, accuracy 0.1%	six 0-20mA/0-10V resolution 12 bit, accuracy 0.1%		
Pulse: as per digital inputs, Max pulse rate 100Hz, pulse width min 5ms	one input (DI1)	four input(DI1-4) - first pulse input (DI1) max 1000Hz, pulse width min 0.5ms		
Outputs				
Digital	4 (1 Relay Form A, AC, 50V 5A/ DC 30V 2A; 3 FET)	one FET output 30VDC 500mA		
Analog: current sink to common, max loop voltage 27V, max loop resistance 1000 ohms	two 4-20 mA resolution 15 bit, accuracy 0.1%			
Pulse: FET 30VDC 500mA max 100Hz	one			
Power Supply				
Battery supply	11.5-15.0 VDC	11.5-15.0 VDC		
Normal supply	12-24 VAC or 15-30 VDC, over-voltage and reverse power protected	12-24 VAC or 15-30 VDC, over-voltage and reverse power protected		
Battery charging circuit	included for 1.2-12 AHr sealed battery	included for 1.2-12 AHr sealed battery		
Solar regulator	for direct connection of solar panel (up to 30W) and solar battery (100AHr)	for direct connection of solar panel (up to 30W) and solar battery (100AHr)		
Internal monitoring	power fail, solar charge status, and battery voltage	power fail, solar charge status, and battery voltage		
Notes	An internal DC/DC converter provides 24VDC 150mA for analog loop supply.	An internal DC/DC converter provides 24VDC 150mA for analog loop supply.		
Serial Port				
RS232/RS485	serial port 9600 baud, 8 bits, no parity, 1 stop bit	serial port 9600 baud, 8 bits, no parity, 1 stop bit		
RS232 connection	9pin DB9 female connector	9pin DB9 female connector		
RS485 connection	max cable distance 2000 m terminal connections	max cable distance 2000 m terminal connections		
General Data				
Operating Temperature	-40 to 60°C (-40 to 140°F)	-40 to 60°C (-40 to 140°F)		
Humidity	0-99%RH	0-99%RH		
EMC Standards	FCC Part 15, AS3548, 89/336/EEC, EN 301 489	FCC Part 15, AS3548, 89/336/EEC, EN 301 489		
Approvals	Class 1 Div 2 👰	Class 1 Div 2 🚱		
Mounting	DIN-rail mounting	DIN-rail mounting		
LED indication	For power supply, WDT, digital I/O	For power supply, WDT, digital I/O		
Antenna connector	SMA female coaxial	SMA female coaxial		
Dimensions mm (in)	130 x 188 x 60 (5.1 x 7.4 x 2.4)	130 x 188 x 60 (5.1 x 7.4 x 2.4)		

Ordering Data

	Туре	Part No.	Туре	Part No.
	WI-I/O 9-1	6720005000	WI-I/O 9-2	6720005001
Accessories: DB9 Male - DB9 Female Serial config. cable	WI-CSER-905-9	6720005105	WI-CSER-905-9	6720005105

WI-I/O 9-3 WI-I/O 9-4







Technical Data

Toommour Butu		
Inputs		
Digital: opto-isolated (5000V) inputs suitable for voltage free contacts or NPN transistor, contact wetting current 5 mA		up to 16 inputs (4 inputs + 12 selectable I/O) the 12 selectable inputs are surge protected but not isolated
Analog: "floating" differential inputs, common mode voltage 27V, 24VDC for powering external loops provided, digital filtering 1 sec.		
Pulse: as per digital inputs, Max pulse rate 100Hz, pulse width min 5ms		four input(DI1-4) - first pulse input (DI1) max 1000Hz, pulse width min 0.5ms
Outputs		
Digital	eight FET output 30VDC 500mA	up to 16 FET output (4 outputs + 12 selectable I/O)
Analog: current sink to common, max loop voltage 27V, max loop resistance 1000 ohms	eight 0-20 mA resolution 12 bit, accuracy 0.1%	
Pulse: FET 30VDC 500mA max 100Hz	four (DO1-4)	four (DO 1-4)
Power Supply		
Battery supply	11.5-15.0 VDC	11.5-15.0 VDC
Normal supply	12-24 VAC or 15-30 VDC, over-voltage and reverse power protected	12-24 VAC or 15-30 VDC, over-voltage and reverse power protected
Battery charging circuit	included for 1.2-12 AHr sealed battery	included for 1.2-12 AHr sealed battery
Solar regulator	for direct connection of solar panel (up to 30W) and solar battery (100AHr)	for direct connection of solar panel (up to 30W) and solar battery (100AHr)
Internal monitoring	power fail, solar charge status, and battery voltage	power fail, solar charge status, and battery voltage
Notes	An internal DC/DC converter provides 24VDC 150mA for analog loop supply.	An internal DC/DC converter provides 24VDC 150mA for analog loop supply.
Serial Port		
RS232/RS485	serial port 9600 baud, 8 bits, no parity, 1 stop bit	serial port 9600 baud, 8 bits, no parity, 1 stop bit
RS232 connector	9pin DB9 female connector	9pin DB9 female connector
RS485 connector	max cable distance 2000 m terminal connections	max cable distance 2000 m terminal connections
General Data		
Operating Temperature	-40 to 60°C (-40 to 140°F)	-40 to 60°C (-40 to 140°F)
Humidity	0-99%RH	0-99%RH
EMC Standards	FCC Part 15, AS3548, 89/336/EEC, EN 301 489	FCC Part 15, AS3548, 89/336/EEC, EN 301 489
Approvals	Class 1 Div 2 🐠	Class 1 Div 2 🚱
Mounting	DIN-rail mounting	DIN-rail mounting
LED indication	For power supply, WDT, digital I/O	For power supply, WDT, digital I/O
Antenna Connector	SMA female coaxial	SMA female coaxial
Dimensions mm (in)	130 x 188 x 60 (5.1 x 7.4 x 2.4)	130 x 188 x 60 (5.1 x 7.4 x 2.4)

Ordering Data

Туре	Part No.
WI-I/O 9-3	6720005002
WI-CSER-905-9	6720005105
	WI-I/O 9-3

Туре	Part No.
WI-I/O 9-4	6720005003
WI-CSER-905-9	6720005105

WI-I/O-EX Expansion I/O Units (Serial I/O)

The WI-I/O-EX is a wired device capable of interfacing with other Weidmuller wireless radios to increase the number of signals radios can monitor/control. They can also be used as a slave to any Modbus control system.


Typical Applications

Expansion I/O for WI-I/O 9 wireless units and WI-MOD units

- up to 31 x WI-I/O-EX units can be connected to each wireless unit via RS485 (up to 2 km long). Serial I/O multiplexer
- transfer I/O via RS485— up to 32 units per multi-drop link




 up to 31 x WI-I/O-EX units can be connected to each Modbus master via RS485 (up to 2 km long).



Features

- Multi I/O channels- monitoring and control functions
- Connected via RS485 multi-drop
- Selectable communications via WIB-net or Modbus protocol (both RTU and ASCII formats)
- Sensor signals connected at one module (input signals) are transmitted to another module where the signals are re-created as output signals, or passed via serial to a host device such as a PLC or SCADA system
- Connect to WI-I/O 9 wireless I/O units for up to 31 serial addresses per wireless unit
- Connect WI-I/O-EX units together to form a serial multi-drop I/O system - up to 32 serial addresses per multi-drop link— no Master device is required to control communications

- Connect up to 99 x WI-I/O-EX units as multi-drop Modbus I/O (RS485 extenders/isolators required for more than 31 units per single multi-drop length)
- RS485 multi-drop up to 2 km (1 mile) depending on installation environment
- Three I/O versions available
- Peer-to-peer communications;
 Exception reporting; Reliable self-checking messages; Any input on any unit can be linked to any output on any unit. Inputs can be linked to multiple outputs; Serial communications 9.6Kb/s
- Up to 32 Units
- Alternate Modbus RTU or Modbus ASCII slave protocol, serial communications configurable up to 115.2Kb/s,
 7 or 8 data bit format
- External I/O plus internally calculated values analog setpoint status, pulse rate and pulse total, power supply voltage, power supply alarm
- Setpoint status generated by comparing analog inputs to high and low setpoints



- Analog inputs selectable as "floating" dual-terminal inputs or commoned single-terminal inputs;
 Configurable current (0-10/0-20/4-20mA) or voltage (0-5/0-10/1-5V).
- Analog outputs selectable as single-terminal source or sink outputs. Configurable current (0-10/0-20/4-20mA) or voltage (0-5/0-10/1-5V). Configurable scaling, zero and span parameters.
- Pulse inputs generate separate pulse count value and a pulse rate value. Pulse rates are treated as internal analog registers with a configurable maximum value.

- Multiple communication-failure diagnostics with output status. Fail-to-transmit alarm and fail-to-receive alarm status.
- Class 1 Div 2 hazardous areas approval
- Input measurement display and output "forcing" diagnostics.
- Communication logging diagnostics.
- Easy-to-use E-Series Windows configuration available at www.weidmuller.ca or weidmuller.com



Serial Unit Ordering Information

WI-I/O-EX	67200005038 -11	67200005039 -12	67200005040 -13	
Digital inputs	up to 16	up to 8 Voltage-free contacts	up to 8	
Digital outputs	up to 16	up to 8	up to 8	
Analog inputs	0	4 "floating"/ 8 commoned 0-20mA / 0-10V	0	
Analog outputs	0	0	8 sink / source 0-20mA / 0-10V	
Pulse inputs	4 1KHz	0	0	
Pulse outputs	8 100Hz	8 100Hz	8 100Hz	

Note: Digital inputs and outputs are combined channels. When a channel is used as an output, it is not available as an input. Pulse and digital I/O are same connection.

Dimensions



General Specifications

- Temperature: -40 to 60°C / -40 to 140°F
- **Humidity:** 0-99% RH
- Regulatory Approvals: EMC FCC Part 15, AS3548, 89/336/EEC
- Certifications: CSA Class I, Division 2 hazardous areas (USA/Canada)
- **Housing:** high density thermo-plastic, 5.91" x 6.97" x 1.38" (150 X 177 x 35mm) with DIN-rail mounting
- Removable terminals up to 12 gauge (2.5 mm²)
- LED indication for power supply, processor OK, serial TX and RX, digital I/O

Inputs and Outputs

Digital Inputs

- Suitable for voltage-free contacts or NPN transistor, contact wetting current 5mA, inputs are surge protected
- Type -11 up to 16 selectable I/O
- Type -12, -13, up to 8 selectable I/O

Digital Outputs

- Field Effect Transistor (FET) outputs, 30VDC 200mA
- Type -11 up to 16 selectable I/O
- Type -12, -13, up to 8 selectable I/O

Analog Inputs

- "Floating" differential inputs, common mode voltage 27V, 24VDC for powering external loops provided, 0-20mA/0-10V, resolution 12-bit, accuracy 0.1%
- Type-12 8 input channels, selectable as 4 dualterminal floating inputs or 8 single-terminal commoned inputs

Analog Outputs

- Selectable as current/voltage source or current sink to common, max. loop voltage 27V, max. loop resistance 1000 ohms, 0 – 20mA/0 – 10V, 12-bit, accuracy 0.1%
- Type -13 8 channels

Pulse Inputs

- Specifications as per digital inputs, max. pulse rate 1kHz, pulse width min. 0.5 ms
- Type -11- 4 inputs (DIO1-4)

Pulse Outputs

- Specifications as per digital outputs, max. pulse rate 100Hz, pulse width min. 5ms
- Type -11,-12,-13, 8 outputs (DIO 1-8)

Power Supply

- **Battery Supply:** 9 30VDC, over-voltage and reverse power protected
- Internal monitoring of supply voltage. These values may be transmitted to remote modules for monitoring.
- Internal DC/DC converter provides 24VDC 250mA for analog loop supply

Serial Port

- RS485 serial port configurable up to 115.2Kb/s, 7 or 8 data bits, none/even/odd parity, 1 or 2 stop bits
- RS232 configuration port 9 pin DB9 female connector, 9.6Kb/s, 8/n/1
- RS485 max cable distance 2000m terminal connections



SP°c₁n₂

WI-I/O-EX-1-S-11

WI-I/O-EX-1-S-12





Technical Data

Inputs

Digital: suitable for voltage free contacts or NPN transistor, contact wetting current 5mA, inputs are surge protected	up to 16 selectable I/O	up to 8 selectable I/O
Analog: "floating" differential inputs, common mode voltage 27V, 24VDC for powering external loops provided, 0-20mA/0-10V resolution 12 bit, accuracy 0.1%		8 input channels, selectable as 4 dual-terminal floating inputsor 8 single-terminal commoned inputs.
Pulse: specifications as per digital inputs Max pulse rate 1kHz, pulse width min 0.5ms	4 inputs (DIO1-4)	
Outputs		
Digital: FET outputs, 30VDC 200mA	up to 16 selectable I/O	up to 8 selectable I/O
Pulse: specifications as per digital outputs Max pulse rate 100Hz, pulse width min 5ms	8 outputs (DIO1-8)	8 outputs (DIO 1-8)
Power Supply	10.8 - 30VDC, over-voltage and reverse power protected Internal monitoring of supply voltage. These values may be transmitted to remote modules for monitoring. An internal DC/DC converter provides 24VDC 250mA for analog loop supply.	10.8 - 30VDC, over-voltage and reverse power protected Internal monitoring of supply voltage. These values may be transmitted to remote modules for monitoring. An internal DC/DC converter provides 24VDC 250mA for analog loop supply.
Serial Port		
RS485	serial port configurable up to 115.2Kb/s, 7/8 data bits, n/e/o parity, 1 / 2 stop bits	serial port configurable up to 115.2Kb/s, 7/8 data bits, n/e/o parity, 1 / 2 stop bits
RS232 connector	configuration port 9pin DB9 female connector, 9.6Kb/s, 8/n/1	configuration port 9pin DB9 female connector, 9.6Kb/s, 8/n/1
RS485 connector	max cable distance 2000 m terminal connections	max cable distance 2000 m terminal connections
General Data		
Operating Temperature	-40 to 60°C (-40 to 140°F)	-40 to 60°C (-40 to 140°F)
Humidity	0-99% RH	0-99% RH
EMC Standards	FCC Part 15, AS3548, 89/336/EEC	FCC Part 15, AS3548, 89/336/EEC
Approvals	Class 1 Div 2 hazardous areas 🐠	Class 1 Div 2 hazardous areas 👰
Mounting	DIN-rail mounting	DIN-rail mounting
LED indication	power supply, processor OK, serial TX and RX, digital I/O	power supply, processor OK, serial TX and RX, digital I/O
Dimensions mm (in)	150 x 177 x 35 (5.91 x 6.97 x 1.38)	150 x 177 x 35 (5.91 x 6.97 x 1.38)

Туре	Part No.	Туре	Part No.
WI-I/O-EX-1-S-11	6720005038	WI-I/O-EX-1-S-12	6720005039

WI-I/O-EX-1-S-13





Inputs:	
Digital: suitable for voltage free contacts or NPN transistor, contact wetting current 5mA, inputs are surge protected	up to 8 selectable I/O
Outputs	
Digital: FET outputs, 30VDC 200mA	up to 8 selectable I/O
Analog: selectable as current/voltage source or current sink to common, max loop voltage 27V, max loop resistance 1000 ohms, 0 – 20mA/0 – 10V, 12 bit, accuracy 0.1%	8 channels
Pulse: specifications as per digital outputs Max pulse rate 100Hz, pulse width min 5ms	8 outputs (DIO 1-8)
Power Supply	10.8 - 30VDC, over-voltage and reverse power protected. Internal monitoring of supply voltage. These values may be transmitted to remote modules for monitoring. An internal DC/DC converter provides 20VDC 250mA for analog loop supply.
Serial Port	
RS485	serial port configurable up to 115.2Kb/s, 7/8 data bit n/e/o parity, 1 / 2 stop bits
RS232 connector	configuration port 9pin DB9 female connector, 9.6Kb/s, 8/n/1
RS485 connector	max cable distance 2000 m terminal connections
General Data	
Operating Temperature	-40 to 60°C (-40 to 140°F)
Humidity	0-99% RH
EMC Standards	FCC Part 15, AS3548, 89/336/EEC
Approvals	Class 1 Div 2 hazardous areas 👰
Mounting	DIN-rail mounting
LED indication	power supply, processor OK, serial TX and RX, digital I/O
Dimensions mm (in)	150 x 177 x 35 (5.91 x 6.97 x 1.38)


Wireless Gateways WI-GTWY-9

Wireless gateways interface between other Weidmuller wireless devices and control systems (such as PLC's, DCS and SCADA). In addition to channeling the wireless network data into one central control system, they can also act as an eight input/output transceiver.



Applications

- Wirelessly connect PLCs on a new machine to an existing factory automation system
- Interface different automation systems in different sections of a plant
- Connect protocol devices into a common wireless network
- Weidmuller wireless units are used to wirelessly transmit signals for PLCs or DCS



Wireless gateways connect to popular process control and automation databuses and convert signal information to the proven WIB-net wireless protocol.


Main benefits:

- Wireless extension of factory automation, providing a high security firewall. The wireless gateway connects to a databus and transfers I/O values to another wireless gateway unit via WIB-net communications. The other gateway interfaces to its own databus. Multiple gateway units can communicate in a WIB peer-to-peer network.
- There is an efficient wireless protocol conversion in the modules enabling an efficient transfer of data to Modbus, Profibus, Ethernet and DeviceNet.
- Interface between PLCs, DCS, HMI, or SCADA and Weidmuller wireless units. The wireless gateway keeps an "image" of the remote wireless network in its memory and interfaces this image to the databus.
- Network wireless units and gateways to connect sensor signals and control systems

Features

- Connects to data bus at full bus speed (e.g. 12Mb/s for Profibus, 100Mb/s for Ethernet)
- Provides Protocol Conversion (Profibus, Modbus, Ethernet, DeviceNet)
- Can interconnect master-slave, slave-slave and master-master
- Interconnects different data buses wireless protocol conversion
- Provides a peer-to-peer wireless network using WIB-net
- High security data encryption
- Automatic acknowledgment and error-correction
- Multiple path routing
- Eight on-board discrete I/O, individually configurable as input or output
- Network configuration is performed with easy-to-use free software
- Wide range power supply with integral back-up battery-charging feature
- Frequency hopping spread spectrum
- 902-928 MHz 1W license-free USA/Canada/Mexico
- Configurable sub-bands license-free South America, Australia/NZ, Asia, Europe available on request

Interconnection Flexibility



Dimensions







General Specifications

- Frequency: frequency hopping spread spectrum 902-928 MHz, sub-bands configurable
- **Power:** transmit power 1W, approved to FCC Part 15.247, RSS210
- Sensitivity: receiver data sensitivity 108 dBm
- Max. Range (line-of-sight): USA/Canada, 4W ERP 20+ miles; other countries, 1W ERP, 15+ km depending on local conditions
- Data Rate: 19.2 Kb/s with forward-error correction
- Antenna Connector: SMA female coaxial
 Temperature: -40 to 60°C / -40 to 140°F
- **Humidity:** 0 99% RH
- Regulatory Approvals: EMC Compliant EN 301 489, FCC Part 15
- Certifications: Class I, Division 2 (USA, Canada)
- Housing: extruded aluminum case 130 x 183 x 60 mm, 5.1 x 7.2 x 2.4 inches, DIN-rail mounting, removable terminal blocks for ease of module replacement, terminals suitable for 12 gauge (2.5 mm²) wire
- Radio communications can be configured for combination of event-reporting (change-of-state), update time, read/write blocks and poll response.
 Radio message includes system addressing, unit addressing, error-checking and configurable security encryption. Communication control includes message acknowledgments and up to four re-transmissions.
- **Peer-to-peer addressing.** Messages may be routed through five intermediate repeater addresses.
- Fail-to-transmit and fail-to-receive alarms are configurable.
- LED indication for processor OK, radio TX and RX, serial TX and RX, active status
- Modbus RTU (binary), master / slave configurable; RS232 or RS485, 300 - 19200 bits/sec.

Inputs and Outputs

 Eight discrete I/O, individually configurable as input or output. Inputs suitable for voltage-free contacts. Outputs are FET, 30VDC 500mA.

Power Supply

- Battery Supply: battery charging circuit included for 12V back-up battery, max. charge current regulated to 0.7A (>12V supply)
- Normal Supply: 9 30VDC / 12 24VAC
- Normal current drain: 12V 150mA; 24V 90mA add 5mA per active I/O, current drain during radio transmission, add to above: 12V 350mA; 24V 200mA

Set-point Status


• Modbus 4300 I/O points (analog plus discrete)

Serial Port

- RS232 9 pin DB9 female connector
- RS485 terminal connections

Configuration and Diagnostics

 Diagnostics include online read/write of I/O registers, radio signal strength values from remote units and off-line testing of databus protocol.





Radio communications can be configured for combination of event reporting (change-of-value), update time, read/write blocks and poll response. Radio message includes system addressing, unit addressing, error checking and configurable security encryption. Communication control includes message acknowledgments and up to four re-transmissions. Peer to peer addressing. Messages may be routed through four intermediate repeater addresses. Fail-to-transmit and fail-to-receive alarms configurable

WI-GTWY-9-MD1 Modbus (Master and Slave), DF1

WI-GTWY-9-PR1 Profibus DP Slave





Technical Data

Power Supply	9 - 30VDC / 12 - 24VAC	9 - 30VDC / 12 - 24VAC
	Battery charging circuit included for 12V back-up battery, max charge current regulated to 0.7A (>12V supply) Normal current drain MD1 version 12V 150mA; 24V 90mA Other version 12V 270mA; 24V 170mA Add 5mA per active I/O	Battery charging circuit included for 12V back-up battery, max charge current regulated to 0.7A (>12V supply) Normal current drain MD1 version 12V 150mA; 24V 90mA Other version 12V 270mA; 24V 170mA Add 5mA per active I/O
Current drain during radio transmission	Add 12V 350mA; 24V 200mA to above	Add 12V 350mA; 24V 200mA to above
I/O Capacity	4300 I/O points (analog plus discrete)	416 I/O bytes up to 1952 DI/1952 DO, or up to 122 AI/122 AO
Register Size	16 bit	16 bit
Number of remote WI-GTWY-9 addresses	500	500
General Data		
Operating Temperature	-40 to 60°C (-40 to 140°F)	0 to 60°C (30 to 140°F)
Humidity	0 - 99 %RH	0 - 95 %RH
EMC Standards	EN 301 489, FCC Part 15, Approved to FCC Part 15.247, RS210	EN 301 489, FCC Part 15, Approved to FCC Part 15.247, RS210
Approvals	Class 1 Div 2 🚱	Class 1 Div 2 🐠
Mounting	DIN-rail mounting,	DIN-rail mounting,
LED indication	for processor OK, radio TX and RX, serial TX and RX, active status	for processor OK, radio TX and RX, serial TX and RX, active status
Dimensions mm (in)	130 x 183 x 60 (5.1 x 7.2 x 2.4)	130 x 183 x 60 (5.1 x 7.2 x 2.4)
Wireless Communications	Modbus RTU (binary), master / slave configurable. RS232 or RS485, 300 - 19200 bits/sec.	Profibus-DP functionality according to EN 50170.
	Allen-Bradley DF1 full-duplex. RS232 only, 300 - 19200 bits/sec.	RS-485 optically isolated with on-board DC/DC converter, automatic baudrate detection (9600 bit/s - 12 Mbit/s)
On-board I/O	Eight discrete I/O, individually configurable as input or output. Inputs suitable for voltage free contacts. Outputs are FET, 30VDC 500mA.	Eight discrete I/O, individually configurable as input or output. Inputs suitable for voltage free contacts. Outputs are FET, 30VDC 500mA.
Configuration	via free Windows software	via free Windows software
Diagnostics	on-line read/write of I/O registers, radio signal strength values from remote units, and off-line testing of data bus protocol.	on-line read/write of I/O registers, radio signal strength values from remote units, and off-line testing of data bus protocol.
Radio Transceiver		
Frequency hopping spread spectrum	902-908 MHz, sub-bands configurable	902-908 MHz, sub-bands configurable
Transmit power	1W	1W
Receiver data sensitivity	-108dBm	-108dBm
Maximum line-of-sight range	USA/Canada, 4W ERP, 20+ miles	USA/Canada, 4W ERP, 20+ miles
Data rate	19.2 Kb/s with forward-error correction	19.2 Kb/s with forward-error correction
Antenna connector	SMA female coaxial	SMA female coaxial

Ordering Data


	Туре	Part No.
	WI-GTWY-9-MD1	6720005020
Accessories: DB9 Male - DB9 Female Serial config. cable	WI-CSER-905-9	6720005105

Туре	Part No.
WI-GTWY-9-PR1	6720005021
WI-CSER-905-9	6720005105

40



WI-GTWY-9-PR2 Profibus DP Master WI-GTWY-9-ET1
Ethernet IP, Modbus TCP,
TCP/IP functions







Technical Data

Power Supply Current drain during radio transmission I/O Capacity	9 - 30VDC / 12 - 24VAC Battery charging circuit included for 1 battery, max charge current regulated supply) Normal current drain MD1 version 12V 150mA; 24V 90m/ Other version 12V 270mA; 24V 170r Add 5mA per active I/O Add 12V 350mA; 24V 200mA to abo 2048 bytes input and 2048 bytes out	to 0.7A (>12V A nA ove put up to 4300	9 - 30VDC / 12 - 24VAC Battery charging circuit inclubattery, max charge current supply) Normal current drain MD1 version 12V 150mA; 2 Other version 12V 270mA; Add 5mA per active I/O Add 12V 350mA; 24V 200 2048 bytes input and 2048	regulated to 0.7A (>12V 24V 90mA 24V 170mA mA to above bytes output up to 4300	
	discrete I/O points, or up to 1024 ana analog out	log in / 1024	discrete I/O points, or up to 1024 analog in / 1024 analog out		
Register Size	16 bit		16 bit		
Number of remote WI-GTWY-9 addresses	500		500		
General Data					
Operating Temperature	0 to 60°C (30 to 140°F)		0 to 60°C (30 to 140°F)		
Humidity	0 - 95 %RH		0 - 95 %RH		
EMC Standards	EN 301 489, FCC Part 15, Approved t 15.247, RS210	o FCC Part	EN 301 489, FCC Part 15, Approved to FCC Part 15.247, RS210		
Approvals	Class 1 Div 2 🚱		Class 1 Div 2 @		
Mounting	DIN-rail mounting,		DIN-rail mounting,		
LED indication	for processor OK, radio TX and RX, serial TX and RX, active status		for processor OK, radio TX and RX, serial TX and RX, active status		
Dimensions mm (in)	130 x 183 x 60 (5.1 x 7.2 x 2.4)		130 x 183 x 60 (5.1 x 7.2 x	2.4)	
Wireless Communications	ireless Communications Profibus-DP functionality according to EN 50170.		10/100 Mbit/s, RJ45 conne	ctor, Transformer isolated	
RS-485 optically isolated with on-board DC/DC converter, automatic baudrate detection (9600 bit/s - 12 Mbit/s)			interface Modbus/TCP class 0, class 1 and partially class 2 slave EtherNet/IP level 2 I/O Server Embedded Web system (Dynamic HTTP), on-board file system (1.4MB flash disc), user downloadable web pages through FTP server, Email functionality (SMTP)		
On-board I/O	Eight discrete I/O, individually configu output. Inputs suitable for voltage free Outputs are FET, 30VDC 500mA.	ndividually configurable as input or ble for voltage free contacts. Eight discret output. Inpu		ly configurable as input o	
Configuration	via free Windows software		via free Windows software		
Diagnostics	on-line read/write of I/O registers, radio signal strength values from remote units, and off-line testing of data bus protocol.		on-line read/write of I/O registers, radio signal strength values from remote units, and off-line testing of data bus protocol.		
Radio Transceiver					
Frequency hopping spread spectrum	902-908 MHz, sub-bands configurable	e	902-908 MHz, sub-bands co	onfigurable	
Transmit power	1W	· ·	1W		
Receiver data sensitivity	-108dBm		-108dBm		
Maximum line-of-sight range	USA/Canada, 4W ERP, 20+ miles		USA/Canada, 4W ERP, 20+ miles		
Data rate	19.2 Kb/s with forward-error correction	on	19.2 Kb/s with forward-erro	r correction	
Antenna connector	SMA female coaxial		SMA female coaxial		
Ordering Data					
	Туре	Part No.	Туре	Part No	
	\//LGT\//Y-9-PR2	6720005022	\\/\LGT\\/\Y_9_FT1	6720005023	

	Туре	Part No
	WI-GTWY-9-PR2	6720005022
Accessories: DB9 Male - DB9 Female Serial config. cable	WI-CSER-905-9	6720005105

Туре	Part No.
WI-GTWY-9-ET1	6720005023
WI-CSER-905-9	6720005105



Radio communications can be configured for combination of event reporting (change-of-value), update time, read/write blocks and poll response. Radio message includes system addressing, unit addressing, error checking and configurable security encryption.Communication control includes message acknowledgments and up to four re-transmissions. Peer to peer addressing. Messages may be routed through four intermediate repeater addresses. Fail-totransmit and fail-to-receive alarms configurable

WI-GTWY-9-DE1 **DeviceNet Slave**



WI-GTWY-9-M+1 Modbus Plus Slave



Technical Data

Power Supply	9 - 30VDC / 12 - 24VAC Battery charging circuit included for 12V back-up battery, max charge current regulated to 0.7A (>12V supply) Normal current drain MD1 version 12V 150mA; 24V 90mA Other version 12V 270mA; 24V 170mA Add 5mA per active I/O	9 - 30VDC / 12 - 24VAC Battery charging circuit included for 12V back-up battery, max charge current regulated to 0.7A (>12V supply) Normal current drain MD1 version 12V 150mA; 24V 90mA Other version 12V 270mA; 24V 170mA Add 5mA per active I/O
Current drain during radio transmission	Add 12V 350mA; 24V 200mA to above	Add 12V 350mA; 24V 200mA to above
I/O Capacity	512 bytes input and 512 bytes output up to 4300 discrete I/O points, or up to 256 analog in / 256 analog out	2048 bytes input and 2048 bytes output up to 4300 discrete I/O points, or up to 1024 analog in / 1024 analog out
Register Size	16 bit	_16 bit
Number of remote WI-GTWY-9 addresses	500	500
General Data		
Operating Temperature	0 to 60°C (30 to 140°F)	0 to 60°C (30 to 140°F)
Storage Temperature		
Humidity	0 - 95 %RH	0 - 95 %RH
EMC Standards	EN 301 489, FCC Part 15, Approved to FCC Part 15.247, RS210	EN 301 489, FCC Part 15, Approved to FCC Part 15.247, RS210
Approvals	Class 1 Div 2 🚱	Class 1 Div 2 🚱
Mounting	DIN-rail mounting,	DIN-rail mounting,
LED indication	for processor OK, radio TX and RX, serial TX and RX, active status	for processor OK, radio TX and RX, serial TX and RX, active status
Dimensions mm (in)	_130 x 183 x 60 (5.1 x 7.2 x 2.4)	130 x 183 x 60 (5.1 x 7.2 x 2.4)
Wireless Communications	DeviceNet 2.0 Slave, optically isolated RS422 with selectable baudrate between 125, 250 and 500 Kbit/sec.	Modbus RTU (binary), master / slave configurable. RS232 or RS485, 300 - 19200 bits/sec.
		Modbus Plus Slave, optically isolated RS485 with standard baudrate of 1 Mbit/sec, global data base transactions with routing for up to six networks.
On-board I/O	Eight discrete I/O, individually configurable as input or output. Inputs suitable for voltage free contacts. Outputs are FET, 30VDC 500mA.	Eight discrete I/O, individually configurable as input or output. Inputs suitable for voltage free contacts. Outputs are FET, 30VDC 500mA.
Configuration	via free Windows software	via free Windows software
Diagnostics	on-line read/write of I/O registers, radio signal strength values from remote units, and off-line testing of data bus protocol.	on-line read/write of I/O registers, radio signal strength values from remote units, and off-line testing of data bus protocol.
Radio Transceiver		
Frequency hopping spread spectrum	902-908 MHz, sub-bands configurable	902-908 MHz, sub-bands configurable
Transmit power	1W	1W
Receiver data sensitivity	-108dBm	-108dBm
Maximum line-of-sight range	USA/Canada, 4W ERP, 20+ miles	USA/Canada, 4W ERP, 20+ miles
Data rate	19.2 Kb/s with forward-error correction	19.2 Kb/s with forward-error correction
Antenna connector	SMA female coaxial	SMA female coaxial

Part No.

6720005024

6720005105

Type

WI-GTWY-9-M+1

WI-CSER-905-9

Part No. 6720005025

6720005105

Туре

WI-GTWY-9-DE1

WI-CSER-905-9

Ordering Data

cable

42

Accessories: DB9 Male - DB9 Female Serial config.

Wireless Data Modems

Wireless data modems connect to serial or Ethernet links and transmit the data wirelessly. The modem controls the wireless messages and data ports to provide a "transparent" data transfer.

Wireless Ethernet Data Modems

The Weidmuller Wireless Ethernet Modems are a robust, license-free wireless 802.11 standards compliant transceiver capable of high bandwidth communications. They are optimized for throughputs of up to 108Mbps which provides robust and secure two-way wireless communications in challenging indoor and outdoor environments typical of industrial monitoring and control applications.

The Weidmuller modems offer node to node deterministic mesh network repeatability for further range and multiple channel spacing options to increase network scalability. Integrated Modbus server capability allows seamless I/O expansion through the use of WI-I/O-EX-1-S Expansion units.

Applications

- IP Cameras
- Roaming Vehicles
- PLC Communications
- Data Logger Communications
- Serial and Ethernet Communications
- Agriculture Sprayer Control
- Water/ Waste Water Systems
- SCADA Networks

Weldmiller >

Features

- 802.11b/g and 802.11a Standard Compliant Options 902 – 928MHz; 2.412 – 2.472GHz (802.11b/g); 5.18 – 5.825GHz Frequency (802.11a)
- Up to 108Mbps Data Throughout
- Transmit and Receive Antenna Diversity
- Access Point/Client and Bridge/Router Configuration
- Serial Client/Server/Multicast Modbus TCP to RTU Gateway
- Spanning Tree (Self Healing) Support
- Deterministic AP to AP Mesh Network Repeatability
- · Fast Roaming for AP to AP Handover
- IEEE 802.11i Secure 128-bit AES Encryption (WPA2)
- · MAC and IP Address Filtering
- Digital I/O Channel Transfer
- Configurable Settings for High Noise Environments
- Over-The-Air Network Diagnostics and Configuration
- VLAN Tagging Supported for Bridging and Routing Modes

Wireless Serial Data Modems

The Weidmuller Wireless Serial Modem is an RS232 or RS485 data modem that enables cost effective, two-way communications between serial devices such as PLCs, RTUs and other industrial machinery to host monitoring and control systems.

Offering scalability from simple to complex deployments, coupled data rates up to 500kbps with low latency performance make them ideal for demanding Modbus or Profibus applications. Reliability is maximized through interference immune frequency hopping spread spectrum technology while security is assured via data encryption to the AES 256-bit standard.

Applications

- SCADA Systems
- Pump Control Networks
- Water/Wastewater
- PLC/RTU Interfaces
- Serial Output Instruments
- · Building Automation/Security
- Embedded Machine Control



Features

- 902 928MHz; 2.401 2.4835GHz Frequency
- USB interface for ease of configuration
- Reduced transmission latency for high speed control
- Superior receiver sensitivity and rejection to cut through interference
- Adjustable output RF power to keep signals within your plant
- Voltage Test Point for RSSI measurement
- · Sleep Mode and Frequency Blocking

Serial Only Data

WI-MOD-9-SER-D Serial 900Mhz

WI-MOD-24-SER-D Serial 2.4GHz







Technical Data

Radio Transceiver		
Transmission	Frequency Hopping Spread Spectrum (FHSS)	Frequency Hopping Spread Spectrum (FHSS)
Frequency - USA/Canada	902 – 928MHz	2.401 - 2.4835GHz
Transmit Power	10 mW to 1W (0 - 30dBm)	1 – 100mW (0 – 20dBm)
Modulation	GFSK & MSK	GFSK & MSK
Receiver Sensitivity	-96dBm, 100dBm, -105dBM @ 900MHz	-92dBm, -98dBm, -102dBm @ 2.4GHz
Expected line-of-sight range, depending on local conditions	900Mhz: 64km (40 miles)	2.4GHz: 12km (7 miles)
RF Data Transmission Rate	900Mhz Band: 500kbps, 250kbps, 125kbps	2.4GHz Band: 250kbps, 125kbps, 19.2kbps
Range may be extended by:	Ability to construct complex networks using multiple repeaters and roaming features	Ability to construct complex networks using multiple repeaters and roaming features
Serial Ports		
Serial Settings	Baud rate, data bits, stop bits, parity, flow control	Baud rate, data bits, stop bits, parity, flow control
RS232 Connection	EIA-232 via terminal block	EIA-232 via terminal block
RS485 Connection	EIA-485 via terminal block with selectable termination resistor	EIA-485 via terminal block with selectable termination resistor
Protocols & Configuration		
System Address	4.2 x 109 possible addresses	4.2 x 109 possible addresses
Protocols Supported	Modbus RTU, DF1, Profibus	Modbus RTU, DF1, Profibus
User Configuration	USB Interface	USB Interface
Configuration Parameters	Master/Slave, Repeater, Serial Data Items	Master/Slave, Repeater, Serial Data Items
Security	AES 128, 192 and 256-bit	AES 128, 192 and 256-bit
General Data		
Power Supply	9 - 30 VDC, over voltage and reverse wiring protected	9 - 30 VDC, over voltage and reverse wiring protected
Normal current drain	150mA @ 24 VDC (900Mhz)	100mA @ 24 VDC (2.4GHz)
Current when transmitting	200mA @ 24 VDC (900MHz)	125mA @ 24 VDC (2.4GHz)
Low power mode current drain		
Operating Temperature	-40 to 70°C (-40 to 158°F)	-40 to 70°C (-40 to 158°F)
Humidity	10% to 90% non-condensing	10% to 90% non-condensing
Weight	240g (0.55lbs)	240g (0.55lbs)
EMC Standards	FCC Part 15; EN 301 489	FCC Part 15; EN 301 489
RF (Radio)	FCC Part 15.247; ETSI EN 300-328	FCC Part 15.247; ETSI EN 300-328
Approvals	cUL, Class I Div 2, Groups A, B, C, D, Temp Code: T5 ATEX Zone 2, EEx nL IIC T5 II 3G, IECEX Ex nL IIC T5 EN/UL 60950-1 (pending)	cUL, Class I Div 2, Groups A, B, C, D, Temp Code: T5 ATEX Zone 2, EEx nL IIC T5 II 3G, IECEX Ex nL IIC T5 EN/UL 60950-1 (pending)
Mounting	DIN-rail mounting	DIN-rail mounting
Dimensions mm (in)	116mm x 60mm x 66mm (4.57" x 2.36" x 2.60")	116mm x 60mm x 66mm (4.57" x 2.36" x 2.60")
Antenna connection	SMA Female coaxial	SMA Female coaxial
Housing	Plastic with aluminum base, IP20 rated	Plastic with aluminum base, IP20 rated
Terminal Blocks	16 - 22 AWG (16 - 20AWG for power)	16 - 22 AWG (16 - 20AWG for power)
Reported Diagnostics	RF, Serial	RF, Serial
LED indication	RF Link, RF TX & RX, RS232 TX & RX, RS485 TX & RX	RF Link, RF TX & RX, RS232 TX & RX, RS485 TX & RX
Network Management	Via master radio to all remotes	Via master radio to all remotes
Discrete Output	RF Link Status 0.5A @ 30 VDC Relay	RF Link Status 0.5A @ 30 VDC Relay

ordornig Data				
	Туре	Part No.	Туре	Part No.
	WI-MOD-9-SFR-D	6720005055	WI-MOD-24-SFR-D	6720005056

Serial Only Data

WI-MOD-9-D Serial 900MHz





Technical Data

Radio Transceiver	
Transmission	Frequency Hopping Spread Spectrum Transceiver
Frequency - USA/Canada	902 - 928 MHz
Transmit Power	1W (30dBm)
Modulation	Frequency Shift Keying
Receiver Sensitivity	-106dBm @ 19.2kbps, -103dBm @ 115.2kbps (1%FER)
Expected line-of-sight range, depending on local conditions	USA/Canada 32kms (20+ miles) @ 4W ERP
RF Data Transmission Rate	_19200 baud, 57600 baud, 115200 baud (selectable)
Range may be extended by:	up to five intermediate repeaters in controlled mode unlimited repeaters in transparent mode
Serial Ports	
Serial Settings	7 or 8 data bits, even/odd/Parity Bits Configurable
RS232 Connection	DB9 Female DCE; RTS/CTS/DTR/DCD (Hardware Signals Provided)
RS485 Connection	2-Pin Terminal Block (Max Distance 1.2km (4000') - Non Isolated)
Protocols & Configuration	
System Address	Configurable 8 Bit Value (0 - 255)
Protocols Supported	Operating Mode, Radio and Serial Settings
User Configuration	Windows Software or AT Hayes Commands Via Serial Port
Configuration Parameters	Transparent Mode / Control Mode
Security	
General Data	
Power Supply	10 - 30 VDC or 10 - 24 VAC
Normal current drain	70mA/12 VDC or 50mA/24 VDC
Current when transmitting	350mA/12V or 250mA/ 24V
Low power mode current drain	20mA/12 VDC or 15mA/24 VDC
Operating Temperature	_40 to +60°C (-40 to +140°F)
Humidity	0 - 99% RH Non-Condensing
Weight	0.5kg (1.1lbs)
EMC Standards	FCC Part 15 Class A
RF (Radio)	AS/NZS 4268, FCC 15.247
Approvals	CSA Class I Division 2, AS/NZS 60950, IEC 60950
Mounting	DIN-rail mounting
Dimensions mm (in)	114 x 168 x 30mm (4.5" x 6.7" x 1.2")
Antenna connection	SMA female coaxial
Housing	Powder-Coated Aluminum
Terminal Blocks	Removable; Max conductor 12 AWG (2.5mm²)
Reported Diagnostics	RSSI Measurement (dBm), Bit Error Ratio (BER)
LED indication	Power/OK, Radio TX/RX, Serial TX/RX, DCD
Network Management	-
Discrete Output	Voltage Free Contact

Туре	Part No.
WI-MOD-9-D	6720005050

	6720005054 WI-MOD-E-G	6720005057 WI-MOD-E-A	1242110000 IE-WL-AP-BR-CL-ABG-US	6720005015 WI-MOD-945-E	6720005051 WI-MOD-9-E
Frequency	2.412 - 2.472GHz	5.18 - 5.825GHz ¹	2.4Ghz / 5.8Ghz	902-928MHz1	902 - 928MHz ¹
Modulation	802.11b/g + OFDM	802.11a + OFDM	802.11 a/b/g	802.11 g + OFDM	802.11-FHSS
TX Power	15 - 400mW ²	15 - 400mW ²	15-100mW	15 - 1000mW	100mW - 1W ²
Data Rate	108Mbps	108Mbps	54Mbps	54Mbps	200Kbps
WDS (AP-AP)	Yes	Yes	Yes	Yes	No
Self Heal (Spanning Tree)	Yes	Yes	Yes	Yes	Yes
Serial Client/ Server/ Multicast	Yes	Yes	Yes	Yes	Yes
Encryption Security Level (Maximum level highlighted)	WPA2 /802.11i	WPA2 /802.11i	WPA / WPA2/802.1X	WPA2/802.11i	128 bit AES Encryption
MAC / IP Filtering	Yes	Yes	Yes	Yes	Yes
Network Function	AP /Client Bridge /Router	AP /Client Bridge /Router	AP/Client/Bridge	AP /Client Bridge /Router	AP /Client Bridge /Router
Online Diagnostics	Yes	Yes	Yes	Yes	Yes
Online Configuration	Yes	Yes	Yes	Yes	Yes

¹Frequency availability - country regulatory dependant. ²Configurable TX Power option available - country regulations apply.



Ethernet and Serial Data



WI-MOD-9-E Serial and Ethernet 900Mhz (FHSS)



WI-MOD-945-E Serial and Ethernet 900MHz (DSSS)



Technical Data

Tooliilloai Bata		
Radio Transceiver		
Transmission	Frequency Hopping Spread Spectrum Transceiver	Direct Sequence Spread Spectrum (DSSS)
Frequency - USA/Canada	902 - 928 MHz	902 - 928MHz
Transmit Power	0.1 - 1W (20 - 30 dBm) configurable	250mW (+24dBm) to 1W (+30dBm)
Modulation	Frequency Shift Keying	802.11g Orthogonal Frequency Data
		Modulation (OFDM)
Receiver Sensitivity	-108 dBm @ 10-6 BER	-95dBm @ 0.25Mbps - 71dBm @ 54Mbps (8% FER)
Channel Spacing	16 x 50	9 x 1.25MHz; 9 x 2.5MHz; 4 x 5MHz; 4 x 10MHz; 2 x 20MHz
RF Data Transmission Rate	19.2, 57.6, 115.2Kb/s or auto rate selection	1 – 54Mbps "Auto Mode" Selects Fastest Rate Possible Relative to RSSI"
Expected line-of-sight range, depending on local conditions	up to 60 miles / 100 km line-of-sight using high gain antennas (*up to 4W ERP permitted in USA/Canada) Range may be extended using repeater features	6+ miles @ 630mW/30Km (18 mi.) @ 1W (*up to 4W ERP permitted in USA/Canada) Range may be extended using repeater features
Range may be extended by:	up to five intermediate repeaters in controlled mode unlimited repeaters in transparent mode	Ability to construct complex networks using multiple repeaters and roaming features
Ethernet/Serial Port	unimitted repeaters in transparent mode	multiple repeaters and roaming leatures
Ethernet	10/100baseT; Auto MDX	10/100 BaseT RJ45, IEEE 802.3 compliant.
Euromot	Bridge/router functions work with all Ethernet protocols	Bridge/router functions work with all Ethernet protocols
Embedded Protocols:	TCP/IP, UDP ARP, PPP, ICMP, HTTP, FTP, TFTP, TELNET	TCP/IP, UDP ARP, PPP, ICMP, HTTP, FTP, TFTP, TELNET, SNMP, RADIUS/802.1X, DHCP, OFDM
Serial		
RS232 V.24 DCE	DB9 Female DCE; RTS/CTS/DTR/DCD (Hardware Signals Provided)	DB9 Female DCE; RTS/CTS/DTR/DCD
RS485	2-Pin Terminal Block (Configurable Termination) Serial server, PPP, Modbus to Modbus TCP conversion	2-Pin Terminal Block – Non-Isolated Serial server, PPP, Modbus to Modbus TCP conversion
Serial Settings	7/8 Data Bits; Stop/Start/Parity (Configurable)	7/8 Data Bits; Stop/Start/Parity (Configurable)
Data Rate (Bps)	1.2 to 115.2 Kb/s	1200, 2400, 4800, 9600, 14400, 19200, 38400, 57600
		76800, 115200, 230400
Protocols/Configuration	ECCID 1 01 CL T . CC.	FCCID 1 01 CL T CL .
System Address	ESSID; 1 – 31 Character Text String TCP/IP, UDP, ARP, Radius/802,1x, DHCP, DNS, PPP, ICMP.	ESSID; 1 – 31 Character Text String
Protocols supported	HTTP, FTP, TFTP, TELNET, MODBUS-RTU and MODBUS-TCP	TCP/IP, UDP, ARP, Radius/802.1x, DHCP, DNS, PPP, ICMP, HTTP, FTP, TFTP, TELNET, MODBUS-RTU and MODBUS-TCP
Network/Configurable Parameters	Configurable as Access Point or Client, Bridge or Router Point-to-point, Point-to-multipoint, user configurable addressing Repeater functionality MAC Filtering - whitelist or blacklist	Access Point/Client/Bridge/Router/VLAN Point-to-Point, Point-to-Multi-point Wireless Distribution System (AP - AP Repeater) Modbus TCP/RTU Gateway Serial Client/Server/Multicast Simultaneous RS232/485 Connection Embedded Modbus Master/Slave for I/O Transfer
User Configuration	Remote Access - Over-the-Air Network Access - Ethernet	User Configurable Parameters via HTTPS Embedded Web Server Network Access - Ethernet
Security	128 bit AES encryption	Data Encryption – 802.11i with CCMP 128-bit AES Support for 802.1x Radius Server Secure HTTP Protocol
Bandwidth Protection	MAC Address – Whitelist/Blacklist IP Filtering – Whitelist/Blacklist	MAC Address - Whitelist/Blacklist IP Filtering - Whitelist/Blacklist ARP/GARP Filtering - Whitelist/Blacklist
General Data		
Antenna connection	Single Female SMA 50Ω	2 x Female SMA Standard Polarity 50Ω Supports signal diversity or high-gain antenna
Operating Temperature	-40 to 60°C (-40 to 140°F)	-40 to +60°C ; -40 to +140°F
Humidity	99% non-condensing	0 - 99% RH Non-condensing
Power Supply	9 to 30 VDC; Under/Over Voltage Protection	9 to 30 VDC; Under/Over Voltage Protection
Current consumption Idle:	280mA (12V), 150mA (24V)	270mA @ 12 VDC; 140mA @ 24 VDC
Transmit:	(1W) 500mA (12V), 300mA (24V)	500mA @ 12V (+30dBm), 250mA @ 24V (+30dBm)
EMC	FCC CFR47 Part 15; EN 301 489-3; EN 301 489-5	FCC Part 15; EN 301 489 - 17; AS/NZS CISPR22
RF (Radio)	FCC 15.247, RS210	EN 300 328; FCC Part 15; RSS 210
Approvals	CSA Class I Division 2, AS/NZS 60950, IEC 60950	CSA Class I, Division 2; ATEX; IECEx NA IIC; IEC 60950 (RoHS Compliant); cULus Listed (pending on 1W)
Mounting	DIN-rail mounting	DIN-rail mounting
Dimensions (LxWxH) mm	114 x 168 x 30mm (4.5" x 6.7" x 1.2")	114 x 168 x 30mm (4.5" x 6.7" x 1.2")
Weight	< 0.4 kg / 0.8 lb	0.5kg (1.1lb).
Housing	Powder-Coated Aluminium	Powder-Coated Aluminium
Mounting Terminal Blocks	DIN-Rail Removable: May conductor 12 AVVC (2 Emm2)	DIN-Rail Remarkha: May Conductor 12 AN/C (2 5 mm²)
Terminal Blocks	Removable; Max conductor 12 AWG (2.5mm²)	Removable; Max Conductor 12 AWG (2.5 mm²)
LED indication	Power/OK; RX; TX/Link; RS232; LAN; RS485; Digital I/O Serial Activity, Digital I/O, LAN 10/100Mbit Link	Power/OK; RX; TX/Link; RS232; LAN; RS485; Digital I/O Serial Activity, Digital I/O, LAN 10/100Mbit Link
		RSSI Measurements (dBm) Connectivity Information/
Reported Diagnostics	Diagnostics available through web pages	Statistics System Log File

Ordering Data			
	Туре	Part No.	T
	WI-MOD-9-E	6720005051	V

Туре	RF Power	Part No.
WI-MOD-945-E	630mW	6720005015
WI-MOD-945-F-H	1W/	6720005016

Ethernet and Serial Data





WI-MOD-E-G Serial and Ethernet 2.4GHz

TCP



WI-MOD-E-A Serial and Ethernet 5.8GHz



Technical Data
Radio Transceiver
Transmission
Frequency - USA/Canada
Transmit Power
Modulation
Receiver Sensitivity
Channel Spacing
RF Data Transmission Rate
Expected line-of-sight range, depending on local conditions
Range may be extended by:
Ethernet/Serial Port
Ethernet
Embedded Protocols:
Serial
RS232 V.24 DCE
50.105

Serial	
RS232 V.24 DCE	
RS485	
Serial Settings	
Data Rate (Bps)	
Protocols/Configurati	on
System Address	
Protocols supported	

Network/Configurable Parameters

	i
User Configuration	
Security	
Bandwidth Protection	
General Data	
Antenna connection	
Operating Temperature	
Humidity	
Power Supply	
Current consumption Idle:	
Transmit:	
EMC	
RF (Radio)	
Approvals	
Mounting	
Dimensions (LxWxH) mm	
Weight	
Housing	
Mounting	
Terminal Blocks	
LED indication	
Reported Diagnostics	1
Input/Output Configurable DI/DO/AI	

FCC 15.247, RS210
CSA Class I, Division 2; ATEX; IECEx NA III (RoHS Compliant); cULus Listed
DIN-rail mounting
4.5" x 5.5" x 1.2" (114 x 140 x 30 mm)
1.0 lb (0.45 kg)
Powder-Coated Aluminium
DIN-Rail
Removable; Max conductor 12 AWG (2.5r
Power/OK; RX; TX/Link; RS232; LAN; RS4

Serial Activity, Digital I/O, LAN 10/100Mbit Link Diagnostics available through web pages

Input Voltage-Free Contact
Output FET 30 VDC 500mA

Direct Sequence Spread Spectrum (DSSS)	Direct Sequence Sp
2.412-2.472 GHz	5.150-5.825 GHz
15-400 mW (data rate and country-specific)	15-400 mW (data
Orthogonal frequency data modulation (OFDM)	Orthogonal frequer
-100 dBm @ 250 kbps, 74 dBm @ 108 Mbps (8% FER)	-100 dBm @ 250 k
5-MHz spacing (13 channels, 2.412-2.472 GHz)	20-MHz spacing (2
1-108 Mbps "Auto Mode" selects fastest rate possible relative to RSSI	6-108 Mbps "Auto Mode" select
6 miles (10 km) @ 400 mW	3 miles (5 km) @ 40

repeaters and roaming features 10/100 BaseT RJ45, IEEE 802.3 compliant.

Range may be extended using repeater features Ability to construct complex networks using multiple

Bridge/router functions work with all Ethernet protocols TCP/IP, UDP ARP, PPP, ICMP, HTTP, FTP, TFTP, TELNET, SNMP, RADIUS/802.1X, DHCP, OFDM

DB9 Female DCE; RTS/CTS/DTR/DCD
2-Pin Terminal Block – Non-Isolated Serial server, PPP, Modbus to Modbus TCP conversion
7/8 Data Bits; Stop/Start/Parity (Configurable)
1200, 2400, 4800, 9600, 14400, 19200, 38400, 57600, 76800, 115200, 230400
ESSID; 1 - 31 Character Text String
TCP/IP, UDP, ARP, Radius/802.1x, DHCP, DNS, PPP, ICMP, HTTP, FTP, TFTP, TELNET, MODBUS-RTU and MODBUS-

Access Point/Client/Bridge/Router/VLAN Point-to-Point, Point-to-Multi-point Wireless Distribution System (AP - AP Repeater) Modbus TCP/RTU Gateway Serial Client/Server/Multicast Simultaneous RS232/485 Connection Embedded Modbus Master/Slave for I/O Transfer User Configurable Parameters via HTTPS Embedded Web Server Network Access - Ethernet Data Encryption - 802.11i with CCMP 128-bit AES Support for 802.1x Radius Server Secure HTTP Protocol MAC Address - Whitelist/Blacklist

IP Filtering – Whitelist/Blacklist
ARP/GARP Filtering – Whitelist/Blacklist
$2~x$ Female SMA Standard Polarity 50Ω Supports signal diversity or high-gain antenna
-40 to 60°C (-40 to 140°F)
0 - 99% RH non-condensing
9 to 30 VDC; Under/Over Voltage Protection
270 mA @ 12V (idle); 140 mA @ 24V (idle)
470 mA @ 12V (400 mW), 250 mA @ 24V (400 mW)
FCC CFR47 Part 15; EN 301 489-3; EN 301 489-5
FCC 15.247, RS210
CSA Class I, Division 2; ATEX; IECEx NA IIC; IEC 60950 (RoHS Compliant); cULus Listed
DIN-rail mounting
4.5" x 5.5" x 1.2" (114 x 140 x 30 mm)
1.0 lb (0.45 kg)
Powder-Coated Aluminium
DIN-Rail
Removable; Max conductor 12 AWG (2.5mm²)
Power/OK; RX; TX/Link; RS232; LAN; RS485; Digital I/O

put Voltage-Free Contact utput FET 30 VDC 500mA	

Direct Sequence Spread Spectrum (DSSS)
5.150-5.825 GHz
15-400 mW (data rate and country-specific)
Orthogonal frequency data modulation (OFDM)
-100 dBm @ 250 kbps, -74 dBm @ 108 Mbps (8% FER)
20-MHz spacing (27 channels, 5.150-5.8 GHz)
6-108 Mbps "Auto Mode" selects fastest rate possible relative to RSSI
3 miles (5 km) @ 400 mW
Range may be extended using repeater features
Ability to construct complex networks using multiple
repeaters and roaming features

10/100 BaseT RJ45, IEEE 802.3 compliant. Bridge/router functions work with all Ethernet protocols TCP/IP, UDP ARP, PPP, ICMP, HTTP, FTP, TFTP, TELNET, SNMP, RADIUS/802.1X, DHCP, OFDM

DB9 Female DCE; RTS/CTS/DTR/DCD
2-Pin Terminal Block – Non-Isolated Serial server, PPP, Modbus to Modbus TCP conversion
7/8 Data Bits; Stop/Start/Parity (Configurable)
1200, 2400, 4800, 9600, 14400, 19200, 38400, 57600, 76800, 115200, 230400

ESSID; 1 - 31 Character Text String TCP/IP, UDP, ARP, Radius/802.1x, DHCP, DNS, PPP, ICMP, HTTP, FTP, TELNET, MODBUS-RTU and MODBUS-TCP

Access Point/Client/Bridge/Router/VLAN Point-to-Point, Point-to-Multi-point Wireless Distribution System (AP - AP Repeater) Modbus TCP/RTU Gateway Serial Client/Server/Multicast Simultaneous RS232/485 Connection Embedded Modbus Master/Slave for I/O Transfer User Configurable Parameters via HTTPS Embedded Web Server Network Access - Ethernet Data Encryption - 802.11i with CCMP 128-bit AES Support for 802.1x Radius Server Secure HTTP Protocol

MAC Address - Whitelist/Blacklist

	AC Address – Whitelist/Blacklist Filtering – Whitelist/Blacklist			
	RP/GARP Filtering - Whitelist/Blacklist			
	x Female SMA Standard Polarity 50Ω			
Supports signal diversity or high-gain antenna -40 to +60°C; -40 to +140°F 0 - 99% RH Non-condensing 9 to 30 VDC; Under/Over Voltage Protection 270mA @ 12 VDC; 140mA @ 24 VDC				
			47	70 mA @ 12V (400 mW), 250 mA @ 24V (400 mW)
			FC	C Part 15; EN 301 489 - 17; AS/NZS CISPR22
			ΕN	I 300 328; FCC Part 15; RSS 210
			CSA Class I, Division 2; ATEX; IECEx NA IIC; IEC 60950 (RoHS Compliant); cULus Listed	
DIN-rail mounting				
4.	5" x 5.5" x 1.2" (114 x 140 x 30 mm)			
1.0	0 lb (0.45 kg)			
Po	wder-Coated Aluminium			
DI	N-Rail			
Re	movable; Max Conductor 12 AWG (2.5 mm²)			
Power/OK; RX; TX/Link; RS232; LAN; RS485; Digital I/O Serial Activity, Digital I/O, LAN 10/100Mbit Link				
			RSSI Measurements (dBm) Connectivity Information/ Statistics System Log File	
	out Voltage-Free Contact utput FET 30 VDC 500mA			


Туре	Part No.
WI-MOD-E-G	6720005054

Туре	Part No.
WI-MOD-E-A	6720005057

Ethernet Only Data

Industrial Wireless - Access point/bridge/client

- IEEE 802.11a/b/g compatible single radio module (2.4 GHz or 5 GHz band)
- Power input by redundant 24 V DC power inputs or Power-over-Ethernet
- Multi-SSID and VLAN support
- Turbo Roaming for seamless wireless connections
- Integrated DI/DO for on-site monitoring and warning
- QoS (WMM) support





Technical Data

WLAN Interface	
Standards	IEEE 802.11a/b/g/h for Wireless LAN
	IEEE 802.11i for Wireless Security
	IEEE 802.3u for 10/100BaseT(X)
	IEEE 802.3af for Power-over-Ethernet
	IEEE 802.1D for Spanning Tree Protocol
	IEEE 802.1w for Rapid STP
	•
	IEEE 802.1Q VLAN
Spread Spectrum and Modulation	 DSSS with DBPSK, DQPSK, CCK
(typical)	 OFDM with BPSK, QPSK, 16QAM, 64QAM
	 802.11b: CCK @ 11/5.5 Mbps,
	DQPSK @ 2 Mbps,DBPSK @ 11 Mbps
	 802.11a/g: 64QAM @ 54/48 Mbps,
	16QAM @ 36/24 Mbps, QPSK @ 18/12
	Mbps, BPSK @ 9/6 Mbps
Operating Channels (central	US: 2.412 to 2.462 GHz (11 channels)
	5.18 to 5.24 GHz (4 channels)
frequency)	,
	EU: 2.412 to 2.472 GHz (13 channels)
	5.18 to 5.24 GHz (4 channels)
Security	 SSID broadcast enable/disable
	 Firewall for MAC/IP/Protocol/Port-based
	filtering
	64-bit and 128-bit WEP encryption,
	WPA /WPA2-Personal and Enterprise
	(IEEE 802.1X/RADIUS, TKIP and AES)
Transmission Rates	802.11b: 1, 2, 5.5, 11 Mbps
	802.11a/g: 6, 9, 12, 18, 24, 36, 48, 54 Mbps
TX Transmit Power	802.11b: Typ. 23±1.5 dBm @ 1 to 11 Mbps
	802.11g: Typ. 20±1.5 dBm @ 6 to 24 Mbps,
	Typ. 19±1.5 dBm @ 36 Mbps,
	Typ. 18±1.5 dBm @ 48 Mbps,
	,,
	Typ. 17±1.5 dBm @ 54 Mbps
	802.11a: Typ. 18±1.5 dBm @ 6 to 24 Mbps,
	Typ. 16±1.5 dBm @ 36 to 48 Mbps,
	Typ. 15±1.5 dBm @ 54 Mbps
RX Sensitivity	802.11b: -97 dBm @ 1 Mbps, -94 dBm @ 2 Mbps,
•	-92 dBm @ 5.5 Mbps, -90 dBm @ 11 Mbps
	802.11g: -93 dBm @ 6 Mbps, -91 dBm @ 9 Mbps,
	-90 dBm @ 12 Mbps, -88 dBm @ 18 Mbps,
	• • • • • • • • • • • • • • • • • • • •
	-84 dBm @ 24 Mbps, -80 dBm @ 36 Mbps,
	-76 dBm @ 48 Mbps, -74 dBm @ 54 Mbps
	802.11a: -90 dBm @ 6 Mbps, -89 dBm @ 9 Mbps,
	-89 dBm @ 12 Mbps, -85 dBm @ 18 Mbps
	-83 dBm @ 24 Mbps, -79 dBm @ 36 Mbps
	-75 dBm @ 48 Mbps, -74 dBm @ 54 Mbps
Protocol Support	
General Protocols:	Proxy ARP, DNS, HTTP, HTTPS, IP, ICMP, SNTP
General Frotocols:	
	TCP, UDP, RADIUS, SNMP, PPPoE, DHCP
AP-only Protocols:	ARP, BOOTP, DHCP, dynamic VLAN-Tags for
	802.1X-Clients, STP/RSTP (IEEE 802.1D/w)
Interface	
Default Antenna	2 dBi dual-band omni-directional antenna.
Delault Antenna	•
	RP-SMA (male)
Connector for External Antennas	RP-SMA (female)
LAN Port	10/100BaseT(X), auto negotiation speed
	· · · · · · · · · · · · · · · · · · ·

(RJ45-type)

Wireless Data Modems—WLAN









Interface (continued)		
Console Port	RS-232 (RJ45-type)	
LED Indicators	PWR1, PWR2, PoE, FAULT, STATE, signal	
	strength, CLIENT MODE, BRIDGE MODE,	
	WLAN, 10M, 100M	
Alarm Contact	1 relay output with current carrying capacity	
	of 1 A @ 24 VDC	
Digital Inputs	2 electrically isolated inputs	
	 +13 to +30 V for state "1" 	
	 +3 to -30 V for state "0" 	
	Max. input current: 8 mA	
Physical Characteristics		
Housing	Metal, IP30 protection	
Weight	850 g	
Dimensions	53.6 x 135 x 105 mm (2.11 x 5.31 x 4.13 in)	
Installation	DIN-Rail mounting	
Environmental Limits		
Operating Temperature	0 to 60° C (32 to 140° F)	
Storage Temperature	-40 to 85° C (-40 to 185° F)	
Ambient Relative Humidity	5% to 95% (non-condensing)	
Power Requirements		
Input Voltage	12 to 48 V DC, redundant dual DC power	
	inputs or 48 V DC Power-over-Ethernet	
	(IEEE 802.3af compliant)	
Connector	10-pin Pluggable Terminal (0.2-1.5mm²)	
Connector	28-14 AWG	
Power Consumption	• 0.121 to 0.494 A @ 12 to 48 VDC	
	• 0.3 A @ 24 VDC	
Reverse Polarity Protection	Present	
Regulatory Approvals		
Safety	EN60950-1, UL60950-1	
Radio	EN300 328, EN301 893,	
EMC	EN301 489-1/-17, FCC Part 15 Subpart B	
	Class B, EN55022/55024	
Hazardous Location	UL/cUL Class I, Div. 2; ATEX Class I, Zone 2	
MTBF	392.209 hrs	
Warranty		
Warranty Period	5 years	

Models	Model Type	Operating Temperature	Part No.
IEEE 802.11a/b/g wireless AP/	IE-WL-AP-BR-CL-ABG-EU	0 to +60° C	1242100000
Bridge/Client (European version) IEEE 802.11a/b/g wireless AP/	IE-WLT-AP-BR-CL-ABG-EU IE-WL-AP-BR-CL-ABG-US	-40 to +75° C 0 to +60° C	1286480000
Bridge/Client for American market	IE-WLT-AP-BR-CL-ABG-US	-40 to +75° C	1286490000
Accessories	Model Type		Part No.
Accessories External Backup and Restore Module	Model Type EBR-Module RS232		Part No.

Wireless Data Modems - Licensed Frequencies

Licensed frequencies have many advantages and are ideal for industrial applications. The Weidmuller product offers powerful long-range communications to extend Ethernet networks in difficult-to-reach locations. Flexible options available support 360 to 512MHz (MHz) as well as 930 to 960MHz (60MHz) configurations, providing users with an integrated and complete industrial Ethernet infrastructure solution.

The FCC (United Stated) and Industry Canada (Canada) has information to help you through the licensing process. You can find the basic information you need to begin the process. If you are engaged in Public Safety Radio Activities, you can go directly to:

FCC: http://wireless.fcc.gov/publicsafety **Industry Canada:** http://www.ic.gc.ca/eic/site/sd-sd.nsf/eng/home

Aging Infrastructure



Process Control



Movable Machinery



Licensees in the Industrial/Business Radio Pool are issued to radio users to support business operations. Their communications systems are used for support of day-to-day business activities, such as dispatching, AVL and diverting personnel or work vehicles, coordinating the activities of workers and machines on location, or remotely monitoring and controlling equipment with data radio modems.

Applications

- · Remote Well Head Monitoring
- Pipeline Leak Detection
- PLC Networks
- · Environmental Monitoring
- Water Treatment Facilities
- Mining Operations Infrastructure
- Tank Farm Monitoring



The Weidmuller Wireless Ethernet Modem is a robust, licensed and license-free wireless transceiver capable of ultra-long range communications.

With models operating at 360 to 512MHz and 930 to 960MHz up to 5.0W, the modems are optimized for throughputs of up to 19.2kbps. This provides robust and secure two-way wireless communications in extremely challenging outdoor environments; over obstructed paths typical of remote monitoring and control applications.

Capable of operating in Access Point/Client configuration, functioning as a network Bridge/Router, or serving as a Serial Server (RS232/485), the devices use over-the-air data compression to ensure maximum throughput. Integrated Modbus server capability allows seamless integration with smart sensors, RTU's or I/O expansion through the use of WI-I/O-EX-1-S Expansion modules.

Features

- 10mW 5W RF Power
- Access Point/Client and Bridge/Router Configuration
- Spanning Tree (Self Healing) Support
- Designed for Industrial, High Noise Environments
- Over-The-Air Network Diagnostics and Configuration
- VLAN Tagging Supported for Bridging and Routing Modes
- Network Management Capabilities
- Frequencies Configured Via Built-In Webserver

WI-MOD-400-E Licensed Serial and Ethernet 400MHz 5W modem



WI-MOD-950-E Licensed Serial and Ethernet 900MHz 5W modem



Technical Data

Technical Data
Transmitter/Receiver
Frequency - USA/Canada
Transmit Power
Radio Transceiver/Modulation
nadio fransceiver/iviodulation
Channel Bandwidth
Receiver Sensitivity
Data Rates
Observation of the second of t
Channel Spacing
Radio Range
Protocol
Security
Configuration
Diagnostics
Ed. (0. 'I.D.)
Ethernet/Serial Port
Ethernet
Embedded Protocols:
Serial
RS232 V.24 DCE
RS485
Serial Settings
Data Rate (Bps)
Protocols/Configuration
System Address
Protocols Supported
Network Parameters
11
User Configuration
Security
Bandwidth Protection
General Data
Antenna Connection
Operating Temperature Humidity
Power Supply
Current Consumption Idle:
Transmit:
EMC
RF (Radio)
Approvals
Mounting
Dimensions (LxWxH) mm
Weight
Housing
Mounting
Terminal Blocks
Terminal Blocks LED Indication
LED Indication

360 - 380MHz, 380 - 400MHz, 400 - 420MHz, 420
- 440MHz, 430 - 450MHz, 450 - 470MHz, 470 -
490MHz, 490 – 512MHz
0.5 - 5.0W(1) (+27 to +37dBm)
2-level FSK or 4-level FSK
12.5 kHz / 25 kHz

12.5 kHz / 25 kHz
12.5kHz: -100dBm (9600bps), -111dBm (4800bps) 25.0kHz: -99dBm (19.2kbps), -110dBm (9600bps)
12.5kHz: 4800bps, 9600bps 25.0kHz: 9600bps, 19.2kbps
12.5kHz, 25.0kHz (Supports 5 or 6.25kHz Frequency Steps)
31 miles (50 km) @ 5W / 6 miles (10 km) @ 0.5W Range may be extended using repeater features
CSMA/CA with 32 bit CRC and auto-correction
WPA PSK - 80211i - 802.1x MAC Filtering; IP Filtering; ARP Filtering Password protected configuration
LITTO with remarks configuration via windows link

RSSI, channel noise, BER, connection monitoring and statistics
10/100baseT; Auto MDX Bridge/router functions work with all Ethernet protocols
TCP/IP, UDP ARP, PPP, ICMP, HTTP, FTP, TFTP, TELNET, SNMP, RADIUS/802.1X, DHCP, OFDM

HTTP with remote configuration via wireless link

DB9 Female DCE
2-Pin Terminal Block (Configurable Termination) Serial server, PPP, Modbus to Modbus TCP conversion
7/8 Data Bits; Stop/Start/Parity (Configurable)
1200, 2400, 4800, 9600, 14400, 19200, 38400, 57600, 115200, 230400

ESSID; 1 - 31 Character Text String
TCP/IP, UDP, ARP, Radius/802.1x, DHCP, DNS, PPP, ICMP, HTTP, FTP, TFTP, TELNET, MODBUS-RTU and MODBUS-TCP
Single Point to Point, Central Master with Multiple Slaves,

Single Point to Point, Central Master with Multiple Slaves, Large Fixed Network, Network with Roaming Stations, Redundant Radio Paths, Automatic Selection of Radio Paths, Prioritization of Traffic Flows, Bandwidth Efficiency Features, Bandwidth Utilization, Routing, Bridging, VLAN Remote Access - Over-the-Air, Local Access - USB, Network Access - Ethernet

WPA-PSK, WPA-Enterprise, Password Protected
MAC Address - Whitelist/Blacklist
IP Filtering - Whitelist/Blacklist
ARP/GARP Filtering - Whitelist/Blacklist

Single Female SMA 50Ω
-30 to 60°C (-20 to 140°F)
99% non-condensing
9 to 30 VDC; Under/Over Voltage Protection
120mA @ 13.8V; 70mA @ 24V
1.5A @ 13.8V (5W); 650mA @ 24V (5W)
FCC CFR47 Part 15; EN 301 489-3; EN 301 489-5
FCC CFR47 Part 90; IC RSS 119; EN 300 113; EN 300 220; AS/NZS4295
Class I, Division 2; IEC EX Zone 2; ATEX Zone 2; EN/IEC 60950-1; UL Listed (pending)
DIN-rail mounting
168 x 114 x 30mm (6.7" x 4.5" x 1.2")
< 0.55 kg / 1.2 lb
Powder-Coated Aluminium
DIN-rail
Removable; Max conductor 12 AWG (2.5mm²)
Power/OK; RX; TX/Link; RS232; LAN; RS485; Digital I/O Serial Activity, Digital I/O, LAN 10/100Mbit Link

Diagnostics available through web pages or optional Network Management System

FET to Ground to Activate External Circuits
Max Voltage 30 VDC, Max Current 500mA ON 2.0 VDC,
OFF 3.0 VDC, 30 VDC max;
Single Analog Input Range 0 - 25mA, Accuracy +/- 0.5%

928 - 960MHz (User Set)

0.5 - 5.0W(1) (+27 to +37dBm)
Based on 802.11 Meshing Standard, operating at lower data rates. Half Duplex UHF radio supports operation on Licensed 900MHz bands.
12.5 kHz / 25 kHz
12.5kHz Channel 19,200 baud @ -100 dBm; 9600 baud @ -111 dBm 25kHz Channel 19,200 baud @ -99 dBm; 9600 baud @ -110 dBm
12.5kHz bandwidth - 4800 baud, 9600 baud 25 kHz bandwidth - 9600 baud, 19,200 baud
12.5kHz, 25.0kHz (Supports 5 or 6.25kHz Frequency Steps)
31 miles (50 km) @ 5W / 6 miles (10 km) @ 0.5W Range may be extended using repeater features
CSMA/CA with 32 bit CRC and auto-correction
WPA PSK - 80211i - 802.1x MAC Filtering; IP Filtering; ARP Filtering Password protected configuration
HTTP with remote configuration via wireless link
RSSI, channel noise, BER, connection monitoring and statistics
10/100 B T DIAF IFFF 000 0

10/100 BaseT RJ45, IEEE 802.3 compliant.
Bridge/router functions work with all Ethernet protocols
TCP/IP, UDP ARP, PPP, ICMP, HTTP, FTP, TFTP, TELNET, SNMP, RADIUS/802.1X, DHCP, OFDM

1.2 to 2	230.4 Kb/s	
1.2 to 2	230.4 Kb/s	
Serial s	server, PPP, Modbus to Modbus T	CP conversion

ESSID; 1 – 31 Character Text String	
TCP/IP, UDP, ARP, Radius/802.1x, DHCP, DNS, PPP, ICM HTTP, FTP, TFTP, TELNET, MODBUS-RTU and MODBUS-TCP	IP

Single Point to Point, Central Master with Multiple Slaves, Large Fixed Network, Network with Roaming Stations, Redundant Radio Paths, Automatic Selection of Radio Paths, Prioritization of Traffic Flows, Bandwidth Efficiency Features, Bandwidth Utilization, Routing, Bridging, VLAN Remote Access - Over-the-Air, Local Access - USB, Network Access - Ethernet

WPA-PSK, WPA-Enterprise, Password Protected
MAC Address – Whitelist/Blacklist
IP Filtering – Whitelist/Blacklist
ARP/GARP Filtering – Whitelist/Blacklist

Single Female SMA 50Ω
-30 to 60°C (-20 to 140°F)
99% non-condensing
9 to 30 VDC; Under/Over Voltage Protection
270mA @ 12 VDC; 140mA @ 24 VDC
2.5A @ 9 VDC (5W); 0.75A @ 30 VDC (5W)
FCC CFR47 Part 15; EN 301 489-3; EN 301 489-5
FCC CFR47 Part 90; IC RSS 119; EN 300 113; EN 300 220; AS/NZS4295
UL Listed (pending)

FCC CFR47 Part 15; EN 301 489-3; EN 301 489-5
FCC CFR47 Part 90; IC RSS 119; EN 300 113; EN 300 220; AS/NZS4295
UL Listed (pending)
DIN-rail mounting
168 x 114 x 30mm (6.7" x 4.5" x 1.2")
< 0.55 kg / 1.2 lb
Powder-Coated Aluminium
DIN-rail
Removable; Max conductor 12 AWG (2.5mm²)
Power/OK; RX; TX/Link; RS232; LAN; RS485; Digital I/O Serial Activity, Digital I/O, LAN 10/100Mbit Link
Diagnostics available through web pages or optional Network Management System
FET to Ground to Activate External Circuits Max Voltage 30 VDC, Max Current 500mA ON 2.0 VDC, OFF 3.0 VDC, 30 VDC max; Single Analog Input Range 0 - 25mA, Accuracy +/- 0.5%

Ordering Data

Input/Output Configurable DI/DO/AI

	Туре	Part No.
	WI-MOD-400-E-5W	6720005017
Note	Default 450–470MHz Band. Consult factory for other bands.	

Туре	Part No.
WI-MOD-950-E-5W	6720005018

Enclosures

Specialty Enclosures

At Weidmuller, we have the resources and capabilities to design and build both industrial and ATEX certified enclosures. We handle every aspect of the process:

- Initial design specifications
- Assembly and installation of box elements
- Design and specification of DIN-rail modules
- Terminal wiring
- Specifying, ordering and integrating third-party products
- Application of special coatings
- Adding elements such as mounting plates and holes or knockouts for cable glands
- Providing full ATEX certification and documentation

Weidmuller is a Certified ATEX Installation House—ATEX licensed to design and build ATEX certified enclosures, providing you with all the required documentation and certification and reducing your risk in hazardous locations.

All this means that you don't have to spend your time specifying, ordering and managing inventory for your projects. Design-Build-Deliver Services and Solutions does all this and more.

Upon completion, we'll ship your industrial or ATEX certified enclosure to any location you specify-on time and on budget.









Weidmuller is a licensed ATEX manufacturer—our ATEX certified enclosures meet multiple global standards and regulations and ensure that you have certified hazardous location protection.



Pre-configured Wireless Enclosures

Weidmuller is pleased to offer three pre-configured and assembled Wireless Enclosure Solutions. These three wireless enclosures feature plastic or metal enclosures with either Wireless Ethernet Modems or Radio Frequency (RF) Transmitters/Receivers. Just connect power and your signals and you are wireless!





The Ethernet solution is available in both a stainless steel or plastic enclosure and features a Weidmuller wireless Ethernet (WiFi) 2.4Ghz modem, which can function as an access point, bridge, client or router.

In addition to the modem technology, the enclosure comes complete with the following components: power supply, circuit protection, surge protection, terminal blocks, ground blocks, antenna, antenna connection cables and through panel cable glands.

This complete, preassembled solution provides all the necessary elements for a remote wireless Ethernet installation.

Ordering Data

	Part No.
Wireless Ethernet Enclosure - Stainless Steel Solution	6760004616
Dimensions mm/in (h x w x d)	458 x 382 x 205 / 18.03 x 15.04 x 8.07

Features:

- NEMA4X Stainless Steel Enclosure
- 2.4GHz (WiFi) Wireless Ethernet modem
- Operate as a Client/Bridge/Access Point/Router with a 400mW transmit power
- Built in Security/Encryption including AES and WEP with matching antenna and all cabling
- · Assembled, wired and tested!
- Surge protection included
- Transmit range up to 3 miles with appropriate antenna
- Data transmission rates up to 54Mbps

Ordering Data

	Part No.
Wireless Ethernet Enclosure - Plastic Solution	6760004617
Dimensions mm/in (h x w x d)	356 x 305 x 212 / 14.02 x 12.01 x 8.35

Features:

- NEMA 4X Plastic Enclosure
- 2.4GHz (WiFi) Wireless Ethernet modem
- Operate as a Client/Bridge/Access Point/Router with a 400mW transmit power
- Built in Security/Encryption including AES and WEP with matching antenna and all cabling
- · Assembled, wired and tested!
- Surge protection included
- Transmit range up to 3 miles with appropriate antenna
- Data transmission rates up to 54Mbps

The I/O version is comprised of two preassembled plastic enclosures. Each enclosure contains a power supply, circuit protection, surge protection, antenna, antenna connection cables and terminal blocks.

In addition to these components, one enclosure houses a transmitter and the second enclosure houses a receiver. The transmitter and receiver operate on 900Mhz radio bands and are preconfigured to send and receive multiple I/O signals. The I/O solution can transmit and receive two digital signals and one analog signal over a range of several miles.


This self-contained solution is designed for quick and easy set-up. The pre-installed terminals make I/O and power connections fast and easy, for "out of the box" operation.

Ordering Data

	Part No.
Wireless I/O 900MHz - Plastic Solution	6760004618
Dimensions mm/in (h x w x d)	307 x 256 x 162 / 12.08 x 10.09 x 6.38

Features:

- Two pre-assembled NEMA4x Plastic Enclosures and Full IP67 Ingress protection
- 900MHz (Frequency Hopping) Transmitter and Receiver with a 1W transmit power
- Preconfigured and mapped I/O with matching antenna and all cabling
- Surge protection included
- · Cable glands included for signal and power access
- · Assembled, wired and tested!
- Transmit range up to 20 miles with appropriate antenna
- Transmitter accepts up to 1 analog and 2 digital intputs
- Receiver accepts up to 1 analog and 2 digital outputs




Applications for cellular routers are not designed for just one vertical market

Typical Applications:

- Networking Wind Turbines and Solar Collectors
- · Electricity Network Control
- Tank Farm Monitoring
- · Water Distribution Network
- · Environmental Monitoring





Features	Benefits	
5 Band Multicarrier Cellular Modem	Speeds of up to 21 Mbps	
Receiver Antenna Diversity	Weak Signal Strength is less of an issue	
Integrated VPN Capability	Monitoring & Control of Communications	
IPsec & GRE Tunneling	Ensures Secure Transmission	
Built-in DHCP Server & Port Forwarding	Simplifies Networking	
Dual Ethernet ports	Adds flexibility	
Over the Air Network Diagnostics & Configuration	Optimizes Operational Performance	

Connection of Communications Networks


Maximum security with the Industrial Ethernet Router

Communication networks used for office applications and for automation are converging. The advantages that result from this process are put into practice more and more frequently because they make procedures more transparent and facilitate data exchange substantially.

Weidmuller's Industrial Ethernet Router ensures that different networks interoperate in unison and with top-level security.

Application example:

Well maintenance and real time data collection. Cellular to main office; WiFi connection locally between wells.





Intelligent firewall: Stateful packet inspection

Our routers ship with a firewall with configurable filter functions that adapt automatically to the network traffic they see (stateful package inspection). This firewall recognizes the messages that are stateful, i.e. legitimized and let them pass. Unidentified packets are kept out of your industrial networks.

Application example:

Device Monitoring of OEM equipment







Want to be able to communicate with machinery and systems securely, reliably and from anywhere?

The router can translate between the addresses of various networks with protocols like port forwarding and 1:1 NAT masquerading.

These functions conceal all of the machine's IP address downstream of the router.





Communication between networks is done securely via the two Gigabit ports on the LAN/WAN interface.

The integrated VPN is also ideally suited to secure remote access to the LAN, via either a wired or wireless 3G/UMTS Internet connection.

Gigabit Industrial Security Router

- 2 Gigabit ports (LAN/WAN)
- Integrated firewall
- NAT masquerading, 1:1 network mapping and port forwarding
- Remote access via VPN (OpenVPN, IPsec, L2TP)
- Key switch function for activation/deactivation of WAN/ VPN connection
- Variant with integrated 3G/UMTS modem for rapid, Internet-based wireless access
- Back-up and recovery of device configuration using SIM card
- Full Layer 2/3 Router





Technical data

Modes

Modes	
IP-Router	Static or dynamic routing, supporting RIPv2 / OSPF
Transparent Bridge	2-port switch with additional layer-2 filter
Network Services	
	DHCP server / DHCP relay
	DNS relay
	NTP client
	DynDNS (DHCP client by RFC 2136)
Firewall	
	IPv4 Stateful inspection Firewall (incoming/outgoing)
	 NAT-Masquerading, 1:1 NAT, Portforwarding Layer-2/3-Filter (VLAN ID, VLAN, QoS tag,
	MAC address, Ethertype frame)
	"Auto learning" feature to create packet filter rules
	(analysis of network traffic)
	 Layer 2/3-based packet prioritization
	(Ethernet frame, IP header, VLAN tag)
VPN	
	Configurable as OpenVPN server or client
	(Layer 2 and Layer 3)
OpenVPN	Authentication with X.509 Certificates Tunnel support via HTTP provi
	 Tunnel support via HTTP proxy Maximum of 10 different client or server configurations
	Unlimited number of client connections in server mode
	Can be configured as an IPsec server or client
	PSK authentication (user ID, password)
	or X.509 certificates
IPsec	 Hardware-based encryption for faster data throughput
11 300	A maximum of 64 simultaneous connections
	(subnet to subnet or as an IPsec server)
	 Encryption algorithms DES-56, 3DES-168, AES 128, AES 192, AES-256
Management	220 00, 0220 100,7120 120,7120 102,7120 200
	Configuration via WEB interface (HTTP / HTTPS)
	Web interface in German or English
	Configuration support through detailed help
	information (tooltip)
	Configurable multi-user access with definable rights mask
	Support of SNMP v1/v2/v3, event log / syslog
Other	
Modbus/TCP	Integrated Modbus TCP Server for status queries, and software-based activation / de-activation of VPN connections
	"Remote Capture" feature for network diagnostics via a
Diagnosis	connected PC (Wireshark)
	Client Monitoring (via ICMP) with alarm function
Monitoring	in case of error
Interfaces	
RJ45 ports	2x10/100/1000BaseT(X)
USB port	Option for future expansion
SCM card reader	Save and restore of the configuration using a smart card (memory chip)
	Signaling states for power, status, cut, alert, active VPN
LED indicators	connection and an active UMTS connection
	"Alarm" -> Indicates a configurable network status or
Digital outputs	error (24 V out)
Digital outputs	 "VPN-active" -> Indicates an active VPN connection
	(24 V out)

Interfaces (continued)
Digital inputs	"Cut" -> Disconnects physically (link down) the WAN port (24 V) "VPN-initiate" -> Enables a pre-configured VPN connection (24 V)
Reset button	Restoring the factory default
Power requirements	
Input Voltage	1x 24 V DC (7 to 36 volts)
Current consumption	max. 600 mA @ 24 V DC
Technical data (housi	ng)
Housing	Metal, IP 30 protection
Dimensions (W x H x D)	35 x 159 x 134 mm (without antenna) 35 x 255 x 134 mm (with UMTS SMA female antenna)
Installation	TS 35
Environmental Limits	
Operating temperature	-20 °C to +70 °C
Storage Temperature	-20 °C to +85 °C
Ambient humidity	6 to 90 % not condensing
DSL and UMTS/HSPA	
DSL	Connection to the DSL modem via LAN or WAN port Free configuration of the PPPoE login
DynDNS	Support automatic registration
UMTS/3G	Built-in quad-band UMTS / HSPA modem (only variant IE-SR-2GT-UMTS/3G) 1.1 Mbps peak downlink, uplink 5.8 Mbps peak WCDMA 850/1900/2100 MHz GSM/GPRS/EDGE 850/900/1800/1900 MHz CC, IC, CE, GCF, PTCRB, A-Tick, AT&T, Telstra, NTT, DoCoMo, Softbank, Bell
Approvals	
Security	cULus Listed
EMC	FCC Part 15 Class A, EN 55022 Class A, EN61000-4-2 (ESD), EN61000-4-3 (RS) EN61000-4-4 (EFT), EN61000-4-5 (Surge), EN61000-4-6 (CS)
Shock	DIN EN 60068-2-27
Vibration	DIN EN 60068-2-6
Warranty	
Warranty Period	3 years

Models	Туре	Part No.
LAN/WAN router	IE-SR-2GT-LAN	1345270000
LAN/WAN router with integrated UMTS/3G modem	IE-SR-2GT-UMTS/3G	1345250000

Multi-Service Provider Cellular Modem and Router

The 615M-1 is a powerful Multi-Service Provider Cellular Broadband Router that delivers wireless data connectivity for up to two LAN connections and one serial port through public cellular networks at 3G network speeds.

- High Speeds Speeds up to 14.4Mbps with backward compatibility
- Multicarrier Compatibility and Carrier Redundancy -GPRS/EDGE, UMTS/HSPA; EVDO RevO/A, 1xRTT
- VPN Functionality Internal PPTP VPN Server and Client
- Supports Industrial Networking Protocols
- Meets Key Certifications and Compliance UL Listed, Class I Division 2, FCC Part 15, Industry Canada, CE, A-Tick, IEC 60950-1, PTCRB
- Carrier Specific Approvals: AT&T, Verizon, Sprint, Rogers, Telstra, Optus, Vodaphone
- DIN-rail mount or panel mount, Simple and fast installation





Technical data

lechnical data	
Transceiver/Receiv	er
	Quad-band 850/900/1900/2100MHz/AWS(1,2)
	Quad-band 850/900/1800/1900MHz(3,4)
Frequency	800MHz Cellular/1900MHz PCS/2100MHz(5)
	800MHz Cellular/1900MHz PCS/2100MHz(6)
	800MHz Cellular/1900MHz PCS(7)
Transmit Power (Max)	250mW(1,2); 2W(3,4); 250mW(5,6,7)
Transmission	UMTS, HSPA, EDGE, GPRS, EVDO Rev A (IS-856-A), 1xEVDO Rev 0 (IS-856), 1xRTT (IS-2000)
Modulation	UMTS, HSPA, EDGE, GPRS, EVDO Rev A (IS-856-A), 1xEVDO Rev 0 (IS-856), 1xRTT (IS-2000)
Receive Sensitivity	-109dBm(1); -109dBm(2); -105dBm(3,4); -107dBm(5,6,7)
Channel Spacing	5MHz(1,2); 10MHz(2); 1.25MHz(5,6,7)
	Downlink up to 384kbps; Uplink up to 384kbps(1)
	Downlink up to 14.4Mbps; Uplink up to 5.76Mbps(2)
	Downlink up to 236kbps; Uplink up to 236kbps(3)
Data Rate	Downlink up to 115kbps; Uplink up to 115kbps(4)
	Downlink up to 3.1Mbps; Uplink up to 1.8Mbps(5)
	Downlink up to 2.4Mbps; Uplink up to 153.6kbps(6)
	Downlink up to 153.6kbps; Uplink up to 153.6kbps(7)
Range (LoS)	Cellular Depends on Service Provider
Antenna Connector	2 x Female SMA Standard Polarity(1,2,3,4,5,6,7)
Input/Output	
Discrete Input	ON 2.3 VDC, OFF 0.7 VDC, 5.5 VDC max(8)
B:	NPN Transistor Close to Digital Ground, Pull Down
Discrete Output	100ohm(8)
Relay Outputs	Max Voltage 30 VDC, Max Current 1A(8)
Analog Inputs	Voltage Input Range 0 – 30 VDC, Accuracy +/-0.2 VDC(8)
Interfaces	
	10/100baseT; RJ45 Connector - 2 x IEEE 802.3
Ethernet Port	(Auto MDIX)
Link Activity	Activity LED
Serial Port RS232	DB9 Female DCE
Data Rate (Bps)	1200, 2400, 4800, 9600, 14400, 19200, 38400, 57600, 76800, 115200
Serial Settings	8 Data Bits; No Stop/1 Start/Parity (Configurable)
Protocols and Configuration	
Protocols Supported	TCP/IP, UDP, ARP, ICMP, FTP, TFTP, TELNET, PING, GPS-NMEA (optional), DHCP; MAC Filtering (Whitelist), IP Filtering (Blacklist), DMZ, Dynamic RADIUS/802.1x DNS, Port Forwarding; SNMP, HTTP Embedded Web Server; IPsec GRE Tunneling, PPTP, VPN,

Protocols and Configuration (continued)				
User Configuration	Configuration and Firmware Upgrades via HTTP/OTA (Over-The-Air)			
Configurable	Client/Router, Serial Client Server			
Parameters	Simultaneous RS232 Connection			
Security	VPN, SIM Card PIN, RADIUS, IPsec			
Bandwidth	MAC Address - Whitelist/Blacklist, IP Filtering - Protection Whitelist/Blacklist Network Management SNMP V2c, V3			
Approvals				
EMC	FCC Part 15; Industry Canada; CE; A-Tick			
RF (Radio)	EN 300 328; FCC Part 15			
Hazardous Area	Class I, Division 2; cULus			
Safety	IEC 60950-1			
UL	cULus Listed			
Environmental	MIL-STD-810F			
Approvals	PTCRB, Carrier Specific Approvals			
General				
Dimensions	109 x 153 x 45mm (4.3" x 6" x 1.8")			
Housing	Powder-coated Aluminum			
Mounting	DIN-rail, Panel Mount (Optional)			
Terminal Blocks	I/O: Removable Terminal Block, Screwless-Push in Wire, 18 - 28AWG			
Temperature Rating	-30 to +70°C; -22 to +158°F			
Humidity Rating	5 - 95% RH Non-condensing			
Weight	1.13kg (2.5lb)			
LED Indication	RSSI; SVC; NET; GPS; AUX			
Reported Diagnostics	Diagnostics Available Through Web Pages			
Power Supply				
Nominal Supply	9 to 28 VDC; Under/Over Voltage Protection & Reverse Polarity Molex 43025-0400 4-Pin Locking Connector			
Average Current Draw	130mA @ 13.8 VDC (Idle)			
Transmit Current Draw	350mA @ 13.8 VDC			

Type		Part No.
3G MODEM RS232 2DI 2DO 2/	AI 2AO	615M-1
Notes	(1) UMTS, (2) HSPA, (3) EDGE, (4) GPRS, (5) EVDO Rev A (IS-856-A), (6) 1xEVDO Rev ((7) 1xRTT (IS-2000), (8) Access via SNMP on	

Gigabit Industrial Security Router

- 2 Gigabit ports (LAN/WAN)
- Integrated firewall
- NAT masquerading, 1:1 network mapping and port forwarding
- Key switch function for activation/deactivation of WAN/VPN connection
- Back-up and recovery of device configuration using SIM card
- Full Layer 2/3 Router





Technical data

Technical dat	a
Modes	
IP-Router	Static or dynamic routing, supporting RIPv2 / OSPF
Transparent Bridge	2-port switch with additional layer-2 filter
Network Services	
	 DHCP server / DHCP relay DNS relay NTP client DynDNS (DHCP client by RFC 2136)
Firewall	
	IPv4 Stateful inspection Firewall (incoming/outgoing) AT-Masquerading, 1:1 NAT, Portforwarding Layer-2/3-Filter (VLAN ID, VLAN, QoS tag, MAC address, Ethertype frame) "Auto learning" feature to create packet filter rules (analysis of network traffic) Layer 2/3-based packet prioritization (Ethernet frame, IP header, VLAN tag)
Management	
	 Configuration via WEB interface (HTTP / HTTPS) Web interface in German or English Configuration support through detailed help information (tooltip) Configurable multi-user access with definable rights mask Support of SNMP v1/v2/v3, event log / syslog
Other	
Modbus/TCP	Integrated Modbus TCP Server for status queries
Diagnosis	"Remote Capture" feature for network diagnostics via a connected PC (Wireshark)
Monitoring	Client Monitoring (via ICMP) with alarm function in case of error
Interfaces	
RJ45 ports	2x10/100/1000BaseT(X)
USB port	Option for future expansion
SCM card reader	Save and restore of the configuration using a smart card (memory chip)
LED indicators	Signaling states for power, status, cut, alert, active VPN connection and an active UMTS connection
Digital outputs	"Alarm" -> Indicates a configurable network status or error (24 V out)
Digital inputs	"Cut" -> Disconnects physically (link down) the WAN port (24 V)
Reset button	Restoring the factory default

Power requirements	
Input Voltage	1x 24 VDC (7 to 36 volts)
Current consumption	max. 600 mA @ 24 VDC
Technical data (housi	ng)
Housing	Metal, IP 30 protection
Dimensions (W x H x D)	35 x 159 x 134 mm (without antenna) 35 x 255 x 134 mm (with UMTS antenna)
Installation	TS 35
Physical Dimensions	
Housing	Metal, IP 30 protection
Dimensions (WxHxD)	35 x 159 x 134 mm
Installation	TS 35
Environmental Limits	
Operating Temperature	-20 °C to +70 °C
Storage Temperature	-20 °C to +85 °C
Ambient Humidity	6 to 90 % not condensing
DSL	Connection to the DSL modem via LAN or WAN port Free configuration of the PPPoE login
DynDNS	Support automatic registration
Approvals	
Security	cULus Listed
EMC	FCC Part 15 Class A, EN 55022 Class A, EN61000-4-2 (ESD), EN61000-4-3 (RS) EN61000-4-4 (EFT), EN61000-4-5 (Surge), EN61000-4-6 (CS)
Shock	DIN EN 60068-2-27
Vibration	DIN EN 60068-2-6
Warranty	
Warranty Period	3 years
MTBF	135,270 hrs


Models	Туре	Part No.
LAN/WAN router	IF CD OCT FN	1489940000
(Firewall and NAT Only)	IE-SR-2GT-FN	1403340000

Wireless Accessories

900 MHz Antennas







Representative Photo

Representative Photo

Representative Photo

Whip and Dipole

Gain	Туре	Frequency Range	Description	Connector Type	Part No.
-2dBd	WI-ANT-900MHZ-0DBDUCKSMAM	806-960MHz	Direct attach	SMA male	6720005232
-2dBd	WI-ANT-DPL-DG900-1	900-930MHz	Mount Bkt & 3ft cable	SMA male	6720005086
OdBd	WI-ANT-DEMO-900	900-930MHz	Direct attach	SMA male	6720005089
OdBd	WI-ANT-DPL-0-16	853-930Mhz	Mount Bkt & 15ft cable	SMA male	6720005080
3dBd	WI-ANT-900MHZ-3DBSTUBMAG	896-940MHz	Only use with MAG Base	Determined by	6720005230
			6720005263	MAG BASE	
3dBd	WI-ANT-0.9/2.4GHZ-3/4DBMOBILE	902-928Mhz	Only use with thru- panel base	Determined by Base	6720005276
		(Dual Band)	6720005277	(NFemale)	

Omni

Gain	Туре	Frequency Range	Description	Connector Type	Part No.
OdBd	WI-ANT-900MHZ-0DB0MNINF	902-925MHz	Inc. 6720005271 clamp/brkt	N-Type Female	6720005233
3dBd	WI-ANT-900MHZ-3DB0MNINF	902-925MHz	Inc. 6720005271 clamp/brkt	N-Type Female	6720005234
5dBd	WI-ANT-900MHZ-5DB0MNINF	902-925MHz	Inc. 6720005271 clamp/brkt	N-Type Female	6720005235
7dBd	WI-ANT-900MHZ-7DB0MNINF	902-925MHz	Inc. 6720005272 clamp/brkt	N-Type Female	6720005236
3dBd	WI-ANT-950Mhz-3dbdOMNINF	890-960MHz	Inc. attached clamp/brkt	N-Type Female	6720005273
5dBd	WI-ANT-950Mhz-5dbdOMNINF	890-960MHz	Inc. attached clamp/brkt	N-Type Female	6720005274
7dBd	WI-ANT-950Mhz-7dbdOMNINF	890-960MHz	Inc. attached clamp/brkt	N-Type Female	6720005275

Directional

Gain	Туре	Frequency Range	Description	Connector Type	Part No.
3dBd	WI-ANT-900MHZ-3DBYAGINF	890-960Mhz	Inc. 6720005266 clamp/brkt	N-Type Female	6720005219
6.5dBd	WI-ANT-900MHZ-6.5DB-2'YAGINF	890-960Mhz	Inc. 6720005266 clamp/brkt	N-Type Female	6720005221
10dBd	WI-ANT-900MHZ-10DB-2'YAGINF	890-960Mhz	Inc. 6720005266 clamp/brkt	N-Type Female	6720005223
12dBd	WI-ANT-900MHZ-12DB-2'YAGINF	890-960Mhz	Inc. 6720005266 clamp/brkt	N-Type Female	6720005225
14dBd	WI-ANT-900MHZ-14DB-2'YAGINF	890-960Mhz	Inc. 6720005267 clamp/brkt	N-Type Female	6720005226

2.4 GHz Antennas







Whip and Dipole

Representative	Photo

Representative Photo

Representative Photo

Gain	Туре	Frequency Range	Description	Connector Type	Part No.
OdBi	WI-ANT-DEMO-2400	2.2-2.5GHz	Direct attach	SMA male	6720005099
2dBi	WI-ANT-24GHZ-2DB DUCK SMA-M	2.2-2.5GHz	Direct attach	SMA male	6720005207
3dBi	WI-ANT-24GHZ-3DB FOR MAG BASE	2.2-2.9GHz	Use with MAG base 6720005263	N-Type Female	6720005208
4dBd	WI-ANT-0.9/2.4GHZ-3/4DB MOBILE	2.4-2.5GHz (Dual Band)	Only use with thru-panel base 6720005277	Determined by Base (N Female)	6720005276

Omni

Gain	Туре	Frequency Range	Description	Connector Type	Part No.
4dBi	WI-ANT-24GHZ-4DB OMNI NF	2.4-2.5GHz	Inc. 6720005210 clamp/brkt	N-Type Female	6720005200
6dBi	WI-ANT-24GHZ-6DB OMNI NF	2.4-2.5GHz	Inc. 6720005210 clamp/brkt	N-Type Female	6720005201
6dBi	IE-ANT-O-BG-360-6-NF	2.4-2.5GHz	Inc. clamp/brkt	N-Type Female	1367090000
7dBi	IE-ANT-O-ABG-360-7-NF	2.4-5.8GHz	Low Profile - Inc. clamp/brkt	N-Type Female	1367130000
		(Dual Band)			
8dBi	WI-ANT-24GHZ-8DB OMNI NF	2.4-2.5GHz	Inc. 6720005210 clamp/brkt	N-Type Female	6720005204
10dBi	WI-ANT-24GHZ-10DB OMNI NF	2.4-2.5GHz	Inc. 6720005210 clamp/brkt	N-Type Female	6720005202
12dBi	WI-ANT-24GHZ-12DB OMNI NF	2.4-2.5GHz	Inc. 6720005211 clamp/brkt	N-Type Female	6720005203

Directional

Gain	Туре	Frequency Range	Description	Connector Type	Part No.
9dBi	IE-ANT-P-ABG-75-9-NF	2.4-5.8GHz (Dual Band)	Inc. attached clamp/brkt	N-Type Female	1367140000
9dBi (60°)	WI-ANT-24GHZ-9DB DFP 2'NF	2.3-2.5GHz	Inc. attached clamp/brkt	N-Type Female	6720005212
10dBi	WI-ANT-24GHZ-10DB YAGI NF	2.4-2.5GHz	Inc. attached clamp/brkt	N-Type Female	6720005205
13dBi (35°)	WI-ANT-24GHZ-13DB DFP 2'NF	2.3-2.5GHz	Inc. attached clamp/brkt	N-Type Female	6720005213
14dBi	WI-ANT-24GHZ-14DB YAGI NF	2.4-2.5GHz	Inc. attached clamp/brkt	N-Type Female	6720005206
18dBi (18°)	WI-ANT-24GHZ-18DB DFP 2'NF	2.3-2.5GHz	Inc. attached clamp/brkt	N-Type Female	6720005214

5.8 GHz Antennas







Representative Photo

Representative Photo

Representative Photo

Whip and Dipole

Gain	Туре	Frequency Range	Description	Connector Type	Part No.
4dBi	WI-ANT-5.8GHZ-4DB MOBILE	4.9-5.9GHz	Only use with thru-panel base	Determined by	6720005278
			6720005277	Base (N Female)	

Omni

Gain	Туре	Frequency Range	Description	Connector Type	Part No.
5dBi	IE-ANT-O-AH-360-5-NF	5.1-5.875GHz	Inc. clamp/brkt	N-Type Female	1367120000
7dBi	IE-ANT-O-ABG-360-7-NF	2.4-5.8GHz (Dual Band)	Low Profile - Inc. clamp/brkt	N-Type Female	1367130000
7dBi	WI-ANT-5.8GHZ-7DB OMNI NF	5.15-5.875GHz	Inc. attached clamp/brkt	N-Type Female	6720005283
10dBi	WI-ANT-5.8GHZ-10DB OMNI NF	5.15-5.875GHz	Inc. attached clamp/brkt	N-Type Female	6720005284

Directional

Gain	Туре	Frequency Range	Description	Connector Type	Part No.
9dBi	IE-ANT-P-ABG-75-9-NF	2.4-5.8GHz (Dual Band)	Inc. attached clamp/brkt	N-Type Female	1367140000
9dBi	WI-ANT-5.8GHZ-9DB DFP 2'NF	4.9-5.85GHz	Inc. attached clamp/brkt	N-Type Female	6720005280
11dBi	WI-ANT 5.8GHZ 11DB FLAT PATCH	5.7-5.875GHz	Inc. attached clamp/brkt	N-Type Female	6720005130
13dBi	WI-ANT-5.8GHZ-13DB DFP 2'NF	4.9-5.85GHz	Inc. attached clamp/brkt	N-Type Female	6720005281
18dB / 20dB	WI-ANT-5.8GHZ-20DB DFP 2'NF	4.9-5.85GHz	Inc. attached clamp/brkt	N-Type Female	6720005282

300-500MHz Antennas

Omni

Gain	Туре	Frequency Range	Description	Connector Type	Part No.
5dBd	WI-ANT-440MHZ-5DB OMNI NF	430-470MHz	Inc. attached clamp/brkt	N-Type Female	6720005439
3dbd	WI-ANT-450MHZ-3DB OMNI NF	450-460MHz	Inc. attached clamp/brkt	N-Type Female	6720005440
5dBd	WI-ANT-450MHZ-5DB OMNI NF	450-460MHz	Inc. attached clamp/brkt	N-Type Female	6720005436

Directional

Gain	Туре	Frequency Range	Description	Connector Type	Part No.
10dBd	WI-ANT-390Mhz-10dbdYAGINF	375-403Mhz	Inc. attached clamp/brkt	N-Type Female	6720005441
6.5dBd	WI-ANT-420Mhz-6dbdYAGINF	406-440Mhz	Inc. attached clamp/brkt	N-Type Female	6720005442
9dBd	WI-ANT-420Mhz-9dbdYAGINF	406-440Mhz	Inc. attached clamp/brkt	N-Type Female	6720005443
6.5dBd	WI-ANT-470Mhz-6dbdYAGINF	440-490MHZ	Inc. attached clamp/brkt	N-Type Female	6720005444
9dBd	WI-ANT-470Mhz-9dbdYAGINF	440-490MHZ	Inc. attached clamp/brkt	N-Type Female	6720005445
10dBd	WI-ANT-450MHZ-10DB YAGI	450-470MHz	Inc. attached clamp/brkt	N-Type Female	6720005435
9dBd	WI-ANT-470Mhz-9dbdYAGINF	470-512MHz	lnc. attached clamp/brkt	N-Type Female	6720005446

Cellular Band Antennas

Whip and Dipole

Gain	Туре	Frequency Range	Description	Connector Type	Part No.
OdBi	WI-ANT-900MHZ-0DBDUCKSMAM	806-960/	OdB STUB GSM ANT	SMA Male	6720005232
		1710-2170MHz	806/2017MHz SMA		
2dBi	WI-ANT-GSM-2DB LP	824-896MHz /	LOW-PROF GSM w/	SMA Male	6720005451
		1710-1990MHZ	5m SMA-M CBL		
3dBi	WI-ANT-GSM-LTE-3DB MOBILE	698-2700MHz	LTE 698-2700Mhz	Determined by	6720005450
			ANT - Base 6720005277	Base (N Female)	

Omni

Gain	Туре	Frequency Range	Description	Connector Type	Part No.
2dBi	IE-ANT-3G-806-2170-2-NF	806-960/ 1710-2170MHz	Omni (GSM / UMTS) Inc.	N-Type Female	1491160000
4dBi	IE-ANT-3G-806-2500-4-NF	806-960/	Omni thru-panel IP66	N-Type Female	1491170000
		1710-2170MHz			

Cables

Detailed cable specifications on pages 90 and 91.





Cable Length (ft)	Connector Type	dB Loss 900Mhz	dB Loss 2.4GHz	dB Loss 5.8GHz	Cable Type	Туре	Part No.
1	SMA male - SMA male	0.1	0.2	0.3	PFP 195	WI-ACC-TYP195-1FT SMA M-SMA M	6720005243
2	SMA male - SMA male	0.2	0.4	0.7	PFP 195	WI-ACC-TYP195-2FT SMA M-SMA M	6720005244
3	SMA male - SMA male	0.3	0.6	1.0	PFP 195	WI-ACC-TYP195-3FT SMA M-SMA M	6720005245
1	SMA male - N male	0.1	0.2	0.3	PFP 195	WI-ACC-TYP195-1FT SMA M-NM	6720005270
2	SMA male - N male	0.2	0.4	0.7	PFP 195	WI-ACC-TYP195-2FT SMA M-NM	6720005260
3	SMA male - N male	0.4	0.6	1.0	PFP 195	WI-ACC-TYP195-3FT SMA M-NM	6720005259
10	SMA male - N male	1.2	2.0	3.4	PFP 400	WI-ACC-TYP400-10FT SMA M-NM	6720005240
25	SMA male - N male	2.8	4.8	8.2	PFP 400	WI-ACC-TYP400-25FT SMA M-NM	6720005241
40	SMA male - N male	4.5	7.7	13.1	PFP 400	WI-ACC-TYP400-40FT SMA M-NM	6720005242
1	N male - N male	0.1	0.2	0.2	PFP 400	WI-ACC-TYP195-1FT NM-NM	6720005246
2	N male - N male	0.2	0.4	0.4	PFP 400	WI-ACC-TYP195-2FT NM-NM	6720005247
3	N male - N male	0.3	0.6	0.6	PFP 400	WI-ACC-TYP195-3FT NM-NM	6720005248
10	N male - N male	0.4	0.7	1.1	PFP 400	WI-ACC-TYP400-10FT NM-NM	6720005251
25	N male - N male	1.0	1.7	2.7	PFP 400	WI-ACC-TYP400-25FT NM-NM	6720005252
40	N male - N male	1.6	2.7	4.3	PFP 400	WI-ACC-TYP400-40FT NM-NM	6720005253
55	N male - N male	2.1	3.7	5.9	PFP 400	WI-ACC-TYP400-55FT NM-NM	6720005254
75	N male - N male	3.0	5.2	8.1	PFP 400	WI-ACC-TYP400-75FT NM-NM	6720005255
100	N male - N male	3.8	6.7	10.8	PFP 400	WI-ACC-TYP400-100FT NM-NM	6720005256
200	N male - N male	5.0	9.6	N/A	PFP 600	WI-ACC-TYP600-200FT NM-NM	6720005257

Other Cables

Length	Description	Туре	Connector Type	Part No
2m (6 ft.)	Cable	IE-CC-NM-RPSMAM-2M	RP-SMA to N male	1367110000
4m (12 ft.)	Cable	IE-CC-NM-RPSMAM-4M	RP-SMA to N male	1367100000
2m (6 ft.)	Cable	IE-CC-NM-SMAM-2M	SMA male to N male	1491180000
4m (12 ft.)	Cable	IE-CC-NM-SMAM-4M	SMA male to N male	1491190000
6m (18 ft.)	Cable	IE-CC-NM-SMAM-6M	SMA male to N male	1491210000

Hardware







Description	For use with	Туре	Part No.
DB9 Female RJ45 Serial Configuration Cable	WI-I/O 9-L units	WI-CSER-RJ45	6720005108
Antenna Mounting Brackets			
Angled Bracket for 4, 6, and 10 dBi 2.4 MHz Omnis	2.4 GHz antennas	WI-ACC-24GHZ-4610DB-ANG-BRKT	6720005209
Straight Bracket for 4, 6, and 10 dBi 2.4 MHz Omnis	2.4 GHz antennas	WI-ACC-24GHZ-4610DB-STR-BRKT	6720005210
Mounting Bracket for part number 6720005203	2.4 GHz antennas	WI-ACC-24GHZ-12DB-STR-BRKT	6720005211
Antenna MAG Base with 12' SMA male cable	2.4 GHz & 900 MHz antennas	WI-ACC-MAGBASE 12 RG58 SMA MALE	6720005263
Mounting Bracket for parts 6720005228 and 6720005229	900 MHz antennas	WI-ACC-900MHZ-OMNI-STR-BRKT	6720005268
Mounting Bracket for 900MHz 6.5, 10, 12 dBd Yagis	900 MHz antennas	WI-ACC-900MHZ-YAGI-STR-BRKT	6720005266
Mounting Bracket for part number 6720005226	900 MHz antennas	WI-ACC-900MHZ-14YAGI-STR-BRKT	6720005267
Mounting Bracket for part numbers 6720005233, 6720005234, 6720005235	900 MHz antennas	WI-ACC-900MHZ-0350MNI-STR-BRKT	6720005271
Mounting Bracket for part number 6720005236	900 MHz antennas	WI-ACC-900MHZ-70MNI-STR-BRKT	6720005272
Thru-panel mounting base for low profile antennas	6720005276 & 6720005278	WI-ACC-BH-BASE 5/8 HOLE NF	6720005277
Surge Protection & Bulkhead Mounts			
125-1000 MHz Surge Polyphaser N female - N female	Bulkhead & Surge ≤ 1 GHz	WI-ACC-125-1000MHZ SURGE NF-NF	6720005261
2-6 GHz Surge Polyphaser N female - N female	Bulkhead & Surge ≥ 2 GHz	WI-ACC-2-6GHZ SURGE NF-NF	6720005262
Bulkhead Adapter N female -N female	Bulkhead	WI-ACC-BULK-ADAPT NF-NF	6720005250
Bulkhead Adapter SMA female - SMA female	Bulkhead	WI-ACC-BULK SMA F - SMA F	6720005296
Class 1 Division 1 Bulkhead SMA male - SMA female	Bulkhead	WI-ACC-BULK-C1D1 SMA M - SMA M	6720005298
Class 1 Division 1 Bulkhead SMA male - N male	Bulkhead	WI-ACC-BULK-C1D1 SMA M - NM	6720005299
SMA male to SMA female <2.5Ghz (direct radio connection)	2.4 GHz & 900 MHz antennas	WI-DIV-CCMA	6720005111
Bandpass Filters			
Outdoor rated 900Mhz Band Pass Filter	900 MHz antennas	WI-ACC 900MHZ BAND PASS FILTER	6720005120
Outdoor rated 2.4Ghz Band Pass Filter	2.4 GHz antennas	WI-ACC 2.4GHZ BAND PASS FILTER	6720005121
Outdoor rated 5.8Ghz Band Pass Filter	5.8 GHz antennas	WI-ACC 5.8GHZ BAND PASS FILTER	6720005122


Adapters

Description	Туре	Part No.
Reverse-Polarity SMA Male - SMA Female	WI-ACC-ADAPT RP-SMA M - SMA F	6720005289
SMA male - SMA male Adapter	WI-ACC-ADAPT SMA M - SMA M	6720005290
SMA female - SMA female Adapter	WI-ACC-ADAPT SMA F - SMA F	6720005291
N male - N male Adapter	WI-ACC-ADAPT NM - NM	6720005292
N female - N female Adapter	WI-ACC-ADAPT NF - NF	6720005293
SMA female - N male Adapter	WI-ACC-ADAPT SMA F - NM	6720005294
SMA male - N female Adapter	WI-ACC-ADAPT SMA M - NF	6720005295
SMA female - SMA male Angled Adapter	WI-ACC-ADAPT SMA F - SMA M ANGL	6720005297






Connection DiagramsDirect Connect






SMA male



Enclosure with C1D1 Bulkhead









SMA male

SMA female

Enclosure with Standard Bulkhead & Surge Arrestor




Enclosure without Bulkhead (non-direct)




Radiation Patterns


2.4 GHz Omni Antennas




6720005200 Elevation Pattern




6720005201 Elevation Pattern



6720005202 Elevation Pattern




6720005203 Elevation Pattern




6720005204 Elevation Pattern

2.4 GHz Directional Antennas




6720005212 Azimuth Pattern




6720005212 Elevation Pattern


2.4 GHz Directional Antennas (continued)



900 MHz Omni Antennas



900 MHz Directional Antennas



Antennas

WI-ANT-5.8GHZ-4DB **MOBILE**

WI-ANT-5.8GHZ-7DB **OMNI NF**

WI-ANT-5.8GHZ-10DB **OMNI NF**







Representative Photo

Representative Photo

Representative Photo

Technical Data

Maximum Power	150 Watts	25 watts	25 watts
Polarization	Vertical	Vertical Linear	Vertical Linear
Nominal Impedance	50 Ohms	50 Ohms	50 Ohms
VSWR across the band	< 1.5:1	< 2.0	< 2.0
Radome Material	PVC	PVC	PVC
Termination	Determined by thru-panel base	N Female	N Female
Mounting Base Diameter	, ,		1-5/16"
Electrical Specifications			
Frequency Range	4.9-5.9 GHz	5.15-5.875 GhHz	5.15-5.875 GhHz
Gain	4dBi	7dBi	10dBi
Half Power Vertical Beamwidth		15°	10°
Mechanical Specifications			
Antenna Type	Low Profile Whipless	Omni	Omni
Connector Type	For use with thru-panel base (6720005277)	N Female	N Female
Antenna Height	1.79"	10.2"	18.38"
Bending Moment at Rated Wind		1.1 ft-lbs	5.6 ft-lbs
Max wind load @ rated velocity		3.1 lbs	6.8 lbs
Equivalent Flat Plate Area	1.5" OD	0.04ft ²	0.08ft ²
Rated Wind		125 mph	125 mph
Weight lbs (kg)	0.34 (0.15)	0.3 (0.14)	0.35 (0.16)
Temperature Range	-40 to +70°C	-40 to +70°C	-40 to +70°C

Туре	Part No.	Туре	Part No.	Туре	Part No.
WI-ANT-5.8GHZ-4DB MOBILE	6720005278	WI-ANT-5.8GHZ-7DB OMNI NF	6720005283	WI-ANT-5.8GHZ-10DB OMNI NF	6720005284

Antennas

IE-ANT-O-AH-360-5-NF



Representative Photo

Technical Data

EL . L. LD.	
Electrical Data	
Frequency (Mhz)	5150 - 5875 (Mhz)
VSWR	< 1.7
Gain	5 dBi
3dB beamwidth (horizontal)	360°
3dB beamwidth (vertical)	25°
Front to back ratio	-
Vertical electrical tilt	<u>0°</u>
General Data	
Radiation	Omnidirectional
Nominal Impedance	50 Ohm
Polarisation	Vertical
Connector type	1 x N-Type female
Connector position	Bottom
Composite power max.	6 W
Mechanical Data	
Dimensions	160 x 16 mm (Height x Diameter)
Weight	300 g
Wind load	frontal: 7N @ 160 km/h, lateral 7N @ 160 Km/h
Mast Diameter min.	38.1 mm
Mast Diameter max.	76.2 mm
Environmental Limits	
Environmental Conditions	outdoor
Operating Temperature	-45°C to 70°C
Storage Temperature	-45°C to 70°C
IP Rating	IP64
Material Data	
Radome Color	RAL 9002 (grey-white)
Radome Material	PP
Back plate/base plate material	-

Ordering Data

Model
Туре
Part No.
Note:

802.11 a/h Wireless Antenna; Omni-directonal IE-ANT-O-AH-360-5-NF 1367120000 Mounting material included

WI-ANT-5.8GHZ-9DB **DFP 2'NF**

FLAT PATCH

WI-ANT 5.8GHZ 11DB WI-ANT-5.8GHZ-13DB **DFP 2'NF**

WI-ANT-5.8GHZ-20DB **DFP 2'NF**









Representative Photo

Representative Photo

Representative Photo

Representative Photo

Technical Data

Maximum Power	25 watts	25 watts	25 watts	25 watts
Polarization	Linear, Vertical/horizontal	Linear, Vertical/horizontal	Linear, Vertical/horizontal	Linear, Vertical/horizontal
Nominal Impedance	50 Ohms	50 Ohms	50 Ohms	50 Ohms
VSWR across the band	< 2.0:1	< 1.5:1	< 1.5:1	< 2.0:1
Radome Material	UL 94-V0 Plastic	UL 94HB Polymer	UL 94-V0 Plastic	UL 94-V0 Plastic
Termination	N Female	SMA-Female	N Female	N Female
Mounting Method	adjustable	Four 1/4" Holes	adjustable	Indoor/Outdoor articulating heavy duty adjustable
Electrical Specifications				
Frequency Range	4.94-5.85 (2.40-2.48) GHz	5.725 - 5.875 GHz	4.9-5.9 GHz	4.94-5.85 (2.40-2.48) GHz
Gain	9dBi (8dBi)	11 dBi	13 dBi	20dBi (18dBi)
Half Power Vertical Beamwidth	60°	60°	27°	21° (9°)
Half Power Horizontal Beamwidth	60°	30°	40°	21° (9°)
Front to Back Ratio	>15 dB (>22dB)	>25 dB	> 25 dB	>25 dB (>30dB)
Mechanical Specifications				
Antenna Type	Directional Panel	Directional Panel	Directional Panel	Directional Panel
Connector Type	N Female	SMA-Female	N Female	N Female
Dimensions	5.1" x 4.7" x 1.5"	4.5" x 4.5" x 1"	5.1" x 4.7" x 1.5"	15.1" x13.9" x 1.9"
Max Wind Load @ Rated Velocity	9.3 lbs		9.3 lbs	85 lbs
Equivalent Flat Plate Area				
Rated Wind	125 mph	>150 mph	125 mph	125 mph
Weight lbs (kg)	0.5 (0.23)	<0.4 (<0.2)	0.5 (0.23)	3.9 (1.8)
Temperature Range	-40 to +70°C	-40 to +85°C	-40 to +70°C	-40 to +70°C

Туре	Part No.	Туре	Part No.	Туре	Part No.	Туре	Part No.
 WI-ANT-5.8GHZ-9DB	6720005280	WI-ANT 5.8GHZ 11DB	6720005130	WI-ANT-5.8GHZ-13DB	6720005281	WI-ANT-5.8GHZ-20DB	6720005282
DFP 2'NF		FLAT PATCH		DFP 2'NF		DFP 2'NF	

IE-ANT-P-ABG-75-9-NF

IE-ANT-O-ABG-360-7-NF







Representative Photo

Technical Data

Electrical Data		
Frequency (Mhz)	Band 1: 2400 - 2500 (Mhz)	Band 1: 2400 - 2500 (Mhz)
	Band 2: 5150 - 5875 (Mhz)	Band 1: 5150 - 5875 (Mhz)
		Band 3: 3400 - 3700 (Mhz)
		Band 4: 4900 - 5470 (Mhz)
		Band 5: 5470 - 5935 (Mhz)
VSWR	< 2	Band 1: < 1.8
		Band 2: < 2
		Band 3: < 2
		Band 4: < 1.8
		Band 5: < 1.8
Gain	9 dBi Band 1/2	Band 1: 6 dBi
		Band 2: 6 dBi
		Band 3: 7 dBi
		Band 4: 8 dBi
		Band 5: 8 dBi
3dB beamwidth (horizontal)	75° Band 1 ; 55° Band 2	<u>-</u>
3dB beamwidth (vertical)	55° Band 1/2	-
Front to back ratio	15 dB Band 1/2	<u>-</u>
Vertical electrical tilt	0° Band 1/2	-
General Data		
Radiation	Directional	Omnidirectional
Nominal Impedance	50 Ohm	50 Ohm
Polarisation	Vertical	Vertical
Connector type	1 x N-Type female	1 x N-Type female
Connector position	Bottom	Bottom
Composite power max.	10 W	75 W
Mechanical Data		
Dimensions	101 x 80 x 35 mm (Height x Width x Depth)	50.6 x 86 mm (Height x Diameter)
Weight	110 g	300 g
Wind load	frontal: 7N @ 160 km/h, lateral 7N @ 160 Km/h	frontal: 10N @ 160 km/h
Mast Diameter min.	40 mm	-
Mast Diameter max.	60 mm	=
Environmental Limits		
Environmental Conditions	outdoor	outdoor
Operating Temperature	-40°C to 80°C	-40°C to 80°C
Storage Temperature	-40°C to 80°C	-40°C to 80°C
IP Rating	IP67	IP68
Material Data		
Radome Color	RAL 7044 (grey)	RAL 7043 (dark-grey)
Radome Material	PC	ASA_SAN
Back plate/base plate material		Stainless Steel

Model	802.11 a/b/g/h Wireless Antenna;
	Directional
Туре	IE-ANT-P-ABG-75-9-NF
Part No.	1367140000
Note:	Mounting material included

802.11 a/b/g/h Wireless Antenna;
Omni-directonal
IE-ANT-O-ABG-360-7-NF
1367130000
Mounting material included

WI-ANT-DEMO-2400

WI-ANT-24GHZ-2DB **DUCK SMA-M**

WI-ANT-24GHZ-3DB **FOR MAG BASE**



Representative Photo



Representative Photo



Representative Photo

Technical Data

Maximum Power	1 watt	50 watts	200/150/100 watts
Polarization	Vertical	Vertical, Linear	Vertical
Nominal Impedance	50 ohms	50 ohms	50 ohms
VSWR across the band	1.5:1	< 1.5:1	< 1.5:1
Radome Material	Polyurethane	Polyurethane	Stainless steel
Termination	SMA male	SMA male	N female
Mounting Base Diameter	N/A	N/A	N/A
Electrical Specifications			
Frequency Range	2.4 GHz	2.4 GHz	2.2 - 2.9 GHz
Gain	OdB	2 dBi	3 dBi
Half Power			
Vertical Beamwidth	N/A	50°	30°
Mechanical Specifications			
Antenna Type	Whip	Whip	ISM mobile with WLAN
Connector Type	SMA male	SMA male	N female
Antenna Height	54 mm	114.3 mm	_5.25" (133.35 mm)
Bending Moment at Rated Wind	N/A	N/A	N/A
Max Wind Load @			
Rated Velocity	N/A	N/A	N/A
Equivalent Flat Plate Area	N/A	N/A	N/A
Rated Wind	N/A	N/A	N/A
Weight lbs (kg)	0.019 (0.009)	0.15 (0.068)	0.25 (0.113)
Temperature Range	N/A	-40°C to +85°C	-40°C to +70°C

Gracining Data						
	Туре	Part No.	Туре	Part No.	Туре	Part No.
	WI-ANT-DEMO-2400	6720005099	WI-ANT-24GHZ-2DB	6720005207	WI-ANT-24GHZ-3DB	6720005208
			DUCK SMA-M		FOR MAG BASE	

WI-ANT-24GHZ-4DB **OMNI NF**

WI-ANT-0.9/2.4GHZ-3/4DB **MOBILE**

WI-ANT-24GHZ-6DB **OMNI NF**







Representative Photo

Representative Photo

Representative Photo

-40°C to +70°C

Technical Data

Maximum Power	25 watts	100 watts	25 watts
Polarization	Vertical	Vertical	Vertical
Nominal Impedance	50 ohms	50 ohms	50 ohms
VSWR across the band	< 1.5:1	< 2.0:1	< 1.5:1
Radome Material	UV resistant pultruded fiberglass	PVC	UV resistant pultruded fiberglass
Termination	N female	Determined by Thru-panel base	N female
Mounting Base Diameter	1.25"	Compatible with most 1-1/8" - 18 thread mounts, including 3/4" hole mounts	1.25"
Electrical Specifications			
Frequency Range	2.4 - 2.48 GHz	902-928 MHz / 2400-2500 MHz	2.4 - 2.48 GHz
Gain	4 dBi	4 dBi	6 dBi
Half Power Vertical Beamwidth	30°		20°
Mechanical Specifications			
Antenna Type	Omni	Low Profile Whipless	Omni
Connector Type	N female	For use with thru-panel base (6720005277)	N female
Antenna Height	8.1" (205.7 mm)	2.4" (60.9 mm)	11.6" (294.6 mm)
Bending Moment at Rated Wind	0.7 ft-lbs		1.4 ft-lbs
Max wind load @ rated velocity	2.1 lbs		3.0 lbs
Equivalent Flat Plate Area	.02 ft ²	1.5" OD	.04 ft ²
Rated Wind	125 mph		125 mph
Weight lbs (kg)	0.34 (0.154)	0.29 (0.13)	0.38 (0.172)

Ordering Data

Temperature Range

-40°C to +70°C

ordornig Data	Туре	Part No.	Туре	Part No.	Туре	Part No.
	WI-ANT-24GHZ- 4DB OMNI NF	6720005200	WI-ANT-0.9/ 2.4GHZ- 3/4DB MOBILE	6720005276	WI-ANT-24GHZ-6DB OMNI NF	6720005201

-40°C to +70°C

WI-ANT-24GHZ-8DB OMNI NF

WI-ANT-24GHZ-10DB **OMNI NF**

WI-ANT-24GHZ-12DB **OMNI NF**









Representative Photo

Representative Photo

Representative Photo

Technical Data

recinical Data			
Maximum Power	25 watts	25 watts	25 watts
Polarization	Vertical	Vertical	Vertical
Nominal Impedance	50 ohms	50 ohms	50 ohms
VSWR across the band	< 1.5:1	< 1.5:1	< 1.5:1
Radome Material	UV resistant pultruded fiberglass	UV resistant pultruded fiberglass	UV resistant pultruded fiberglass
Termination	N female	N female	N female
Mounting Base Diameter	1.25"	1.25"	1.5"
Electrical Specifications			
Frequency Range	2.4 - 2.48 GHz	2.4 - 2.48 GHz	2.4 - 2.5 GHz
Gain	8 dBi	10 dBi	12 dBi
Half Power Vertical Beamwidth	13°	9°	7°
Mechanical Specifications			
Antenna Type	Omni	Omni	Omni
Connector Type	N female	N female	N female
Antenna Height	20.2" (513.1 mm)	36.0" (914.4 mm)	_44.0" (1118 mm)
Bending Moment at Rated Wind	4.4 ft-lbs	14.7 ft-lbs	_41 ft-lbs
Max Wind Load @ Rated Velocity	5.2 lbs	10.1 lbs	_22.4 lbs
Equivalent Flat Plate Area	.06 ft ²	.11 ft ²	.25 ft ²
Rated Wind	125 mph	125 mph	125 mph
Weight lbs (kg)	0.50 (0.226)	0.65 (0.295)	3.00 (1.400)
Temperature Range	-40°C to +70°C	-40°C to +70°C	-40°C to +70°C

Туре	Part No.	Туре	Part No.	Туре	Part No.
WI-ANT-24GHZ-8DB OMNI NF	6720005204	WI-ANT-24GHZ-10DB OMNI NF	6720005202	WI-ANT-24GHZ-12DB OMNI NF	6720005203

IE-ANT-O-BG-360-6-NF



Representative Photo

Technical Data

Electrical Data	
Frequency (Mhz)	2400 - 2500 (Mhz)
VSWR	1.8
Gain	6 dBi
3dB beamwidth (horizontal)	360°
3dB beamwidth (vertical)	30°
Front to back ratio	-
Vertical electrical tilt	0°
General Data	
Radiation	Omnidirectional
Nominal Impedance	50 Ohm
Polarisation	Vertical
Connector type	1 x N-Type female
Connector position	Bottom
Composite power max.	25 W
Mechanical Data	
Dimensions	250 x 22 mm (Height x Diameter)
Weight	300 g
Wind load	frontal: 3N @ 160 km/h, lateral 3N @
Mast Diameter min.	160 Km/h
Mast Diameter max.	-
Environmental Limits	
Environmental Conditions	outdoor
Operating Temperature	-40°C to 80°C
Storage Temperature	-40°C to 80°C
IP Rating	IP67
Material Data	
Radome Color	RAL 7035 (light grey)
Radome Material	Glass Fiber
Back plate/base plate material	-

Model	802.11 b/g Wireless Antenna;
Model	Omni-directonal
Туре	IE-ANT-O-BG-360-6-NF
Part No.	1367090000
Note:	Mounting material included

WI-ANT-24GHZ-9DB DFP 2' NF

WI-ANT-24GHZ-10DB YAGI NF WI-ANT-24GHZ-13DB DFP 2' NF



Representative Photo



Representative Photo



Representative Photo

Technical Data

Maximum Power	20 watts	5 watts	20 watts
Polarization	Linear	Linear	Linear
Nominal Impedance	50 ohms	50 ohms	50 ohms
VSWR across the band	<1.6: 1	<1.5: 1	<1.6: 1
Radome Material	UV stable plastic	UV stable plastic	UV stable plastic
Cable Length and type	12" RG58/U	36" coax	12" RG58/U
Termination	N female	N female	N female
Mounting Method	Indoor/outdoor articulating; heavy duty outdoor adjustable	heavy duty outdoor adjustable	Indoor/outdoor articulating; heavy duty outdoor adjustable
Electrical Specifications			
Frequency Range	2.3 - 2.5 GHz	2.4 - 2.485 GHz	2.3 - 2.5 GHz
Gain	9 dBi	10 dBi	13 dBi
Half Power			
Horizontal Beamwidth	60°	55°	35°
Half Power			
Vertical Beamwidth	60°	<u>55°</u>	<u>35°</u>
Front to Back Ratio	>15 dB	>23 dB	>18 dB
Mechanical Specifications			
Antenna Type	Directional Panel	Directional Yagi	Directional Panel
Connector Type	N female	N female	N female
Dimensions	5.1"x4.7"x1.5"	4.5" x 3"	8.8"x8.1"x1.6"
Max Wind Load @ Rated Velocity	9.3 lbf	5.8 lbf	27.9 lbf
Equivalent Flat Plate Area		0.060 ft ²	
Rated Wind	125 mph	125 mph	125 mph
Weight lbs (kg)	0.5 (0.227)	1.0 (0.5)	1.2 (0.544)
Temperature Range	-40°C to +70°C	-40°C to +70°C	-40°C to +70°C
Tomporature name	10 0 10 170 0	10 0 10 170 0	10 0 10 170 0

Туре	Part No.	Туре	Part No.	Туре	Part No.
WI-ANT-24GHZ-9DB	6720005212	WI-ANT-24GHZ-10DB	6720005205	WI-ANT-24GHZ-13DB	6720005213
DFP 2' NF		YAGI NF		DFP 2' NF	

WI-ANT-24GHZ-14DB YAGI NF

WI-ANT-24GHZ-18DB DFP 2' NF







Representative Photo

Technical Data

Maximum Power	5 watts	20 watts
Polarization	Linear	Linear
Nominal Impedance	50 ohms	50 ohms
VSWR across the band	<1.5: 1	<1.6: 1
Radome Material	UV stable plastic	UV stable plastic
Cable Length and type	36" coax	12" RG58/U
Termination	N female	N female
Mounting Method	Heavy duty outdoor adjustable	Indoor/outdoor articulating; heavy duty outdoor adjustable
Electrical Specifications		
Frequency Range	2.4 - 2.485 GHz	2.3 - 2.5 GHz
Gain	14 dBi	18 dBi
Half Power		
Horizontal Beamwidth	30°	18°
Half Power		100
Vertical Beamwidth	30°	19°
Front to Back Ratio	>30 dB	>25 dB
Mechanical Specifications		
Antenna Type	Directional Yagi	Directional Panel
Connector Type	N female	N female
Dimensions	14" x 3"	15.1"x13.9"x1.9"
Max wind load @ rated velocity	18.3 lbf	85 lbf
Equivalent Flat Plate Area	0.20 ft ²	
Rated Wind	125 mph	125 mph
Weight lbs (kg)	1.0 (0.5)	3.9 (1.77)
Temperature Range	-40°C to +70°C	-40°C to +70°C
	·	·

Туре	Part No.	Туре
WI-ANT-24GHZ-14DB	6720005206	WI-ANT-24
YAGI NF		DFP 2' NF

Туре	Part No.
WI-ANT-24GHZ-18DB	6720005214
DFP 2' NF	

WI-ANT-900MHZ-0DB DUCK SMA M

WI-ANT-DPL-DG900-1

WI-ANT-DEMO-900









Representative Photo

Representative Photo

Representative Photo

Technical Data

Maximum Power	5 watts		
Polarization	Tertical, Linear		
Nominal Impedance	50 ohms	50 ohms	50 ohms
VSWR across the band	<2.0:1		
Radome Material			
Termination	SMA male	SMA male	SMA male
Mounting Base Diameter			
Electrical Specifications			
Frequency Range	806-960 MHz/1710-2170 MHz	900-930 MHz	900-930 MHz
Gain	0 dBi	-2 dBi	O dBi
Half Power Vertical Beamwidth			
Mechanical Specifications			
Antenna Type	Portable whip	Ground independent dipole	1/4 wave whip
Connector Type	SMA male	SMA male	SMA male
Antenna Height	6.5" (16.5 cm)	6" (15 cm)	3.5" (9 cm)
Bending Moment at Rated Wind			
Max Wind Load @ Rated Velocity			
Equivalent Flat Plate Area			
Rated Wind			
Weight lbs (kg)			
Temperature Range	-40°C to +85°C		

Туре	Part No.	Туре	Part No.	Туре	Part No.
WI-ANT-900MHZ-0DB DUCK SMA M	6720005232	WI-ANT-DPL-DG900-1	6720005086	WI-ANT-DEMO-900	6720005089

WI-ANT-DPL-0-16



WI-ANT-0.9/2.4GHZ-3/4DB MOBILE

WI-ANT-900MHZ-**ODB OMNI NF**









Representative Photo

Representative Photo

Representative Photo

Representative Photo

0.75 (0.34)

-40°C to +70°C

Technical Data

Maximum Power	10 watts	100 watts	100 watts	150 watts
Polarization	Vertical	Vertical	Vertical	Vertical
Nominal Impedance	50 ohms	50 ohms	50 ohms	50 ohms
VSWR across the band	<1.5: 1	<1.5:1	< 2.0:1	
Radome Material	Fiberglass	Stainless Steel	PVC	Fiberglass
Termination	SMA male	Determined by MAGBASE	Determined by thru-panel base	N female
Mounting Base Diameter		Determined by MAGBASE	Compatible with most 1-1/8" - 18 thread mounts, including 3/4" hole mounts	1-5/16"
Electrical Specifications				
Frequency Range	853-930 MHz	896-940 MHz	902-928 MHz / 2400-2500 MHz	902-928 MHz
Gain	0 dBi	3 dB	3 dBi	Unity
Half Power Vertical Beamwidth				75°
Mechanical Specifications				
Antenna Type	Half wave dipole	5/8 wave over 1/4 wave	Low Profile Whipless	Omni
Connector Type	SMA male	Determined by MAGBASE	For use with thru-panel base (6720005277)	N female
Antenna Height	16" (40 cm)	11" (27.9 cm)	2.4"	14" (35.6 cm)
Bending Moment at Rated Wind				1.4 ft-lbs
Max Wind Load @ Rated Velocity				2.3 lbs
Equivalent Flat Plate Area			1.5" OD	0.06 ft ²
Rated Wind				100 mph

Ordering Data

Temperature Range

0.5 (0.2)

Weight lbs (kg)

Туре	Part No.	Туре	Part No.	Туре	Part No.	Туре	Part No.
WI-ANT- DPL-0-16	6720005080	WI-ANT- 900MHZ-3DB STUB MAG	6720005230	WI-ANT- 0.9/2.4GHZ- 3/4DB MOBILE	6720005276	WI-ANT- 900MHZ-0DI OMNI NF	6720005233

-40°C to +70°C

0.29 (0.13)

-40°C to +70°C

Representative Photo

Antennas WI-ANT-900MHZ-3DBD OMNI NF WI-ANT-900MHZ-7DBD OMNI NF

Representative Photo

Representative Photo

Technical Data

Technical Data			
Maximum Power	150 watts	150 watts	150 watts
Polarization	Vertical	Vertical	Vertical
Nominal Impedance	50 ohms	50 ohms	50 ohms
VSWR across the band			
Radome Material	Fiberglass	Fiberglass	Fiberglass
Termination	N female	N female	N female
Mounting Base Diameter	1-5/16"	1-5/16"	1-5/16"
Electrical Specifications			
Frequency Range	902-928 MHz	902-928 MHz	902-928 MHz
Gain	3 dB	5 dB	7 dB
Half Power			
Vertical Beamwidth	40°	22°	17°
Mechanical Specifications			
Antenna Type	Omni	Omni	Omni
Connector Type	N female	N female	N female
Antenna Height	23.25" (59.1 cm)	48" (121.9 cm)	96" (243.8 cm)
Bending Moment at Rated Wind	4.7 ft-lbs	14.2 ft-lbs	62.5 ft-lbs
Max Wind Load	4.7 10 103	14.2 11 103	02.5 1(1)5
@ Rated Velocity	4.3 lbs	8.0 lbs	15.8 lbs
Equivalent Flat Plate Area	0.12 ft ²	0.22 ft ²	0.44 ft ²
Rated Wind	100 mph	100 mph	100 mph
Weight lbs (kg)	1.25 (0.57)	1.75 (0.79)	4 (1.81)
Temperature Range	-40°C to +70°C	-40°C to +70°C	-40°C to +70°C

Туре	Part No.	Туре	Part No.	Туре	Part No.
WI-ANT-900MHZ-3DB OMNI NF	6720005234	WI-ANT-900MHZ-5DB OMNI NF	6720005235	WI-ANT-900MHZ-7DB OMNI NF	6720005236

WI-ANT-900MHZ-3DBD YAGI NF WI-ANT-900MHZ-6.5DB-2' YAGI NF WI-ANT-900MHZ-10DB-2' YAGI NF







Representative Photo

Representative Photo

Representative Photo

Technical Data

Maximum Power	200 watts	200 watts	200 watts
Polarization	Linear	Linear	Linear
Nominal Impedance	50 ohms	50 ohms	50 ohms
VSWR Across the band	<1.5:1	<1.5:1	<1.5:1
Radome Material	Aluminum 6061-T6	Aluminum 6061-T6	Aluminum 6061-T6
Termination	N female	N female	N female
Mounting Method	Includes mounting hardware	Includes mounting hardware	Includes mounting hardware
Electrical Specifications			
Frequency Range	890-960 MHz	890-960 MHz	890-960 MHz
Gain	3 dBd	6.5 dBd	10 dBd
Half Power Horizontal Beamwidth	168°	100°	56°
Half Power			
Vertical Beamwidth	78°	62°	46°
Front to Back Ratio	>10 dB	>15 dB	>20 dB
Mechanical Specifications			
Antenna Type	Directional Yagi	Directional Yagi	Directional Yagi
Antenna Dimensions (L x W)	13" x 6.8"	13" x 6.8"	24" x 6.8"
Weight lbs (kg)	1.3 (0.59)	2 (0.9)	6.8 (3.08)
Cross Sectional Area	0.11 ft ²	0.12 ft ²	0.24 ft ²
Max Wind Load @ Rated Velocity	2.75 lbf	3 lbf	6 lbf
Rated Wind	125 mph	125 mph	125 mph
Elements	2	3	7
Cable Type	LMR400	RG213	RG213
Cable Length	2 ft.	2 ft.	2 ft.
Connector Type	N female	N female	N female
Temperature Range	-40°C to +85°C	-40°C to +70°C	-40°C to +70°C

Туре	Part No.	Туре	Part No.	Туре	Part No.
WI-ANT-900MHZ-3DB YAGI NF	6720005219	WI-ANT-900MHZ-6.5DB-2' YAGI NF	6720005221	WI-ANT-900MHZ-10DB-2' YAGI NF	6720005223

WI-ANT-900MHZ-12DB-2' YAGI NF WI-ANT-900MHZ-14DB-2' YAGI NF





Representative Photo

Representative Photo

Technical Data

Maximum Power	200 watts	200 watts
Polarization	Linear	Linear
Nominal Impedance	50 ohms	50 ohms
VSWR Across the band	<1.5:1	<1.5:1
Radome Material	Aluminum 6061-T6	Aluminum 6061-T6
Termination	N female	N female
Mounting Method	Includes mounting hardware	Includes mounting hardware
Electrical Specifications		
Frequency Range	890-960 MHz	890-960 MHz
Gain	12 dBd	14 dBd
Half Power Horizontal Beamwidth	40°	32°
Half Power Vertical Beamwidth	34°	26°
Front to Back Ratio	>20 dB	>25 dB
Mechanical Specifications		
Antenna Type	Directional Yagi	Directional Yagi
Antenna Dimensions (L x W)	37" x 6.6"	63" x 6.6"
Weight lbs (kg)	2.5 (1.3)	3.5 (1.58)
Cross Sectional Area	0.35 ft ²	0.67 ft ²
Max wind load @ rated velocity	8.75 lbf	16.75 lbf
Rated Wind	125 mph	125 mph
Elements	11	18
Cable Type	RG213	RG213
Cable Length	2 ft.	2 ft.
Connector Type	N female	N female
Temperature Range	-40°C to +70°C	-40°C to +70°C

Туре	Part No.	Туре	Part No.
WI-ANT-900MHZ-12DB-2' YAGI NF	6720005225	WI-ANT-900MHZ-14DB-2' YAGI NF	6720005226
 17 (61 141		77.0174	

Antennas-900 MHz Omni (Licensed)



Representative Photo

Representative Photo

Representative Photo

Technical Data

recinical Bata			
Maximum Power	150 Watts	150 Watts	150 Watts
Polarization	Vertical Linear	Vertical Linear	Vertical Linear
Nominal Impedance	50 Ohms	50 Ohms	50 Ohms
VSWR across the band	<1.5:1 (70 MHz)	<1.5:1 (70 MHz)	<1.5:1 (40 MHz)
Radome Material	1.0" OD pultruded white fiberglass	1.0" OD pultruded white fiberglass	1.0" OD pultruded white fiberglass
Termination	N Female	N Female	N Female
Mounting Base Diameter	1-5/16"	1-5/16"	1-5/16"
Electrical Specifications			
Frequency Range	890-960 MHz	890-960 MHz	890-940 MHz
Gain	3 dBd	5 dBd	7 dBd
Half Power Vertical Beamwidth	40°	22°	17°
Mechanical Specifications			
Antenna Type	Omni	Omni	Omni
Connector Type	N Female	N Female	N Female
Antenna Height	23"	48"	96"
Bending Moment at Rated Wind	4.7 ft-lbs	14.2 ft-lbs	62.5 ft-lbs
Max Wind Load @ Rated Velocity	4.3 lbs	8.0 lbs	15.8 lbs
Equivalent Flat Plate Area	0.12 ft ²	0.22 ft ²	0.44 ft ²
Rated Wind	100 mph	100 mph	100 mph
Weight lbs (kg)	1.25 lbs	1.75 lbs	4.00 lbs
Temperature Range	-40°C to +70°C	-40°C to +70°C	-40°C to +70°C

Туре	Part No.	Туре	Part No.	Туре	Part No.
WI-ANT-950Mhz-3DBD OMNI NF	6720005273	WI-ANT-950Mhz-5DBD OMNI NF	6720005274	WI-ANT-950Mhz-7DBD OMNI NF	6720005275

Antennas-300-500 MHz

WI-ANT-440MHZ-5DB OMNI NF WI-ANT-450MHZ-3DB OMNI NF WI-ANT-450MHZ-5DB OMNI NF







Representative Photo

Representative Photo


Representative Photo

Technical Data

Technical Data			
Maximum Power	250 Watts	250 Watts	250 Watts
Polarization	Vertical Linear	Vertical Linear	Vertical Linear
Nominal Impedance	50 Ohms	50 Ohms	50 Ohms
VSWR across the band	<1.5:1 (70 MHz)	<1.5:1 (10 MHz)	<1.5:1 (10 MHz)
Radome Material	2.0" OD pultruded white fiberglass	Pultruded white fiberglass	Pultruded white fiberglass
Termination	N Female	N Female	N Female
Mounting Base Diameter	1-5/16"	1-5/16"	1-5/16"
Electrical Specifications			
Frequency Range	430-470 MHz	450-460 MHz	450-460 MHz
Gain	5 dBd (7 dBi)	3 dBd	5 dBd
Half Power Vertical Beamwidth	18°	38°	27°
Mechanical Specifications			
Antenna Type	Omni	Omni	Omni
Connector Type	N Female	N Female	N Female
Antenna Height	83"	71"	77"
Bending Moment at Rated Wind	250 ft-lbs	29.0 ft-lbs	40.4 ft-lbs
Max Wind Load @ Rated Velocity	45 lbs	10.8 lbs	12.6 lbs
Equivalent Flat Plate Area	1.125 ft ²	0.30 ft ²	0.35 ft ²
Rated Wind	125 mph	100 mph	100 mph
Weight lbs (kg)	7.0 lbs	4.0 lbs	4.50 lbs
Temperature Range	-40°C to +70°C	-40°C to +70°C	-40°C to +70°C

Туре	Part No.	Туре	Part No.	Туре	Part No.
WI-ANT-440MHZ-5DB OMNI NF	6720005439	WI-ANT-450MHZ-3DB OMNI NF	6720005440	WI-ANT-450MHZ-5DB OMNI NF	6720005436

Antennas-300-500 MHz WI-ANT-390Mhz-10DBD YAGI NF WI-ANT-420Mhz-6DBD YAGI NF WI-ANT-420Mhz-9DBD YAGI NF WI-ANT-470Mhz-6DBD YAGI NF









Representative Photo

Representative Photo

Representative Photo

Representative Photo

Technical Data

Maximum Power	250 Watts	150 Watts	150 Watts	150 Watts
Polarization	Linear	Linear	Linear	Linear
Nominal Impedance	50 Ohms	50 Ohms	50 Ohms	50 Ohms
VSWR across the band	<1.5:1 (70 MHz)	<1.5:1 (34 MHz)	<1.5:1 (34 MHz)	<1.5:1 (40 MHz)
Radome Material	3/8" solid 6061-T6 aluminum			
Termination	N Female	N Female	N Female	N Female
Mounting Pipe Diameter	1-5/16"	1.9" OD	1.9" OD	1.9" OD
Electrical Specifications				
Frequency Range	375-403 MHz	406-440 MHz	406-440 MHz	440-480 MHz
Gain	10 dBd	6.5 dBd	9 dBd	6.5 dBd
Half Power Vertical Beamwidth	46°	62°	45°	62°
Half Power Horizontal Beamwidth	52°	71°	52°	71°
Front to Back Ratio	>20 dB	>15 dB	>15 dB	>15 dB
Mechanical Specifications				
Antenna Type	Directional Yagi	Directional Yagi	Directional Yagi	Directional Yagi
Connector Type	N Female	N Female	N Female	N Female
Antenna Length (Boom OD)	44" x 14.3"	22" (.75")	34" (.75")	22" (.75")
Number of Elements	7	3	5	3
Bending Moment at Rated Wind	12.75 ft-lbs	12.75 ft-lbs	32.4 ft-lbs	12.75 ft-lbs
Max wind load @ rated velocity	20.84 lbs	14.8 lbs	24.2 lbs	14.8 lbs
Equivalent Flat Plate Area	0.53 ft ²	0.19 ft ²	0.31 ft ²	0.19 ft ²
Rated Wind	100 mph	125 mph	125 mph	125 mph
Weight lbs (kg)	3.5 lbs	1.2 lbs	2 lbs	1.2lbs
Temperature Range	-40°C to +70°C	-40°C to +70°C	-40°C to +70°C	-40°C to +70°C

Туре	Part No.	Туре	Part No.	Туре	Part No.	Туре	Part No.
WI-ANT-390Mhz- 10DBD YAGI NF	6720005441	WI-ANT-420Mhz- 6DBD YAGI NF	6720005442	WI-ANT- 420Mhz-9DBD YAGI NF	6720005443	WI-ANT- 470Mhz-6DBD YAGI NF	6720005444

Antennas-300-500 MHz WI-ANT-470Mhz-9DBD YAGI NF

WI-ANT-450MHZ-10DB YAGI WI-ANT-470Mhz-9DBD YAGI NF







Representative Photo

Representative Photo

Representative Photo

Technical Data

1001111104111144			
Maximum Power	150 Watts	250 Watts	150 Watts
Polarization	Linear	Linear	Linear
Nominal Impedance	50 Ohms	50 Ohms	50 Ohms
VSWR across the band	<1.5:1 (40 MHz)	<1.5:1 (70 MHz)	<1.5:1 (40 MHz)
Radome Material	3/8" solid 6061-T6 aluminum	3/8" solid 6061-T6 aluminum	3/8" solid 6061-T6 aluminum
Termination	N Female	N Female	N Female
Mounting Pipe Diameter	1.9" OD	1.9" OD	1.9" OD
Electrical Specifications			
Frequency Range	440-480 MHz	450-470 MHz	470-512 MHz
Gain	9 dBd	10 dBd	9 dBd
Half Power Vertical Beamwidth	45°	45°	45°
Half Power Horizontal Beamwidth	52°	0°	52°
Front to Back Ratio	> 15 dB	> 20 dB	> 15 dB
Mechanical Specifications			
Antenna Type	Directional Yagi	Directional Yagi	Directional Yagi
Connector Type	N Female	N Female	N Female
Antenna Length (Boom OD)	34" (.75")	42" x 11.8"	34" (.75")
Number of Elements	5	7	5
Bending Moment at Rated Wind	32.4 ft-lbs	250 ft-lbs	32.4 ft-lbs
Max wind load @ rated velocity	24.2 lbs	11.5 lbs	24.2 lbs
Equivalent Flat Plate Area	0.31 ft ²	0.46 ft ²	0.31 ft ²
Rated Wind	125 mph	150 mph	125 mph
Weight lbs (kg)	2 lbs	3 lbs (1.36kg)	2 lbs
Temperature Range	-40°C to +70°C	-40°C to +70°C	-40°C to +70°C

Туре	Part No.	Туре	Part No.	Туре	Part No.
WI-ANT-470Mhz-9DBD YAGI NF	6720005445	WI-ANT-450MHZ- 10DB YAGI	6720005435	WI-ANT-470Mhz-9DBD YAGI NF	6720005446

Antennas-Cellular

WI-ANT-GSM-LTE-3DB Mobile

WI-ANT-GSM-2DB LP



Representative Photo



Representative Photo

Technical Data

Maximum Power	100 Watts	8 Watts
Polarization	Vertical	Linear
Nominal Impedence	50 Ω	50 Ω
VSWR across the band	<2.0:1	<2.5:1
Radome Material	PVC (IP66)	PVC
Termination	Determined by thru-panel base	Male SMA c/w 17 ft (5 meter) RG-174 cable
Mounting Base Diameter	Compatible with most 1/8"-8 thread mounts, including 3/4" hole mounts	1-1/2" through hole mount. Mount assembly includes flat adapter shim for installations or larger cutouts
Electrical Specifications		
Frequency Range	698-2700 MHz	824-896 MHz 1710-1990 MHZ
Gain	3 dBi	2 dBi +/- 1 dB@900 MHz, 1 dB +/-1 dB@1800 MHz
Mechanical Specifications		
Antenna Type (Radiation)	Low Profile Whipless	GSM Multi-band Through Hole Low Profile
Connector Type	For use with thru-panel base (6720005277)	Male SMA
Antenna Height	2.4"	0.59" (1.5cm)
Equivalent Flat Plate Area	1.5" OD	3.1" (8cm)
Weight lbs (kg)	0.29 (0.13)	0.45 (0.24)
Temperature Range	-40°C to +70°C	-40°C to +70°C

	Туре	Part No.	Туре	Part No.
	WI-ANT-GSM-LTE-3DB Mobile	6720005450	WI-ANT-GSM-2DB LP	6720005451

Antennas-Cellular

WI-ANT-900MHZ-0DBDUCKSMAM

IE-ANT-3G-806-2170-2-NF

IE-ANT-3G-806-2500-4-NF







Representative Photo

Representative Photo

Representative Photo

Technical Data

Maximum Power	5 Watts	25 W	
Polarization	Vertical Linear	Vertical, Linear	Vertical, Linear
Nominal Impedence	50 Ω	50 Ω	50 Ω
VSWR across the band	<2.0:1	< 2.5	< 2.0:1
Radome Material	PVC	PVC	PVC (IP66)
Termination	Male SMA	1x N-type female, bottom	1x N-type female, bottom
Mounting Base Diameter	Direct connection 180° swivel, 0°-90° knuckle	1 x antenna, 1 x mounting bracket, 2 x clamps for mast assembly	1 x antenna, 1 x Screw connector and mouting material for vandal proof mounting
Electrical Specifications			
Frequency Range	806-960 MHz / 1.71-2.17 GHz	806-960 (MHz), 1710-2170 (MHz)	806-960 MHz / 1.71-2.5 GHz
Gain	0 dBi	2dBi	4dBi
Mechanical Specifications			
Antenna Type (Radiation)	Low Profile Whip	Omni	Omni
Connector Type	Male SMA	1x N-type female, bottom	1x N-type female, bottom
Antenna Height	7-5/8" (19.4 cm)	7.9" (200 mm)	2.1" (48 mm)
Equivalent Flat Plate Area		1" (22 mm)	1.5" (36 mm)
Weight lbs (kg)	0.15 (0.06)	1.0 (0.430)	1.0 (0.3)
Temperature Range	-40°C to +70°C	-40 to +70°C	-40 to +70°C

Туре	Part No.	Туре	Part No.	Туре	Part No.
WI-ANT-900MHZ- ODBDUCKSMAM	6720005232	IE-ANT-3G-806-2170-2-NF	1491160000	IE-ANT-3G-806-2500-4-NF	1491170000

Cables

- Impedance: 50 ohms
- Foamed Polyethylene
- 100% Bonded Aluminum Foil
- Tinned Copper Braid - CuSn
- Flame-retardant PVC
- Polyethylene Jacket

PFP195



PFP400



PFP600



Technical Data

Electrical Specifications	
Cutoff Frequency	41 GHz
Velocity of Propagation	80%
Dielectric Constant	1.56
Time Delay nS/ft (nS/m)	1.27 (4.17)
Impedance	50 ohms
Capacitance (pF/m)	79.7
Inductance uH/ft (uH/m)	0.064 (0.21)
Shielding Effectiveness	>90 dB
DC Resistance:	
Inner Conductor ohms/ 1000ft (/km)	7.6 (24.9)
Outer Conductor ohms/ 1000ft (/km)	4.9 (16.1)
Voltage Withstand	1000 VDC
Jacket Spark	3000 Vrms
Peak Power	2.5 kW
Mechanical Specifications	
Mechanical Specifications Bend Radius: installation in. (mm)	0.5 (12.7)
•	0.5 (12.7) 2.0 (50.8)
Bend Radius: installation in. (mm)	
Bend Radius: installation in. (mm) Bend Radius: repeated in. (mm)	2.0 (50.8)
Bend Radius: installation in. (mm) Bend Radius: repeated in. (mm) Bending Moment ft-lb (N-m)	2.0 (50.8) 0.2 (0.27)
Bend Radius: installation in. (mm) Bend Radius: repeated in. (mm) Bending Moment ft-lb (N-m) Weight lb/ft (kg/m)	2.0 (50.8) 0.2 (0.27) 0.021 (0.03)
Bend Radius: installation in. (mm) Bend Radius: repeated in. (mm) Bending Moment ft-lb (N-m) Weight lb/ft (kg/m) Tensile Strength lb (kg)	2.0 (50.8) 0.2 (0.27) 0.021 (0.03) 40 (18.2)
Bend Radius: installation in. (mm) Bend Radius: repeated in. (mm) Bending Moment ft-lb (N-m) Weight lb/ft (kg/m) Tensile Strength lb (kg) Flat Plate Crush lb/in. (kg/mm)	2.0 (50.8) 0.2 (0.27) 0.021 (0.03) 40 (18.2) 15 (0.27)
Bend Radius: installation in. (mm) Bend Radius: repeated in. (mm) Bending Moment ft-lb (N-m) Weight lb/ft (kg/m) Tensile Strength lb (kg) Flat Plate Crush lb/in. (kg/mm) Center Conductor (mm)	2.0 (50.8) 0.2 (0.27) 0.021 (0.03) 40 (18.2) 15 (0.27) 0.94 Solid BC
Bend Radius: installation in. (mm) Bend Radius: repeated in. (mm) Bending Moment ft-lb (N-m) Weight lb/ft (kg/m) Tensile Strength lb (kg) Flat Plate Crush lb/in. (kg/mm) Center Conductor (mm) Insulation (mm)	2.0 (50.8) 0.2 (0.27) 0.021 (0.03) 40 (18.2) 15 (0.27) 0.94 Solid BC 2.8
Bend Radius: installation in. (mm) Bend Radius: repeated in. (mm) Bending Moment ft-lb (N-m) Weight lb/ft (kg/m) Tensile Strength lb (kg) Flat Plate Crush lb/in. (kg/mm) Center Conductor (mm) Insulation (mm) Binder	2.0 (50.8) 0.2 (0.27) 0.021 (0.03) 40 (18.2) 15 (0.27) 0.94 Solid BC 2.8 Bonded Aluminum Foil
Bend Radius: installation in. (mm) Bend Radius: repeated in. (mm) Bending Moment ft-lb (N-m) Weight lb/ft (kg/m) Tensile Strength lb (kg) Flat Plate Crush lb/in. (kg/mm) Center Conductor (mm) Insulation (mm) Binder Shield (mm)	2.0 (50.8) 0.2 (0.27) 0.021 (0.03) 40 (18.2) 15 (0.27) 0.94 Solid BC 2.8 Bonded Aluminum Foil 0.11 x 112 CuSn
Bend Radius: installation in. (mm) Bend Radius: repeated in. (mm) Bending Moment ft-lb (N-m) Weight lb/ft (kg/m) Tensile Strength lb (kg) Flat Plate Crush lb/in. (kg/mm) Center Conductor (mm) Insulation (mm) Binder Shield (mm) Insulation Jacket (mm)	2.0 (50.8) 0.2 (0.27) 0.021 (0.03) 40 (18.2) 15 (0.27) 0.94 Solid BC 2.8 Bonded Aluminum Foil 0.11 x 112 CuSn
Bend Radius: installation in. (mm) Bend Radius: repeated in. (mm) Bending Moment ft-lb (N-m) Weight lb/ft (kg/m) Tensile Strength lb (kg) Flat Plate Crush lb/in. (kg/mm) Center Conductor (mm) Insulation (mm) Binder Shield (mm) Insulation Jacket (mm) Environmental Specifications	2.0 (50.8) 0.2 (0.27) 0.021 (0.03) 40 (18.2) 15 (0.27) 0.94 Solid BC 2.8 Bonded Aluminum Foil 0.11 x 112 CuSn 4.95

16.2 GHz
85%
1.38
1.20 (3.92)
50 ohms
78.4
0.060 (0.20)
>90 dB
1.39 (4.6)
1.65 (5.4)
2500 VDC
8000 Vrms
16 kW
1.00 (25.4)
4.0 (101.6)
0.5 (0.68)
0.068 (0.10)
160 (72.6)
40 (0.71)
2.74 Solid CCA
7.24
Bonded Aluminum Foil
0.15 x 192 CuSn
10.29
-40° to +185° F / -40° to +85° C
-94° to +185° F / -70° to +85° C
-40° to +185° F / -40° to +85° C

10.3 GHz
87%
1.32
1.17 (3.83)
50 Ohms
76.8
0.058 (0.19)
>90 dB
0.53 (1.7)
1.2 (3.9)
4000 VDC
8000 Vrms
40 kW
1.50 (38.1)
6.0 (152.4)
2.75 (3.73)
0.131 (0.20)
350 (158.9)
60 (1.07)
4.47 Solid CCA
11.56
Bonded Aluminum Foil
0.18 x 240 CuSn
14.99
-40° to +185° F / -40° to +85° C
-94° to +185° F / -70° to +85° C
-40° to +185° F / -40° to +85° C

Ordering Data

Туре	Part No.
PFP195	6720005243
PFP195	6720005244
PFP195	6720005245
PFP195	6720005259
PFP195	6720005270
PFP195	6720005260

Туре	Part No.
PFP400	6720005240
PFP400	6720005241
PFP400	6720005242
PFP400	6720005246
PFP400	6720005247
PFP400	6720005248
PFP400	6720005251
PFP400	6720005252
PFP400	6720005253
PFP400	6720005254
PFP400	6720005255
PFP400	6720005256

Туре	Part No.
PFP600	6720005257

Cable lengths and part numbers on page 62.

IE-CC-NM-RPSMAM-2M

IE-CC-NM-RPSMAM-4M



Technical Data

Technical Data		
Electrical Data		
Impedance	50 Ohm +/- 2	50 Ohm +/- 2
Max. operating frequency	6 Ghz	6 Ghz
Signal delay	4.08 ns/m	4.08 ns/m
Attenuation @ 2.4 Ghz	approx. 0.55 dB/m	approx. 0.55 dB/m
Attenuation @ 5 Ghz	approx. 0.87 dB/m	approx. 0.87 dB/m
Mechanical Data		
Length	2 m	_4 m
Weight	6.3 kg/100m	6.3 kg/100m
Min. Bending radius (static)	28 mm	_28 mm
Connector type	Connector 1: N-type male Connector 2: RP-SMA male	Connector 1: N-type male Connector 2: RP-SMA male
Environmental Limits		
Operating Temperature	-40°C to 85°C	-40°C to 85°C
Installation Temperature	-20°C to 60°C	-20°C to 60°C
Flammability	IEC 60332-1, UL 1581 § 1080 (VW-1)	IEC 60332-1, UL 1581 § 1080 (VW-1)
Halogen free	IEC 60754	IEC 60754
UV resistance	ISO 4892-2A	ISO 4892-2A
Material Data		
Jacket	LSFH (modified polyethylene)	LSFH (modified polyethylene)
Outer Diamter	5.7 mm	5.7 mm
Ordering Data		

Part No.	1367110000	1367100000
Туре	IE-CC-NM-RPSMAM-2M	IE-CC-NM-RPSMAM-4M
Models	Antenna cable, 2m length N-type (male) -> RP-SMA (male), Impedance 50 Ohm	Antenna cable, 4m length, N-type (male) -> RP-SMA (male), Impedance 50 Ohm

Mounts

WI-ACC-24GHZ-4610DB-ANG-BRKT

WI-ACC-24GHZ-4610DB-STR-BRKT

WI-ACC-24GHZ-12DB-STR-BRKT



Technical Data

Description

Stainless steel "L" bracket mount for wall or pipe mount. For mounting omnidirectional antenna to 2" maximum diameter mast.



Aluminum MFB mount bracket. For mounting 1-1/4" diameter antenna to 2-1/2" maximum diameter mast.



Heavy duty MFB mount bracket

WI-ACC-900MHZ-

YAGI-STR-BRKT

Ordering Data

Туре	Part No.
WI-ACC-24GHZ-	6720005209
4610DR-ANG-RRKT	

Туре	Part No.
WI-ACC-24GHZ-	6720005210
4610DR-STR-RRKT	

Туре	Part No.
WI-ACC-24GHZ-	6720005211
12DB-STR-BRKT	

WI-ACC-MAGBASE 12 RG58 SMA MALE



WI-ACC-900MHZ-OMNI-STR-BRKT



Yagi clamp, fits mast OD of 0.5 - 0.84".
Mounts to legs, towers, accessories

Low frequency magnetic mount Light duty parallel or perpendicular pipe (for antennas operating 800-3000 MHz) to pipe clamp, fits 1.5 - 2.4" to

Ordering Data

Technical Data

Description

Туре	Part No.
WI-ACC-MAGBASE 12	6720005263
RG58 SMA MALE	

Туре	Part No.
WI-ACC-900MHZ-	6720005268
OMNI-STR-BRKT	

1.5 - 2.4" OD pipewith 1.25 - 2.4" OD

Type Part No. WI-ACC-900MHZ-YAGI-STR-BRKT 6720005266

WI-ACC-900MHZ-14YAGI-STR-BRKT



WI-ACC-900MHZ-0350MNI-STR-BRKT



WI-ACC-900MHZ-70MNI-STR-BRKT



Technical Data

Description

Yagi clamp, fits mast OD of 0.75 - 1".

Mounts to legs, towers, accessories with 1.25 - 2.4" OD

Aluminum MFB mount bracket. For mounting 1-5/16" diameter antenna to 2-1/2" maximum diameter mast. Heavy duty fiberglass base station mount. For mounting an antenna with 2-1/2" maximum diameter onto 2-1/2" maximum diameter mast.

Туре	Part No.
WI-ACC-900MHZ-	6720005267
14YAGI-STR-BRKT	

Туре	Part No.
WI-ACC-900MHZ-	6720005271
0350MNI-STR-BRKT	

Туре	Part No.
WI-ACC-900MHZ-	6720005272
70MNI-STR-BRKT	

Surge Suppressor

WI-ACC-125-1000MHZ SURGE NF-NF

WI-ACC-2-6GHZ SURGE NF-NF

WI-DIV-CCMA SMA M – SMA F







Technical Data

Connector
Frequency Range
VSWR
Insertion Loss
Turn-on

N female to N female
125 - 1000 MHz
<1.1 over frequency range
<0.1 dB over frequency range
600fb VDC +/- 20%

	N female to N female
	2.0 - 6.0 GHz
	1.3: 1
	0.1 dB
_	

SMA Male to SMA Female
<1200 MHz
<0.2dB over range

Ordering Data

Туре	Part No.
WI-ACC-125-1000MHZ	6720005261
SURGE NF-NF	

Туре	Part No.
WI-ACC-2-6GHZ	6720005262
SURGE NF-NF	

Туре	Part No.
WI-DIV-CCMA	6720005111
SMA M-SMAF	

Antenna Coupler

WI-ACC-BULK-C1D1 SMA M - SMA F

WI-ACC-BULK-C1D1 SMA M - NF





Technical Data

Maximum Fault Voltage	_2
	_
Maximum Antenna Power Output	_2
Maximum Capacitance	Ę
Frequency Range	2
Impedenance	Ę
Approximate Signal Attenuation (1):	
@ 425 MHz	(
@ 915 MHz	2
@ 2.4 GHz	2
Approximate Weight	(
Housing Material	3
Ambient Temperature Range	
Connector	5
Approvals	

250 VDC, 250 VAC 50-60 Hz
2 watts or 33 dB
5.64 nF
260 to 2483 MHz
50 Ohms
0.6 dB
2.2 dB
2.6 dB
0.5 lb (0.23 kg)
300 Series Stainless Steel
-40°/+85° C
SMA male to SMA female
Class 1 Div 1, group A, B, C, D

250 VDC, 250 VAC 50-60 Hz
2 watts or 33 dB
5.64 nF
260 to 2483 MHz
50 Ohms
3.2 dB
2.4 dB
4.1 dB
0.5 lb (0.23 kg)
300 Series Stainless Steel
-40°/+85° C
SMA male to N female
Class 1 Div 1, group A, B, C, D

Туре	Part No.
WI-ACC-BULK-C1D1	6720005298
SMA M - SMA F	

Туре	Part No.
WI-ACC-BULK-C1D1	6720005299
SMA M - NF	

Adapters

WI-ACC-ADAPT SMA M - SMA M

WI-ACC-ADAPT SMAF-SMAF

WI-ACC-ADAPT NM - NM







Technical Data

Connector

Adapter SMA male to SMA male Adapter SMA female to SMA female Barrel Adapter N male to N male

Ordering Data

Туре	Part No.
WI-ACC-ADAPT	6720005290
SMA M - SMA M	

Туре	Part No.
WI-ACC-ADAPT	6720005291
SMA F - SMA F	

Туре	Part No.
WI-ACC-ADAPT	6720005292
NM - NM	

WI-ACC-ADAPT NF - NF

WI-ACC-ADAPT SMA F - NM

WI-ACC-ADAPT SMA M - NF









Technical Data

Connector

Barrel Adapter N female to N female Adapter SMA female to N male

Adapter SMA male to N female

Ordering Data

Туре	Part No.
WI-ACC-ADAPT	6720005293
NE NE	

Туре	Part No.
WI-ACC-ADAPT	6720005294
SMA F - NM	

Part No. Type WI-ACC-ADAPT 6720005295 SMA M - NF

WI-ACC-BULK SMA F - SMA F

WI-ACC-ADAPT SMAF-SMAMANGL





Technical Data

Connector

Bulkhead Adapter SMA female to SMA female with D-flat Right Angle Adapter SMA male to SMA female

Туре	Part No.
WI-ACC-BULK	6720005296
SMA F - SMA F	

Туре	Part No.
WI-ACC-ADAPT	6720005297
SMA F - SMA M ANGL	

Filters

- Ultra-High Quality Microwave Cavity Filter
- Ultra Low Insertion Loss (0.5 dB nominal)
- Industrial Grade
- Rugged Aluminum Weatherproof Construction for Outdoor or Indoor Use

WI-ACC 900MHZ BAND PASS FILTER



WI-ACC 2.4GHZ BAND PASS FILTER



WI-ACC 5.8GHZ BAND PASS FILTER



Technical Data

Electrical Specifications		
Center Frequency		
Bandwidth		
Out of Band Rejection		
Insertion Loss		
Passband Ripple		
Return Loss		
Impedance		
Number of Cavaties		
Power Handling		
Connectors		
Operating Temp		
Dimensions mm (in)		
Weight Kg (lbs.)		

915 Mhz
35 Mhz
> 40 dB @ 815 Mhz
> 40 dB @ 1015 MHz
0.5 dB
< 0.25 dB
> 15 dB
50 Ohms
4
50 Watts
N Female (2)
-40 to 85°C (-40 to 185°F)
74 x 74 x 50 (2.9 x 2.9 x 1.9)
0.38 (0.84)

2448 MHz
100 Mhz
> 80 dB @ < 2000 Mhz
> 60 dB @ > 2700 MHz
0.25 dB
< 0.25 dB
> 15 dB
50 Ohms
4
50 Watts
N Female (2)
-40 to 85°C (-40 to 185°F)
78 x 78 x 31 (3.0 x 3.0 x 1.2)
0.38 (0.84)

5800 MHz
150 MHz
> 6 dB @ 5570 Mhz
> 6 dB @ 6030 MHz
0.5 dB
< 1.0 dB
> 10 dB
50 Ohms
4
50 Watts
N Female (2)
-40 to 85°C (-40 to 185°F)
58 x 58 x 28 (2.3 x 2.3 x 1.1)
0.31 (0.69)


Туре	Part No.
WI-ACC 900MHZ BAND PASS FILTER	6720005120


Туре	Part No.
WI-ACC 2.4GHz BAND	6720005121
PASS FILTER	

Туре	Part No.
WI-ACC 5.8GHZ BAND	6720005122
PASS FILTER	

Unmanaged Fast Ethernet Switches

- 10/100BaseT(X) (RJ45 connector), 100BaseFX (multi/singlemode, SC or ST connector)
- Redundant dual 12/24/48 V DC, 18 to 30 V AC power inputs
- IP30 aluminum housing
- Rugged hardware design well suited for hazardous locations (Class I Div. 2 /ATEX) and maritime environments (DNV/GL)
- -40 to 75° C operating temperature range (T models)







Technical data

Technology		
Standards	IEEE 802.3 for 10BaseT	
	IEEE 802.3u for 100BaseT(X) as	nd 100BaseFX
	IEEE 802.3x for Flow Control	
Processing Type	Store and Forward	
Flow Control	IEEE 802.3x flow control, back	oressure flow control
Switch Properties		
MAC Table Size	1 K	
Packet Buffer Size	512 Kbit	
Interface		
Fiber Ports	100BaseFX ports	
	(SC/ST connector, multimode, s	inglemode)
RJ45 Ports	10/100BaseT(X) auto negotiation	on speed, Full/Half
	duplex mode, and auto MDI/MD	I-X connection
DIP Switches	Enable/Disable broadcast storm	protection
LED Indicators	Power, 10/100M (TP port), 100	M (fiber port)
Optical Fiber		
	100BaseF	
	multimode	singlemode
Wavelength	1300 nm	1310 nm
Max. TX	-10 dBm	0 dBm
Min. TX	-20 dBm	-5 dBm
RX Sensitivity	-32 dBm	-34 dBm
Link Budget	12 dB	29 dB
Typical Distance	5 km (50/125 μm multimode cable)	40 km (9/125 μm
	4 km (62,5/125 μm multimode cable)	singlemode cable)
Saturation	-6 dBm	-3 dBm
Power Requirements		
Input Voltage	12/24/48 V DC (9.6 to 60 V DC	5),
	18 to 30 V AC (47 to 63 Hz),	
	redundant dual inputs	
Input Current	IE SW BL05 5TX: 0.1 A @ 24 V	
	IE SW BL05 SC/ST/SCS: 0.11 A	
	IE SW BL08 8TX: 0.13 A @ 24 \	
	IE SW BL08 2SC/2ST: 0.22 A @	
	IE SW BL08 SCS: 0.17 A @ 24 \	V
Overload Current Protection		
Connection	1 removable 4-contact terminal	block
Reverse Polarity Protection		
Physical Characteristic		
Housing	Aluminum, IP30 protection	
Dimensions	IIE-SW-BL05-Series:	
	30 x 115 x 70 mm (1.18 x 4.52	2 x 2./6 in)
	IE-SW-BL08-Series:) v 2 76 in\
	50 x 115 x 70 mm (1.96 x 4.52	. x ∠./o in)
Weight	IE-SW-BL05-5TX: 175 g	
1	IE-SW-BL08-8TX: 275 g	
Installation	DIN-Rail mounting	
Environmental Limits		
Operating Temperature	Standard Models: -10 to 60° C (
	Wide Temp. Models: -40 to 75°	C (-40 to 167°F)

-40 to 85° C (-40 to 185° F)

Environmental Limits		
Ambient Relative Humidity	5 to 95 % (non-condensing)	
Regulatory Approvals		
Safety	UL508	
Hazardous Location	UL/cUL Class I, Division 2, Groups A, B, C and D;	
	ATEX Zone 2, Ex nC IIC	
EMI	FCC Part 15, CISPR (EN55022) class A	
EMS	EN61000-4-2 (ESD), level 3;	
	EN61000-4-3 (RS), level 3;	
	EN61000-4-4 (EFT), level 3;	
	EN61000-4-5 (Surge), level 3;	
	EN61000-4-6 (CS), level 3;	
	EN61000-4-8; EN61000-4-11	
Maritime	DNV, GL (IE-SW-BL05-4TX-1SCS/SC/ST: pending)	
Shock	IEC 60068-2-27	
Freefall	IEC 60068-2-32	
Vibration	IEC 60068-2-6	
MTBF (meantime between failures)		
Time	425,000 hrs	
Database	Telcordia (Bellcore), GB	
Warranty		
Warranty Period	5 years	

Ordering Data

		Operating	
Port Variants	Model Type	Temperature	Part No.
5 * RJ45	IE-SW-BL05-5TX	-10 to +60° C	1240840000
	IE-SW-BL05T-5TX	-40 to +75° C	1240850000
4 * RJ45, 1* SC-Multimode	IE-SW-BL05-4TX-1SC	-10 to +60° C	1240890000
	IE-SW-BL05T-4TX-1SC	-40 to +75° C	1286550000
4 * RJ45, 1 * ST-Multimode	IE-SW-BL05-4TX-1ST	-10 to +60° C	1240880000
	IE-SW-BL05T-4TX-1ST	-40 to +75° C	1286540000
4 * RJ45, 1 * SC- Singlemode	IE-SW-BL05-4TX-1SCS	-10 to +60° C	1240870000
	IE-SW-BL05T-4TX-1SCS	-40 to +75° C	1286530000
8 * RJ45	IE-SW-BL08-8TX	-10 to +60° C	1240900000
	IE-SW-BL08T-8TX	-40 to +75° C	1286560000
6 * RJ45, 2 * SC-Multimode	IE-SW-BL08-6TX-2SC	-10 to +60° C	1240910000
	IE-SW-BL08T-6TX-2SC	-40 to +75° C	1240920000
6 * RJ45, 2 * ST-Multimode	IE-SW-BL08-6TX-2ST	-10 to +60° C	1240930000
	IE-SW-BL08T-6TX-2ST	-40 to +75° C	1286570000
7 * RJ45, 1 * SC- Singlemode	IE-SW-BL08-7TX-1SCS	-10 to +60° C	1240950000
	IE-SW-BL08T-7TX-1SCS	-40 to +75° C	1286580000

Accessories

	Model Type	Part No.
19" Rack Mounting Kit	RM-KIT	1241440000





For more port counts, please see Weidmuller Industrial Ethernet Catalogue: www.weidmueller.com

Storage Temperature

Unmanaged Gigabit Ethernet Switches

- Fiber-optic options for extending distance and electrical noise immunity
- Redundant dual 12/24/48 V DC power inputs
- Relay output warning for power failure and port break alarm
- Broadcast storm protection
- Supports jumbo frame transmission (up to 9.6 KB)

















Technical data

Technical data	
Technology	JEEE 200 0 (40D T
Standards	IEEE 802.3 for 10BaseT
	IEEE 802.3u for 100BaseT(X) and
	100BaseFX
	IEEE 802.3ab for 1000BaseT(X) IEEE 802.3z for 1000BaseX
	IEEE 802.3x for Flow Control
Processing Type	Store and Forward
Flow Control	
Flow Control	IEEE 802.3x flow control, back pressure
Conidada Donomandia	flow control
Switch Properties	0.14
MAC Table Size	8 K
Packet Buffer Size	1088 Kbit (IE-SW-BL05-5GT),
	1408 Kbit (IE-SW-VL08-xGT)
Interface	
Fiber Ports	100/1000BaseSFP slot (IE-SW-VL08-
	6GT-2GS)
RJ45 Ports	10/100/1000BaseT(X) auto negotiation
	speed, Full/Half duplex mode, and auto
	MDI/MDI-X connection
DIP Switches	One for port break alarm, one for Enable/
	Disable broadcast storm protection
LED Indicators	PWR1, PWR2, FAULT, 10/100/1000M
Alarm Contact	1 relay output with current carrying
	capacity of 1 A @ 24 V DC
Power Requirements	
Input Voltage	12/24/48 V DC (9.6 to 60 V DC),
	redundant dual inputs
Input Current	IE-SW-BL05-5GT: 0.20 A @ 24 V
•	IE-SW-VL08-8GT: 0.32 A @ 24 V
	IE-SW-VL08-6GT-2GS: 0.34 A @ 24 V
Connection	1 removable 6-contact terminal block
Reverse Polarity Protection	Present
Physical Characteristics	
Housing	Metal, IP30 protection
Dimensions	IE-SW-BL05-5GT:
2	35 x 130 x 105 mm (1.37 x 5.12 x 4.13 in)
	IE-SW-VL08-xGT:
	53.6 x 135 x 105 mm (2.11 x 5.31 x 4.13 in)
Weight	IE-SW-BL05-5GT: 290 g
3	IE-SW-VL08-xGT: 630 g
Installation	DIN-Rail mounting
Environmental Limits	
Operating Temperature	Standard Models: 0 to 60° C (32 to 140° F)
operating rempetature	Wide Temp. Models: -40 to 75° C
	(-40 to 167° F) (on request)
Storage Temperature	-40 to 85° C (-40 to 185° F)
Ambient Relative Humidity	5 to 95 % (non-condensing)
	5 to 35 % (non-condensing)
Regulatory Approvals	LUEGO
Safety	UL508
Hazardous Location	UL/cUL Class I, Division 2, Groups A, B, C,
FAAL	and D; ATEX Zone 2, Ex nC IIC
EMI	FCC Part 15, CISPR (EN55022) class A

D 1 4 A 1	
Regulatory Approvals	
EMS	EN61000-4-2 (ESD), level 3;
	EN61000-4-3 (RS), level 3;
	EN61000-4-4 (EFT), level 3;
	EN61000-4-5 (Surge), level 3;
	EN61000-4-6 (CS), level 3
Maritime	DNV, GL
Shock	IEC 60068-2-27
Freefall	IEC 60068-2-32
Vibration	IEC 60068-2-6
MTBF (meantime between failures	
Time	478,000 hrs (IE-SW-BL05-5GT series)
	325,000 hrs (IE-SW-VL08-XGT series)
Database	Telcordia (Bellcore),
	GB (IE-SW-VL08-xGT series)
Warranty	
Warranty Period	5 years

Ordering Data

	Operating	
Model Type	lemperature	Part No.
IE-SW-BL05-5GT	0 to +60° C	1241250000
IE-SW-BL05T-5GT	-40 to +75° C	1286850000
IE-SW-VL08-8GT	0 to +60° C	1241270000
IE-SW-VL08T-8GT	-40 to +75° C	1286860000
IE-SW-VL08-6GT-2GS	0 to +60° C	1241280000
IE-SW-VL08T-6GT-2GS	40 to +75° C	1286870000
	IE-SW-BL05T-5GT IE-SW-VL08-8GT IE-SW-VL08T-8GT IE-SW-VL08-6GT-2GS	Hodel Type Temperature IE-SW-BL05-5GT 0 to +60° C IE-SW-BL05T-5GT -40 to +75° C IE-SW-VL08-8GT 0 to +60° C IE-SW-VL08T-8GT -40 to +75° C IE-SW-VL08T-6GT-2GS 0 to +60° C IE-SW-VL08T-6GT-2GS 40 to +75° C

Accessories


	Model Type	Part No.
19" Rack Mounting Kit	RM-KIT	1241440000



For more port counts, please see Weidmuller Industrial Ethernet Catalogue: www.weidmueller.com

Managed Entry-level Ethernet Switches

- Turbo Ring and Turbo Chain with fast recovery time (under 20 ms)
- IGMP snooping, QoS, port- and tag-based VLAN
- Configurable error messages via SNMP trap, e-mail or relay output
- User-friendly web-based configuration and management
- External Backup and Restoring Module for easy system reconfiguration (optional accessory)



Technical data

Standards

IEEE 802.3 for 10BaseT • IEEE 802.3u for 100BaseT (X) and 100BaseFX • IEEE 802.3x for Flow Control • IIEEE 802.1D for Spanning Tree Protocol • IEEE 802.1w for Rapid STP • IEEE 802.1p for Class of Service • IEEE 802.1Q for VLAN Tagging

IGMPv1/v2 • GMRP • GVRP • SNMPv1/v2c/v3 • DHCP Server/Client • TFTP • SNTP • SMTP • RARP • RMON • HTTP • Telnet • Syslog • DHCP Option 66/67/82 • BootP • LLDP • Modbus/TCP • IPv6

MIB

+ Like MID • D DDIDCE MID • Dride

MIB-II • Ethernet-Like MIB • P-BRIDGE MIB • Bridge MIB • RSTP MIB • RMON MIB Group 1, 2, 3, 9		
Flow Control		
IEEE 802.3x flow control • back pre	essure flow control	
Switch Properties		
MAC Table Size	8 K	
Packet Buffer Size	1 MBit	
Interface		
Fiber Ports	100BaseFX ports (SC/ST connector)	
RJ45 Ports	10/100BaseT(X) auto negotiation speed, Full/Half duplex mode, and auto MDI/MDI-X connection	
Console Port	RS-232 (RJ45 connector)	
DIP Switches	Turbo Ring, Master, Coupler, Reserve	
LED Indicators	PWR1, PWR2, FAULT, MSTR/HEAD, CPLR/TAIL, 10/100M	
Alarm Contact	1 relay output with current carrying capacity of 1 A @ 24 V DC	

Optical Fiber		
		100BaseFX
	multimode	singlemode
Wavelength	1300 nm	1310 nm
Max. TX	-10 dBm	0 dBm
Min. TX	-20 dBm	-5 dBm
RX Sensitivity	-32 dBm	-34 dBm
Link Budget	12 dB	29 dB
Typical Distance	5 km ^a	— 40 km°
	4 km ^b	— 40 km ^c
Saturation	-6 dBm	-3 dBm

- a 50/125 μm, 800 MHz*km fiber optic cable
- b 62.5/125 $\mu m,\,500$ MHz*km fiber optic cable
- $^{\circ}$ 9/125 μm singlemode fiber optic cable

Power Requirements	
Input Voltage	24 V DC (12 to 45 V DC), redundant dual inputs
Input Current	IE-SW-VL08M-8TX: 0.26 A @ 24 V
	IE-SW-VL08M-6TX-2ST/SC: 0.35 A @ 24 V
	IE-SW-VL08M-5TX-3SC: 0.32 A @ 24 V



For more port counts, please see Weidmuller Industrial Ethernet Catalogue: www.weidmueller.com













Power Requirements (cont	inued)
Overload Current Protection	Present
Connection	1 removable 6-contact terminal block
Reverse Polarity Protection	Present
Physical Characteristics	
Housing	Metal, IP30 protection
Dimensions	53.6 x 135 x 105 mm
	(2.11 x 5.31 x 4.13 in)
Weight	IE-SW-VL08M8TX/6TX-2SC/
	6TX-2ST: 650 g
	IE-SW-VL08M-5TX-3SC: 890 g
Installation	DIN-Rail mounting
Environmental Limits	
Operating Temperature	-40 to 75° C (-40 to 167° F)
Storage Temperature	-40 to 85° C (-40 to 185° F)
Ambient Relative Humidity	5 to 95 % (non-condensing)
Regulatory Approvals	
Safety	UL508, UL60950-1, CSA C22.2 No. 60950-1, EN60950-1
Hazardous Location	UL/cUL Class I, Division 2, Groups A, B, C, and D; ATEX Zone 2, Ex nC IIC
EMI	FCC Part 15, CISPR (EN55022) class A
EMS	EN61000-4-2 (ESD), level 3;
	EN61000-4-3 (RS), level 3;
	EN61000-4-4 (EFT), level 3;
	EN61000-4-5 (Surge), level 3;
	EN61000-4-6 (CS), level 3;
	EN61000-4-8
Maritime	DNV, GL
Shock	IEC 60068-2-27
Freefall	IEC 60068-2-32
Vibration	IEC 60068-2-6
MTBF (meantime between	failures)
Time	IE-SW-VL08MSeries:
	363,000 hrs
Database	Telcordia (Bellcore), GB
Warranty	
14/ · D · I	-

Ordering Data

Warranty Period

		Operating	
Port Variants	Model Type	Temperature	Part No.
8 * RJ45	IE-SW-VL08MT-8TX	-40 to +75° C	1240940000
5 * RJ45, 3* SC-Multimode	IE-SW-VL08MT-5TX-3SC	-40 to +75° C	1240970000
6 * RJ45, 2 * ST-Multimode	IE-SW-VL08MT-6TX-2ST	-40 to +75° C	1240990000
6 *RJ45, 2 *SC-Singlemode	IE-SW-VL08MT-6TX-2SCS	-40 to +75° C	1241020000


5 years

Accessories

	Model Type	Part No.
External Backup and Restore Module	EBR-Modul RS232	1241430000
19" Rack Mounting Kit	RM-KIT	1241440000

1 and 2- port Serial/Ethernet Converter for industrial automation

- High surge protection for the serial ports, LAN ports and power supply connection
- Rugged screw-type terminal blocks for power and serial connectors
- Cascading Ethernet ports for easy wiring
- Redundant DC power inputs
- · Warning by relay output and email
- · Low power consumption



Technical data

recnnicai data	
Ethernet Interface	
Number of Ports	2
Speed	10/100 Mbps, auto MDI/MDIX
Connector	8-pin RJ45
Magnetic Isolation Protection	1.5 KV built-in
Ethernet Line Protection	1 KV (level 2) surge protection
Serial Interface	, , ,
Number of Ports	IE-CS-2TX-1RS232/485: 1,
	IE-CS-2TX-2RS232/485: 2
Serial Standards	RS-232/422/485
Connector	IE-CS-2TX-1RS232/485: DB9 for RS-232,
	terminal block for RS-422/485
	IE-CS-2TX-2RS232/485: DB9 for RS-
	232/422/485
Serial Line Protection	 15 KV ESD protection for all signals
	1 KV (level 2) surge protection
RS-485 Data Direction Control	ADDC® (automatic data direction control)
Serial Communication Parame	The state of the s
Data Bits	5, 6, 7, 8
Stop Bits	1, 1.5, 2
Parity	None, Even, Odd, Space, Mark
Flow Control	RTS/CTS and DTR/DSR (RS-232 only),
David note	XON/XOFF
Baud rate	50 to 921.6 Kbps
Serial Signals	T.D. D.D. DTC CTC DTD DCD DCD CND
RS-232 RS-422	TxD, RxD, RTS, CTS, DTR, DSR, DCD, GND Tx+, Tx-, Rx+, Rx-, GND
RS-485-4w	Tx+, Tx-, Rx+, Rx-, GND
RS-485-2w	Data+, Data-, GND
Software	Data+, Data-, GIND
Network Protocols	ICMP, IP, TCP, UDP, DHCP, BOOTP, Telnet,
TVCtVVOIX 1 TOLOCOIS	Rtelnet, DNS, SNMP, HTTP, SMTP, SNTP, IGMP
Configuration Options	Web Console, Serial Console, Telnet Console
	Windows Utility
Windows Real COM Drivers	Windows 95/98/ME/NT/2000,
	Windows XP/2003/Vista/2008/7 x86/x64
Physical Characteristics	
Housing	Metal, IP30 protection
Weight	IE-CS-2TX-1RS232/485: 475 g
	IE-CS-2TX-2RS232/485: 485 g
Dimensions	36 x 105 x 140 mm (1.42 x 4.13 x 5.51 in)
Environmental Limits	
Operating Temperature	Standard Models: 0 to 60° C (32 to 140° F)
	Wide Temp. Models: -40 to 75° C
	(-40 to 167° F)
Operating Humidity	5 to 95% RH
Storage Temperature	-40 to 85° C (-40 to 185° F)
Power Requirements	
Input Voltage	12 to 48 V DC
Power Consumption	IE-CS-2TX-1RS232/485: 12 to 48 V DC;
	220 mA @ 12 V DC, 110 mA @ 24 V DC
	IE-CS-2TX-2RS232/485: 12 to 48 V DC;
	250 mA @ 12 V DC, 125 mA @ 24 V DC





For more converters, please see Weidmuller Industrial Ethernet Catalogue: www.weidmueller.com

Regulatory Approvals				
EMC		CE (EN550	22 Class A, ENS	55024),
		•	5 Subpart B Clas	**
Safety		UL508		
Hazardous Location		UL/cUL Clas	s 1 Division 2 Gr	oups A, B, C and D
ATEX		Class I, Zon	e 2 (Pending)	
EMS		EN61000-4	1-2 (ESD), Level	3
		EN61000-4	1-3 (RS), Level 3	
			1-4 (EFT), Level 4	
			1-5 (Surge), Leve	
			1-6 (CS), Level 3	
		EN61000-4		
		EN61000-4		
Shock		IEC60068-		
Freefall		IEC60068-		
Vibration		IEC60068-	2-6	
Reliability				
Alert Tools			zer and RTC (rea	
Automatic Reboot Trigger		Built-in WD	T (watchdog tin	ner)
Warranty				
Warranty Period		5 years		
Pin Assignment				
RS-232/422/485	PIN	RS-232	RS-422/RS-	RS-485-2W
DB9 male port			485-4w	
12345 -	1	DCD	TxD-(A)	-
	2	RXD	TxD+(B)	
	3	TXD	RxD+(B)	Data+(B)
	4	DTR	RxD-(A)	Data-(A)
<u> </u>	5	GND	GND	GND
6789 —	6	DSR	-	-
_	7	RTS	-	-
Di- A i	88	CTS	-	-
Pin Assignment				
RS-422/485 Terminal Block Wiring	PIN	RS-4	22/RS-485- 4w	RS-485-2W
	1	7	ΓxD+(B)	-
	2		TxD-(A)	-
	3	F	RxD+(B)	Data+(B)
1 2 3 4 5	4		RxD-(A)	Data-(A)
1 2 3 4 3 =	5		GND	GND

Ordering Data


Models	Туре	Operating Temperature	Part No.
Two RJ45; One serial (RS232: Sub-DB9, RS422/485: terminal block)	IE-CS-2TX-1RS232/485 IE-CST-2TX-1RS232/485	0 to +60° C -40 to +75° C	1242080000 1285830000
Two RJ45; Two serial (RS232/422/485: Two SubDB9)	IE-CS-2TX-2RS232/485 IE-CST-2TX-2RS232/485	0 to +60° C -40 to +75° C	1242090000 1285840000

Accessories

	Model Type	Part No.
19" Rack Mounting Kit	RM-KIT	1241440000

Mounting rail outlet RJ45

- Cat.6A
- IP 20
- TS35





Weidmuller mounting rail outlets should be your first choice in the switchgear cabinet when you need to connect

- installation cables
- RJ45 cables

Variations:

8946920000: RJ45 coupling8946930000: Outlet RJ45 A-coded8946940000: Outlet RJ45 B-coded

• 8946950000: Outlet RJ45 ProfiNet-coded





RJ45-C RJ45-FJ-A RJ45-FJ-B RJ45-FJ-P

Technical Data

Category	Cat. 6A / Class EA (IEC 11801 PDAM
	Am 1.2 2007)
Protection class	IP 20
Housing material	PA UL94 VO
Color	light gray (RAL 7035)
Installation	for terminal rail TS35
Configuration	Switchable voltage connection from
	module / coupling to mounting rail
Plugging cycles	750 plugging cycles for plugs to
	IEC 60603-7
Operating temperature, min. / max.	-25° C / 70° C

Ordering Data


RJ45	Туре	Part No.
RJ45 coupling	IE-TO-RJ45-C	8946920000
Outlet RJ45 A-coded	IE-TO-RJ45-FJ-A	8946930000
Outlet RJ45 B-coded	IE-TO-RJ45-FJ-B	8946940000
Outlet RJ45 PROFINET-coded	IE-TO-RJ45-FJ-P	8946950000

Accessories

	Туре	Part No.
9*11 mm, white	ESG 9/11K MC NEUTRAL	1857440000
9*11 mm, white	LM MT DIN A5 9/11 WS	1964070000
9*11 mm, blue	LM MT DIN A5 9/11 BL	1964100000
9*11 mm, yellow	LM MT DIN A5 9/11 GE	1964110000
9*11 mm, gray	LM MT DIN A5 9/11 GR	1964080000
9*11 mm, green	LM MT DIN A5 9/11 GN	1964120000
9*11 mm, orange	LM MT DIN A5 9/11 OR	1964090000

CPT SNT 70W 12V 6A

CP T SNT 90W 24V 3.8A







Technical Data

Ordering Data

Technical Data		
Input Specifications		
Input voltage	115VAC/230VAC autoselect	115VAC/230VAC autoselect
Input voltage range	85-132/187-264 VAC autoselect (output current derating below 100VAC)	85-132/187-264 VAC autoselect (output current derating below 100VAC)
Input voltage frequency	47Hz - 63Hz	47Hz - 63Hz
Harmonic limits	EN 61000-3-2, Class A (for limited output power)	EN 61000-3-2, Class A (for limited output power)
Hold up time	20ms min. 115/230 VAC	20ms min. 115/230 VAC
Inrush current	<12A @ 115VAC; <20A @ 230VAC	<12A @ 115VAC; <20A @ 230VAC
Recommended Circuit breaker, Curve 1 or fuse, slow blow type	6A	6A
Efficiency	87% typ.	87% typ.
Output Specifications		
Output voltage	12 VDC	24 VDC
Output voltage adj. range	12-14 VDC	24-28 VDC
Output current	6.5A	3.75A
Output power max.	70W	90W
Regulation – Input variation	0.5 % max.	0.5 % max.
- Load variation (10-100 %)	0.5 % max.	0.5 % max.
Ripple and Noise (20MHz Bandwidth)	100 mV pk-pk typ. (200 mV pk-pk max. at lmax)	100 mV pk-pk typ. (200 mV pk-pk max. at Imax)
Electronic short circuit protection	Current limitation at Imax., constant current, automatic recovery	Current limitation at Imax., constant current, automatic recovery
Output overvoltage protection	20V	35V
Overload protection	electronic overload protection	electronic overload protection
Overtemperature protection	Switch off at overtemperature, automatic restart	Switch off at overtemperature, automatic restart
Status indicator	Dual color LED (green: DC ok; red: DC off)	Dual color LED (green: DC ok; red: DC off)
Power OK signal – trigger threshold: – active output signal: (reference to –Vout)	9-11 V 11.0 V ±1.0 V (20 mA max.)	18-22 V 22.0 V ±2.0 V (10 mA max.)
- relay output	rated: 30 VDC/1.0 A	rated: 30 VDC/1.0 A
General Specifications		
Operating temperature range	-25° C to +70° C max. (-13° F to +158°F)	-25° C to +70° C max. (-13° F to +158°F)
Cooling	convection cooling, no internal fan	convection cooling, no internal fan
Mounting	TS35 DIN-rail (Horizontal) to allow for cooling	TS35 DIN-rail (Horizontal) to allow for cooling
Storage temperature	-25° C to +85° C (- 13°F to +185°F)	25° C to +85° C (- 13°F to +185°F)
Humidity (non condensing)	95 % rel. H max.	95 % rel. H max.
Pollution degree	2	2
Temperature coefficient	0.02 %/K	0.02 %/K
Reliability, calculated MTBF @ 25°C acc. to IEC 61709	>1.8 Million hours, max. load	>1.8 Million hours, max. load
Remote On/Off (See LIT0917 - Installation Instructions)	by ext. contact. DC on: -S contact open DC off: -S connected via 1Kohm to -Vout	by ext. contact. DC on: -S contact open DC off: -S connected via 1Kohm to -Vout
Isolation	according to IEC/EN 60950-1, UL 60950-1, UL 508	according to IEC/EN 60950-1, UL 60950-1, UL 508
Environment - Vibration acc. IEC 60068-2-6	3 axis, sine sweep, 10-55 Hz, 1 g, 1 oct/min	3 axis, sine sweep, 10-55 Hz, 1 g, 1 oct/min
- Shock acc. IEC 60068-2-27 Dimension (W x D x H)	3 axis, 15 g half sine, 11 ms 35 x 110 x 110 mm	3 axis, 15 g half sine, 11 ms 35 x 110 x 110 mm
Clearances - Above/Below	80 mm (3.15 in)	80 mm (3.15 in)
- Sides	10 mm (0.39 in)	10 mm (0.39 in)
Weight	0.5kg	0.5kg
Approvals		
	cULus Listed to UL508, CSA C22.2 No. 14	cULus Listed to UL508, CSA C22.2 No. 14
	cRUus to ANSI/UL60950, CSA60950	cRUus to ANSI/UL60950, CSA60950
	CSA to C22.2 No. 107.1	CSA to C22.2 No. 107.1
	cCSAus to CSA60950, ANSI/UL60950	cCSAus to CSA60950, ANSI/UL60950
	cCSAus C1D2 to C22.2 No. 213	cCSAus C1D2 to C22.2 No. 213
	cCSAus C1Z2 to CSA60079-15 & ANSI/ISA 12.012.01	cCSAus C1Z2 to CSA60079-15 & ANSI/ISA 12.012.01
	CE marked	CE marked

Type

CP T SNT 70W 12V 6A

Part No.

1105430000

Type

CP T SNT 90W 24V 3.8A

Part No.

1105790000

PROeco

PRO ECO 72W 24V 3A

PRO ECO 120W 24V 5A





AC

Pay attention to polarity of DC connection

DC

_0 13

N (-) O



Technical Data

Input
Rated input voltage
AC input voltage range
AC frequency range
DC input voltage range
AC current consumption
DC current consumption
Input fuse (internal) / inrush current
Recommended back-up fuse

Out	nut

Rated output voltage
Output voltage
Ramp-up time / residual ripple, switching peaks
Rated output current @ U _{rated}
Continuous output current @ 24 V DC
Capacitive load
Protection against reverse voltages from the load
Protection against internal surge voltage
Signalling
DC OK

Voltage monitoring / no-voltage contact /
contact load

On/Off relay

General	data

Efficiency

Alarm

Error

Power loss @ idling / nominal load

Earth discharge current Power factor (approx.)

Mains buffering @ I_{rated}


Parallel connection option

Height x width x depth / weight

Approvals

Approvals

Connection data	
Connection data	
Conductor connection system	
Number of terminals	
Wire cross-section, rigid min/max	mm²
Wire cross-section, flexible min/max	mm²
Wire cross-section, AWG/kcmil	min/max
Min./max. tightening torque range	Nm
Stripping length	mm
Stripping length	mm



100 240 V AC
85 264 V AC (Derating @ 100 V AC)
47 63 Hz
80 370 DC (Derating @ 120 V DC)
0.55 A @ 230 V AC / 1.04 A @ 110 V AC
0.22 A @ 370 V DC / 0.68 A @ 120 V DC
Yes / max. 40
2 A / DI, Safety fuse
6 A, Char. B, Circuit breaker
24 A, Char. C, Circuit breaker

24	V D	С±	1	%			
2	00	1/ 5	$\overline{}$	- /	111	 1-1	_

22...28 V DC (adjustable via potentiometer on front) < 100 ms / < 50 mVSS @ 24 V DC, I_R 3 A up to 55 °C

3 A @ 55 °C, 2.25 A @ 70 °C

Unrestricted 30...35 V DC

35 V DC

LED Green (U_{output} > 21.6 V DC) LED Yellow (I_{output} > 90 % I_R)

LED Red (Overload, overtemperature, short-circuit, U_{output} < 20.4 V DC)

Yes / NO contact / max. 30 V AC/DC 1 A

Output voltage > 21.6 V DC / < 20.4 V DC

> 87 % @ 230 V AC & 3 A 4 W / 9.5 W

< 1 mA

> 0.42 @ 230 V AC / > 0.45 @ 115 V AC

> 100 ms @ 230 V AC / > 20 ms @ 115 V AC

yes, max. 5

125 / 34 / 100 mm / 0.5 kg

CE, TÜV (EN/IEC 60950-1), cULus

	62, 10 t (E1t) 120 00000 1), 002d3		
Ī	Input	Output	
	Screw connection	Screw connection	
	3 for L/N/PE	5 (13,14,+,)	
	0.5/6	0.5/6	
	0.5/2.5	0.5/2.5	
	26/12	26/12	
	0.5/0.6	0.5/0.6	
	6	6	

100 240 V AC
85 264 V AC (Derating @ 100 V AC)
47 63 Hz
80 370 DC (Derating @ 120 V DC)
1.26 A @ 230 V AC / 2.24 A @ 110 V AC
0.39 A @ 370 V DC / 1.16 A @ 120 V DC
Yes / max. 40
4 A / DI, Safety fuse
6 A, Char. B, Circuit breaker
3 5 A Char C Circuit breaker

24 V DC ± 1 %
2228 V DC (adjustable via potentiometer on front)
< 100 ms / < 50 mVSS @ 24 V DC, I _R
5 A up to 55 °C
5 A @ 55 °C, 3.75 A @ 70 °C
Unrestricted
3035 V DC
35 V DC
LED Green (U _{output} > 21.6 V DC)

LLD dieen (Coutput > 2 1.0 V DC)
LED Yellow (I _{output} > 90 % I _R)
LED Red (Overload, overtemperature, short-circuit,
U _{output} < 20.4 V DC)

Yes / NO contact / max. 30 V AC/DC 1 A

Output voltage > 21.6 V DC / < 20.4 V DC

> 87 % @ 230 V AC & 5 A
4 W / 15 W
< 1 mA
> 0.47 @ 230 V AC / > 0.56 @ 115 V AC
> 80 ms @ 230 V AC / > 20 ms @ 115 V AC
ves. max. 5

125 / 40 / 100 mm / 0.6 kg CE TÜV (EN/IEC 60950-1) cH lus

CE, TOV (EN/IEC 00950-1), COLUS		
	Input	Output
	Screw connection	Screw connection
	3 for L/N/PE	6 (13,14,+,+,)
	0.5/6	0.5/6
	0.5/2.5	0.5/2.5
	26/12	26/12
	0.5/0.6	0.5/0.6
	6	6

Ordering Data

Note		

Туре	Qty.	Part No.
PRO ECO 72W 24V 3A	1	1469470000

The internal varistor found in a switch-mode power unit does not replace the necessary surge protection in a system.

Туре	Qty.	Part No.
PRO ECO 120W 24V 5A	1	1469480000
The internal varistor found in a switch-mode power unit does not replace the necessary surge protection in a system.		

PROeco

PRO ECO 240W 24V 10A

PRO ECO 480W 24V 20A





AC

Pay attention to polarity of DC connection

DC

N (-) O-



Technical Data

Input
Rated input voltage
AC input voltage range
AC frequency range
DC input voltage range
AC current consumption
DC current consumption
Input fuse (internal) / inrush current
Recommended back-up fuse

Output
Rated output voltage
Output voltage
Ramp-up time / residual ripple, switching peaks
Rated output current @ U _{rated}
Continuous output current @ 24 V DC
Capacitive load
Protection against reverse voltages from the load
Protection against internal surge voltage
Signalling
DC OK
Alarm
Error
Voltage monitoring / no-voltage contact / contact load
On/Off relay

Efficiency	
Power loss @ idling / nominal load	
Earth discharge current	
Power factor (approx.)	
Mains buffering @ I _{rated}	
Parallel connection option	
Height x width x depth / weight	
Approvals	
Approvals	
Connection data	
Conductor connection system	
Number of terminals	
Wire cross-section, rigid min/max	mm²
Wire cross-section, flexible min/max	mm²
Wire cross-section, AWG/kcmil	min/max
Min./max. tightening torque range	Nm
Stripping length	mm

L (+) O N (-) O PE O Pay attention to polarity	AC of DC connection	DC	0 + 0 + 0 - 0 - 0 13 0 14
100 0101/10			

100 240 V AC
85 264 V AC (Derating @ 100 V AC)
47 63 Hz
80 370 DC (Derating @ 120 V DC)
1.23 A @ 230 V AC / 2.47 A @ 110 V AC
1.18 A @ 370 V DC / 2.4 A @ 120 V DC
Yes / max. 15 A
4 A / DI, Safety fuse
10 A, Char. B, Circuit breaker
34 A, Char. C, Circuit breaker
24 V DC ± 1 %

24 V DC ± 1 %
2228 V DC (adjustable via potentiometer on front)
< 100 ms / < 50 mVSS @ 24 V DC, I _R
10 A up to 55 °C
10 A @ 55 °C, 7.5 A @ 70 °C
Unrestricted
3035 V DC
35 V DC
LED Green (Lloutout > 21.6 V.DC)

LED Red (Overload, overtemperature, short-circuit,
U _{output} < 20.4 V DC)
Yes / NO contact / max. 30 V AC/DC 1 A
Output voltage > 21.6 V DC / < 20.4 V DC
> 90 % @ 230 V AC & 10 A
3 W / 24 W
< 1 mA
> 0.93 @ 230 V AC / > 0.99 @ 115 V AC
> 20 ms @ 230 V AC / > 20 ms @ 115 V AC
yes, max. 5
125 / 60 / 100 mm / 1 kg

LED Yellow (I_{output} > 90 % I_R)

CE, TÜV (EN/IEC 6095	
Input	Output
Screw connection	Screw connection
3 for L/N/PE	6 (13,14,+,+,)
0.5/6	0.5/6
0.5/2.5	0.5/2.5
26/12	26/12
0.5/0.6	0.5/06
6	6

100 240 V AC
85 264 V AC (Derating @ 100 V AC)
47 63 Hz
80 370 DC (Derating @ 120 V DC)
2.37 A @ 230 V AC / 5.2 A @ 110 V AC
1.55 A @ 370 V DC / 4.65 A @ 120 V DC
Yes / max. 3 A
6 A / DI, Safety fuse
16 A, Char. B, Circuit breaker
68 A, Char. C, Circuit breaker
24 V DC ± 1 %
2228 V DC (adjustable via potentiometer on front)

24 V DC ± 1 %
2228 V DC (adjustable via potentiometer on front)
< 100 ms / < 50 mVSS @ 24 V DC, I _R
20 A up to 55 °C
20 A @ 55 °C, 15 A @ 70 °C
Unrestricted
3035 V DC
35 V DC
LED Green (U _{output} > 21.6 V DC)
LED Yellow (I _{output} > 90 % I _R)

ZZZ Teneti (loupat ee /e iii /
LED Red (Overload, overtemperature, short-circuit,
U _{output} < 20.4 V DC)
Yes / NO contact / max. 30 V AC/DC 1 A
Output voltage > 21.6 V DC / < 20.4 V DC
> 91 % @ 230 V AC & 20 A
5 W / 43 W
< 1 mA
> 0.97 @ 230 V AC / > 0.99 @ 115 V AC
> 20 ms @ 230 V AC / > 20 ms @ 115 V AC

yes, max. 3		
125 / 100 / 120 mm / 1.6	kg	
CE, TÜV (EN/IEC 60950-1), cULus		
Input	Output	
Screw connection	Screw connection	

Input	Output
Screw connection	Screw connection
3 for L/N/PE	7 (13,14,+,+, - ,-,-)
0.5/6	0.18/6
0.5/2.5	0.5/2.5
26/12	26/10
0.5/0.6	0.5/0.6
6	7

Ordering Data

General data

Note		

Туре	Qty.	Part No.
PRO ECO 240W 24V 10A	1	1469490000
The internal varistor found in a supplementary surger		

Туре	Qty.	Part No.	
PRO ECO 480W 24V 20A	1	1469510000	
The internal varistor found in a switch-mode power unit does			

Glossary

Bandwidth

ACK Acknowledgment.

Access point An access point is the connection that ties wireless communication devices into a network. Also

known as a base station, the access point is usually connected to a wired network.

Antenna Gain Antennae don't increase the transmission power, but focus the signal more. So instead of

transmitting in every direction (including the sky and ground) antenna focus the signal usually

either more horizontally or in one particular direction. This gain is measured in decibels.

Bridge A hardware component used to connect two or more network segments which are physically

and logically separated.

Collision avoidance A network node characteristic for proactively detecting that it can transmit a signal without risking

The amount of "transportation" space an Internet user has at any given time.

a collision.

Crossover cable A special cable used for networking two computers without the use of a hub. Crossover cables may

> also be required for connecting a cable or DSL modem to a wireless gateway or access point. Instead of the signals transferring in parallel paths from one set of plugs to another, the signals "crossover." If an eight-wire cable was being used, for instance, the signal would start on pin one at one end of the cable and end up on pin eight at the other end. They "cross-over" from one side to

the other.

CSMA/CA CSMA/CA is a "listen before talk" method of minimizing (but not eliminating) collisions caused by

simultaneous transmission by multiple radios. IEEE 802.11 states collision avoidance method rather than collision detection must be used, because the standard employs half duplex radios-radios capable of transmission or reception-but not both simultaneously. Unlike conventional wired Ethernet nodes, a WLAN station cannot detect a collision while transmitting. If a collision occurs, the transmitting station will not receive an ACKnowledge packet from the intended receive station. For this reason, ACK packets have a higher priority than all other network traffic. After completion of a data transmission, the receive station will begin transmission of the ACK packet before any other node can begin transmitting a new data packet. All other stations must wait a longer pseudo randomized period of time before transmitting. If an ACK packet is not received, the transmitting

station will wait for a subsequent opportunity to retry transmission.

CSMA/CD A method of managing traffic and reducing noise on an Ethernet network. A network device

transmits data after detecting that a channel is available. However, if two devices transmit data simultaneously, the sending devices detect a collision and retransmit after a random time delay.

DHCP A utility that enables a server to dynamically assign IP addresses from a predefined list and limit

> their time of use so that they can be reassigned. Without DHCP, an IT Manager would have to manually enter in all the IP addresses of all the computers on the network. When DHCP is used, whenever a computer logs onto the network, it automatically gets an IP address assigned to it.

A communication connection via the standard telephone network, or Plain Old Telephone Service Dial-up

(POTS).

A program that translates URLs to IP addresses by accessing a database maintained on a collection **DNS**

> of Internet servers. The program works behind the scenes to facilitate surfing the Web with alpha versus numeric addresses. A DNS server converts a name like mywebsite.com to a series of numbers like 107.22.55.26. Every website has its own specific IP address on the Internet.

DSL Various technology protocols for high-speed data, voice and video transmission over ordinary

twisted-pair copper POTS (Plain Old Telephone Service) telephone wires.

Encryption key An alphanumeric (letters and/or numbers) series that enables data to be encrypted and then decrypted so it can be safely shared among members of a network. WEP uses an encryption key

that automatically encrypts outgoing wireless data. On the receiving side, the same encryption key

enables the computer to automatically decrypt the information so it can be read.

Keeps unauthorized users out of a private network. Everything entering or leaving a system's

internal network passes through the firewall and must meet the system's security standards in order to be transmitted. Often used to keep unauthorized people from using systems connected to

the Internet.

Firewall

Hub A multiport device used to connect PCs to a network via Ethernet cabling or via WiFi. Wired hubs

can have numerous ports and can transmit data at speeds ranging from 10 Mbps to multigigabyte speeds per second. A hub transmits packets it receives to all the connected ports. A small wired

hub may only connect 4 computers; a large hub can connect 48 or more.

HZ The international unit for measuring frequency, equivalent to the older unit of cycles per second.

One megahertz (MHz) is one million hertz. One gigahertz (GHz) is one billion hertz. The standard US electrical power frequency is 60 Hz, the AM broadcast radio frequency band is 535-1605 kHz, the

FM broadcast radio frequency band is 88-108 MHz and wireless 802.11b LANs operate at

2.4 GHz.

IEEE Institute of Electrical and Electronics Engineers, New York, www.ieee.org. A membership

> organization that includes engineers, scientists and students in electronics and allied fields. It has more than 300,000 members and is involved with setting standards for computers and

communications

Infrastructure mode A client setting providing connectivity to an AP. As compared to Ad-Hoc mode, whereby PCs

> communicate directly with each other, clients set in Infrastructure Mode all pass data through a central AP. The AP not only mediates wireless network traffic in the immediate neighborhood, but

also provides communication with the wired network. See Ad-Hoc and AP.

1/0 The term used to describe any operation, program or device that transfers data to or from a

computer.

Internet appliance A computer that is intended primarily for Internet access is simple to set up and usually does not

> support installation of third-party software. These computers generally offer customized web browsing, touch-screen navigation, e-mail services, entertainment and personal information

management applications.

IP A set of rules used to send and receive messages at the Internet address level.

IP (Internet Protocol) telephony

Technology that supports voice, data and video transmission via IP-based LANs, WANs and the

Internet. This includes VoIP (Voice over IP).

IP address A 32-bit number that identifies each sender or receiver of information that is sent across the Internet. An IP address has two parts: an identifier of a particular network on the Internet and an

identifier of the particular device (which can be a server or a workstation) within that network.

IPX-SPX IPX, short for Internetwork Packet Exchange, a networking protocol used by the Novell NetWare

operating systems. Like UDP/IP, IPX is a datagram protocol used for connectionless communications. Higher-level protocols, such as SPX and NCP, are used for additional error recovery services. Sequenced Packet Exchange, SPX, a transport layer protocol (layer 4 of the OSI Model) used in Novell Netware networks. The SPX layer sits on top of the IPX layer (layer 3) and provides connection-oriented services

between two nodes on the network. SPX is used primarily by client/server applications.

ISA A type of internal computer bus that allows the addition of card-based components like modems

and network adapters. ISA has been replaced by PCI and is not very common anymore.

ISDN A type of broadband Internet connection that provides digital service from the customer's premises to

the dial-up telephone network. ISDN uses standard POTS copper wiring to deliver voice, data or video.

ISO Network Model A network model developed by the International Standards Organization (ISO) that consists of

> seven different levels, or layers. By standardizing these layers and the interfaces in between, different portions of a given protocol can be modified or changed as technologies advance or systems requirements are altered. The seven layers are: Physical, Data Link, Network, Transport,

Session, Presentation and Application.

LAN A system of connecting PCs and other devices within the same physical proximity for sharing

resources such as an Internet connection, printers, files and drives.

MAC Address A MAC address, short for Media Access Control address, is a unique code assigned to most forms

of networking hardware. The address is permanently assigned to the hardware, so limiting a wireless network's access to hardware - such as wireless cards - is a security feature employed by closed wireless networks. But an experienced hacker - armed with the proper tools - can still figure out an authorized MAC address, masquerade as a legitimate address and access a closed network.

Every wireless 802.11 device has its own specific MAC address hard-coded into it. This unique identifier can be used to provide security for wireless networks. When a network uses a MAC table, only the 802.11 radios that have had their MAC addresses added to that network's MAC table would be able to get onto the network.

Modbus

Modbus is a serial communications protocol for use with its programmable logic controllers (PLCs). Simple and robust, it has since become a de facto standard communication protocol, and it is now amongst the most commonly available means of connecting industrial electronic devices.

Modbus RTU

This is used in serial communication & makes use of a compact, binary representation of the data for protocol communication. The RTU format follows the commands/data with a cyclic redundancy check checksum as an error check mechanism to ensure the reliability of data. Modbus RTU is the most common implementation available for Modbus. A Modbus RTU message must be transmitted continuously without inter-character hesitations. Modbus messages are framed (separated) by idle (silent) periods.

Modbus TCP

Also called Modbus TCP/IP. This is a Modbus variant used for communications over TCP/IP networks, connecting over port 502. It does not require a checksum calculation as lower layers already provide checksum protection.

NAT

Network Address Translation: A network capability that enables a houseful of computers to dynamically share a single incoming IP address from a dial-up, cable or xDSL connection. NAT takes the single incoming IP address and creates new IP address for each client computer on the network.

NIC

A type of PC adapter card that either works without wires (Wi-Fi) or attaches to a network cable to provide two-way communication between the computer and network devices such as a hub or switch. Most office wired NICs operate at 10 Mbps (Ethernet), 100 Mbps (Fast Ethernet) or 10/100 Mbps dual speed. High-speed Gigabit and 10 Gigabit NIC cards are also available. See PC Card.

OFDM

Orthogonal frequency-division multiplexing (OFDM) is a method of encoding digital data on multiple carrier frequencies. OFDM has many advantages over DSSS (more bandwidth over less spectrum, better multi-path immunity, better Doppler shift immunity and greater resilience to interference.) The radios use DSSS when downgraded to data rates of: 1, 2, 5.5 and 11Mbps. OFDM is used when the radio is transmitting at data rates of 6, 9, 12, 18, 24, 36, 48 and 54Mbps. The data rate depends on the RSSI.

Proxy server

Used in larger companies and organizations to improve network operations and security, a proxy server is able to prevent direct communication between two or more networks. The proxy server forwards allowable data requests to remote servers and/or responds to data requests directly from stored remote server data.

RJ-45

Standard connectors used in Ethernet networks. Even though they look very similar to standard RJ-11 telephone connectors, RJ-45 connectors can have up to eight wires, whereas telephone connectors have only four.

Receive Sensitivity

The minimum signal strength required to pick up a signal. Higher bandwidth connections have less receive sensitivity than lower bandwidth connections.

Router

A device that forwards data from one WLAN or wired local area network to another.

Server

A computer that provides its resources to other computers and devices on a network. These include print servers, Internet servers and data servers. A server can also be combined with a hub or router.

Site survey

The process whereby a wireless network installer inspects a location prior to putting in a wireless network. Site surveys are used to identify the radio- and client-use properties of a facility so that access points can be optimally placed.

SSL

Commonly used encryption scheme used by many online retail and banking sites to protect the financial integrity of transactions. When an SSL session begins, the server sends its public key to the browser. The browser then sends a randomly generated secret key back to the server in order to have a secret key exchange for that session.

SNR

Signal to Noise Ratio. The number of decibels difference between the signal strength and background noise.

106

Subnetwork or Subnet

Found in larger networks, these smaller networks are used to simplify addressing between numerous computers. Subnets connect to the central network through a router, hub or gateway. Each individual wireless LAN will probably use the same subnet for all the local computers it talks to.

Switch

A type of hub that efficiently controls the way multiple devices use the same network so that each can operate at optimal performance. A switch acts as a networks traffic cop: rather than transmitting all the packets it receives to all ports as a hub does, a switch transmits packets to only the receiving port.

TCP

A protocol used along with the Internet Protocol (IP) to send data in the form of individual units (called packets) between computers over the Internet. While IP takes care of handling the actual delivery of the data, TCP takes care of keeping track of the packets that a message is divided into for efficient routing through the Internet. For example, when a web page is downloaded from a web server, the TCP program layer in that server divides the file into packets, numbers the packets and then forwards them individually to the IP program layer. Although each packet has the same destination IP address, it may get routed differently through the network. At the other end, TCP reassembles the individual packets and waits until they have all arrived to forward them as a single file.

TCP/IP

The underlying technology behind the Internet and communications between computers in a network. The first part, TCP, is the transport part, which matches the size of the messages on either end and guarantees that the correct message has been received. The IP part is the user's computer address on a network. Every computer in a TCP/IP network has its own IP address that is either dynamically assigned at startup or permanently assigned. All TCP/IP messages contain the address of the destination network as well as the address of the destination station. This enables TCP/IP messages to be transmitted to multiple networks (subnets) within an organization or worldwide.

Transmit Power

The power usually expressed in mW or db that the wireless device transmits at.

VolP

Voice transmission using Internet Protocol to create digital packets distributed over the Internet. VoIP can be less expensive than voice transmission using standard analog packets over POTS (Plain Old Telephone Service).

VPN

A type of technology designed to increase the security of information transferred over the Internet. VPN can work with either wired or wireless networks, as well as with dial-up connections over POTS. VPN creates a private encrypted tunnel from the end user's computer, through the local wireless network, through the Internet, all the way to the corporate servers and database.

WAN

A communication system of connecting PCs and other computing devices across a large local, regional, national or international geographic area Also used to distinguish between phone-based data networks and Wi-Fi. Phone networks are considered WANs and Wi-Fi networks are considered Wireless Local Area Networks (WLANs).

WEP

Basic wireless security provided by Wi-Fi. In some instances, WEP may be all a home or small-business user needs to protect wireless data. WEP is available in 40-bit (also called 64-bit), or in 108-bit (also called 128-bit) encryption modes. As 108-bit encryption provides a longer algorithm that takes longer to decode, it can provide better security than basic 40-bit (64-bit) encryption.

Wi-Fi

Wireless Fidelity: An interoperability certification for wireless local area network (LAN) products based on the Institute of Electrical and Electronics Engineers (IEEE) 802.11 standard.

Notes	

Weidmüller - Partner in Industrial Connectivity

As experienced experts we support our customers and partners around the world with products, solutions and services in the industrial environment of power, signal and data. We are at home in their industries and markets and know the technological challenges of tomorrow. We are therefore continuously developing innovative, sustainable and useful solutions for their individual needs. Together we set standards in Industrial Connectivity.

Weidmuller, Canada

10 Spy Court Markham, Ontario L3R 5H6 Telephone: (800) 268-4080 Facsimile: (877) 300-5635 Email: info1@weidmuller.ca Website: www.weidmuller.ca

Weidmuller, Mexico

Blvd. Hermanos Serdán 698, Col. San Rafael Oriente Puebla, Puebla, Mexico C.P. 72029

Telephone: 01 222 2686267 Facsimile: 01 222 2686219 Email: clientes@weidmuller.com.mx Website: www.weidmuller.com.mx

Weidmuller, United States

821 Southlake Blvd. Richmond, Virginia 23236 Telephone: (800) 849-9343 Facsimile: (804) 379-2593 Email: info@weidmuller.com Website: www.weidmuller.com